

Network Working Group  
Request for Comments: 1593  
Category: Informational

W. McKenzie  
J. Cheng  
IBM Networking Systems  
March 1994

## SNA APPN Node MIB

### Status of this Memo

This memo provides information for the Internet community. This memo does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

### Abstract

This RFC describes IBM's SNMP support for SNA Advanced Peer-to-Peer Networking (APPN) nodes.

### Table of Contents

1.0	Introduction	2
2.0	Definitions	3
2.1	APPN Node Group	3
2.1.1	APPN Node General Information	4
2.1.2	APPN Network Node Information	6
2.1.3	APPN End Node Information	8
2.1.4	APPN Port Information	10
2.1.4.1	General Port Information	10
2.1.4.2	TCP/IP Port Information	14
2.1.4.3	Data Link Switch Port Information	15
2.1.4.4	Token Ring Port Information	16
2.1.4.5	Port DLC Trace Information	17
2.1.5	APPN Link Station Information	23
2.1.5.1	General Link Station Information	23
2.1.5.2	TCP/IP Link Station Information	35
2.1.5.3	Data Link Switch Link Station Information	37
2.1.5.4	Token Ring Link Station Information	39
2.1.5.5	Link Station Status Information	41
2.1.6	SNMP Performance Information for APPN Subagent	46
2.1.7	Performance Information for APPN Node	49
2.1.8	XID Statistics	50
2.2	APPN Topology Group	51
2.2.1	Topology Performance Information	52
2.2.1.1	Topology Route Information	58
2.2.2	Adjacent Node Table	60
2.2.3	Network Node Topology	62
2.2.3.1	NN Topology Table (Indexed by Node Name)	62

2.2.3.2	NN TG Table (Indexed by Node Names and TG Number)	66
2.2.3.3	NN Topology Table (Indexed by FRSN and Node Name)	73
2.2.3.4	NN TG Table (Indexed by FRSN, Node Names, and TG Number) . . . . .	77
2.3	APPN Node Local Topology Group . . . . .	83
2.3.1	Local Topology This Node . . . . .	84
2.3.1.1	Local General Information . . . . .	84
2.3.1.2	Local NN Specific Information . . . . .	85
2.3.1.3	Local TG Information . . . . .	87
2.3.2	Client End Nodes Topology Known to Serving NN . . . . .	93
2.3.2.1	Client End Nodes Information . . . . .	93
2.3.2.2	Client End Nodes TG Information (Tail Vectors) . . . . .	94
2.4	APPN Directory Group . . . . .	99
2.4.1	Directory Performance Information . . . . .	99
2.4.2	Directory Cache Table . . . . .	102
2.5	APPN Class Of Service Group . . . . .	105
2.5.1	COS Mode Table . . . . .	108
2.5.2	COS Name Table . . . . .	109
2.5.3	COS Node Row Table . . . . .	110
2.5.4	COS TG Row Table . . . . .	113
3.0	Acknowledgements . . . . .	119
4.0	Security Considerations . . . . .	119
5.0	Authors' Addresses . . . . .	120

## 1.0 Introduction

This module contains managed objects which describe the following:

- o The APPN node (either an APPN network node or an APPN end node)
- o The connections of the node to other SNA nodes
- o The APPN network topology (as reflected in the network topology database that is replicated in each APPN network node).

This module does not describe the SNA logical units (LUs) served by the APPN node nor does it describe the sessions between LUs. Managed objects for that information are under development.

## 2.0 Definitions

```

IBM-6611-APPN-MIB DEFINITIONS      ::= BEGIN

IMPORTS

    enterprises, Counter, IpAddress,
    Gauge, TimeTicks
        FROM RFC1155-SMI

    DisplayString
        FROM RFC1213-MIB

OBJECT-TYPE
    FROM RFC-1212;

-- *****
ibm                                OBJECT IDENTIFIER ::= { enterprises 2 }
ibmProd                            OBJECT IDENTIFIER ::= { ibm 6 }
ibm6611                            OBJECT IDENTIFIER ::= { ibmProd 2 }
ibmappn                            OBJECT IDENTIFIER ::= { ibm6611 13 }

-- ***** The APPN Node Group *****
ibmappnNode                         OBJECT IDENTIFIER ::= { ibmappn 1 }
ibmappnGeneralInfoAndCaps           OBJECT IDENTIFIER ::= { ibmappnNode 1 }
ibmappnNnUniqueInfoAndCaps          OBJECT IDENTIFIER ::= { ibmappnNode 2 }
ibmappnEnUniqueCaps                OBJECT IDENTIFIER ::= { ibmappnNode 3 }
ibmappnPortInformation              OBJECT IDENTIFIER ::= { ibmappnNode 4 }
ibmappnLinkStationInformation       OBJECT IDENTIFIER ::= { ibmappnNode 5 }
ibmappnSnmpInformation             OBJECT IDENTIFIER ::= { ibmappnNode 6 }
ibmappnMemoryUse                   OBJECT IDENTIFIER ::= { ibmappnNode 7 }
ibmappnXidInformation              OBJECT IDENTIFIER ::= { ibmappnNode 8 }

-- This group provides global information about the
-- APPN node, which is either a network node or an end node.

-- The first section applies to all APPN nodes.
-- The second section applies only to network nodes.
-- The third section applies only to end nodes.
-- The fourth section applies to Port information.
-- The fifth section applies to SNA link station Information.
-- The sixth section applies to SNMP traffic for this APPN sub-agent
-- The seventh section applies to APPN memory usage.
-- The eighth section applies to XID activities.

```

```
-- APPN General Information
-- This section applies to both network and end nodes.

ibmappnNodeCpName    OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned network name
         for this node in the format NETID.CPNAME."
    ::= { ibmappnGeneralInfoAndCaps 1 }

ibmappnNodeNetid     OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned APPN network identification,
         which can be from one to eight characters.
         This ID is used with the control point name
         to create a fully-qualified control point name."
    ::= { ibmappnGeneralInfoAndCaps 2 }

ibmappnNodeBlockNum   OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The block number is the first three digits of the node_id.
         These 3 hexadecimal digits identify the product and are not
         configurable."
    ::= { ibmappnGeneralInfoAndCaps 3 }

ibmappnNodeIdNum     OBJECT-TYPE
    SYNTAX DisplayString (SIZE (5))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The ID number is the last 5 digits of the node_id.
         These 5 hexadecimal digits are administratively defined and
         combined with the 3 digit block number form the node_id.
         This node_id is used to identify the local node and is
         include in APPN alerts as well as being included in XIDs.
         A unique value is required for connections to SNA"
```

```

    sub-area.

 ::= { ibmappnGeneralInfoAndCaps 4 }

ibmappnNodeType OBJECT-TYPE
SYNTAX INTEGER {
    networkNode(1),
    endNode(2),
    len(4)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Type of APPN node, either network, len, or end node."

 ::= { ibmappnGeneralInfoAndCaps 5 }

ibmappnNodeUpTime OBJECT-TYPE
SYNTAX TimeTicks
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Time (in hundredths of a second) since this APPN node
     was initialized.

 ::= { ibmappnGeneralInfoAndCaps 6 }

ibmappnNodeNegotLs OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports negotiable
     link stations.

 ::= { ibmappnGeneralInfoAndCaps 7 }

ibmappnNodeSegReasm OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports segment
     reassembly. This is only supported when
     segment generation is also supported.

 ::= { ibmappnGeneralInfoAndCaps 8 }

```

```

ibmappnNodeBindReasm OBJECT-TYPE
  SYNTAX INTEGER {yes(1), no(2)}
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Indicates whether this node supports Bind segment
     reassembly. This will only be supported when Bind
     segment generation is also supported."
  ::= { ibmappnGeneralInfoAndCaps 9 }

ibmappnNodeParallelTg   OBJECT-TYPE
  SYNTAX INTEGER {yes(1), no(2)}
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Indicates whether this node supports parallel TGS."
  ::= { ibmappnGeneralInfoAndCaps 10 }

ibmappnNodeService      OBJECT-TYPE
  SYNTAX INTEGER {yes(1), no(2)}
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Indicates whether this node allows call-in from nodes not
     defined locally."
  ::= { ibmappnGeneralInfoAndCaps 11 }

ibmappnNodeAdaptiveBindPacing  OBJECT-TYPE
  SYNTAX INTEGER {yes(1), no(2)}
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Indicates whether this node supports adaptive bind pacing."
  ::= { ibmappnGeneralInfoAndCaps 12 }

-- ****
-- APPN Network Node Information
-- This section provides global information about the
-- APPN network node.

ibmappnNodeNnRcvRegChar OBJECT-TYPE
  SYNTAX INTEGER {yes(1), no(2)}

```

```

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports receiving registered
     characteristics."
 ::= { ibmappnNnUniqueInfoAndCaps 1 }

ibmappnNodeNnGateway      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this is a gateway node."
 ::= { ibmappnNnUniqueInfoAndCaps 2 }

ibmappnNodeNnCentralDirectory  OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports central directory
     cache."
 ::= { ibmappnNnUniqueInfoAndCaps 3 }

ibmappnNodeNnTreeCache  OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports route tree cache."
 ::= { ibmappnNnUniqueInfoAndCaps 4 }

ibmappnNodeNnTreeUpdate  OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node supports
     incremental_tree_update, which is only
     supported when tree caching is supported."
 ::= { ibmappnNnUniqueInfoAndCaps 5 }

ibmappnNodeNnRouteAddResist   OBJECT-TYPE

```

```

SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Route addition resistance is a value that
    indicates the relative desirability
    of using this node for intermediate session traffic.
    The value, which can be any integer 0-255,
    is used in route computation. The lower the value,
    the more desirable the node is for intermediate routing."

 ::= { ibmappnNnUniqueInfoAndCaps 6 }

ibmappnNodeNnIsr      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node supports intermediate
    session routing."

 ::= { ibmappnNnUniqueInfoAndCaps 7 }

ibmappnNodeNnFrsn      OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Flow reduction sequence numbers (FRSNs) are associated
    with Topology Database Updates (TDUs) and are unique
    only within each APPN network node. A TDU can be
    associated with multiple APPN resources. This object
    is the last FRSN sent in a topology update to
    adjacent network nodes."

 ::= { ibmappnNnUniqueInfoAndCaps 8 }

-- ****
-- APPN End Node Information

ibmappnNodeEnSegGen    OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this end node supports segment generation."

```

```

 ::= { ibmappnEnUniqueCaps 1 }

ibmappnNodeEnModeCosMap OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether this end node supports
         mode name to COS name mapping."

 ::= { ibmappnEnUniqueCaps 2 }

ibmappnNodeEnLocateCdinit OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether this end node supports Locate Cdinit."

 ::= { ibmappnEnUniqueCaps 3 }

ibmappnNodeEnSendRegNames OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node will register its LUs with the
         adjacent serving network node:

          NO - do not register names
          YES - register names"

 ::= { ibmappnEnUniqueCaps 4 }

ibmappnNodeEnSendRegChar OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether this node supports
         send register characteristics, which is only
         supported when send registered names is also
         supported."

 ::= { ibmappnEnUniqueCaps 5 }

```

```

-- ****
-- APPN Port information
--

ibmappnNodePortTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodePortEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "The Port table describes the configuration and current
         status of the ports used by APPN. The type of DLC is
         included in this table as a pointer to the DLC port
         specific tables."
    ::= { ibmappnPortInformation 1 }

ibmappnNodePortEntry OBJECT-TYPE
    SYNTAX IbmappnNodePortEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "The Port Name is used as the index to this table."

INDEX
    { ibmappnNodePortName }

    ::= { ibmappnNodePortTable 1 }

IbmappnNodePortEntry ::= SEQUENCE {
    ibmappnNodePortName          DisplayString,
    ibmappnNodePortState         INTEGER,
    ibmappnNodePortDlcType       INTEGER,
    ibmappnNodePortPortType      INTEGER,
    ibmappnNodePortSIMRIM        INTEGER,
    ibmappnNodePortLsRole        INTEGER,
    ibmappnNodePortMaxRcvBtuSize INTEGER,
    ibmappnNodePortMaxIframeWindow INTEGER,
    ibmappnNodePortDefLsGoodXids Counter,
    ibmappnNodePortDefLsBadXids Counter,
    ibmappnNodePortDynLsGoodXids Counter,
    ibmappnNodePortDynLsBadXids Counter,
    ibmappnNodePortSpecific      OBJECT IDENTIFIER
}

ibmappnNodePortName OBJECT-TYPE

```

```

SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for this APPN port.
     The name can be from one to eight characters."
::= { ibmappnNodePortEntry 1 }

ibmappnNodePortState      OBJECT-TYPE
SYNTAX INTEGER {
    inactive(1),
    pendactive(2),
    active(3),
    pendinact(4)
}
ACCESS read-write
STATUS mandatory
DESCRIPTION
    "Indicates the current state of this port."
::= { ibmappnNodePortEntry 2 }

ibmappnNodePortDlcType OBJECT-TYPE
SYNTAX INTEGER {
    other(1),          -- none of the following
    sdlc(2),
    dls(3),
    socket(4),
    ethernet(5),
    tokenRing(6)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The type of DLC interface, distinguished according
     to the protocol immediately 'below' this layer."
::= { ibmappnNodePortEntry 3 }

ibmappnNodePortPortType OBJECT-TYPE
SYNTAX INTEGER {
    leased(1),
    switched(2),
    sharedAccessFacilities(3)
}
ACCESS read-only
STATUS mandatory

```

```

DESCRIPTION
    "Identifies the type of line used by this port."
 ::= { ibmappnNodePortEntry 4 }

ibmappnNodePortSIMRIM OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether Set Initialization Mode (SIM) and
     Receive Initialization Mode (RIM) are supported."
 ::= { ibmappnNodePortEntry 5 }

ibmappnNodePortLsRole OBJECT-TYPE
SYNTAX INTEGER {
    primary(1),
    secondary(2),
    negotiable(3),
    abm(4)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Initial role for LSS activated through this port,
     where 'abm' indicates asynchronous balance mode."
 ::= { ibmappnNodePortEntry 6 }

ibmappnNodePortMaxRcvBtuSize OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum Basic Transmission Size (BTU) that a
     link station on this port can receive."
 ::= { ibmappnNodePortEntry 7 }

ibmappnNodePortMaxIframeWindow OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum number of I-frames that can be received
     by the XID sender before an acknowledgement is received."

```

```

 ::= { ibmappnNodePortEntry 8 }

ibmappnNodePortDefLsGoodXids      OBJECT-TYPE
SYNTAX  Counter
ACCESS  read-only
STATUS  mandatory
DESCRIPTION
        "The total number of successfull XIDs that have occurred
        on all defined link stations on this port since the last
        time this port was started."

 ::= { ibmappnNodePortEntry 9 }

ibmappnNodePortDefLsBadXids      OBJECT-TYPE
SYNTAX  Counter
ACCESS  read-only
STATUS  mandatory
DESCRIPTION
        "The total number of unsuccessfull XIDs that have occurred
        on all defined link stations on this port since the last
        time this port was started."

 ::= { ibmappnNodePortEntry 10 }

ibmappnNodePortDynLsGoodXids      OBJECT-TYPE
SYNTAX  Counter
ACCESS  read-only
STATUS  mandatory
DESCRIPTION
        "The total number of successfull XIDs that have occurred
        on all dynamic link stations on this port since the last
        time this port was started."

 ::= { ibmappnNodePortEntry 11 }

ibmappnNodePortDynLsBadXids      OBJECT-TYPE
SYNTAX  Counter
ACCESS  read-only
STATUS  mandatory
DESCRIPTION
        "The total number of unsuccessfull XIDs that have occurred
        on all dynamic link stations on this port since the last
        time this port was started."

 ::= { ibmappnNodePortEntry 12 }

ibmappnNodePortSpecific OBJECT-TYPE
SYNTAX OBJECT IDENTIFIER

```

```
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Identifies the port specific OBJECT IDENTIFIER
     that can provide additional information."
 ::= { ibmappnNodePortEntry 13 }

-- ****
-- 
-- 

ibmappnNodePortIpTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNodePortIpEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "Port table (TCP/IP specific)."
 ::= { ibmappnPortInformation 2 }

ibmappnNodePortIpEntry OBJECT-TYPE
SYNTAX IbmappnNodePortIpEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The IP Name is used as the index to this table."

INDEX
{ ibmappnNodePortIpName }
 ::= { ibmappnNodePortIpTable 1 }

IbmappnNodePortIpEntry ::= SEQUENCE {
    ibmappnNodePortIpName          DisplayString,
    ibmappnNodePortIpPortNum       INTEGER
}

ibmappnNodePortIpName OBJECT-TYPE
SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for this APPN port.
     The name can be from one to eight characters."
```

```

 ::= { ibmappnNodePortIpEntry 1 }

ibmappnNodePortIpPortNum OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Local TCP/IP port number."

 ::= { ibmappnNodePortIpEntry 2 }

-- ****
-- 
--

ibmappnNodePortDlsTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNodePortDlsEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "Port table (DLS specific)."

 ::= { ibmappnPortInformation 3 }

ibmappnNodePortDlsEntry OBJECT-TYPE
SYNTAX IbmappnNodePortDlsEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The DLS Name is used as the index to this table.

INDEX
    {ibmappnNodePortDlsName}

 ::= { ibmappnNodePortDlsTable 1 }

IbmappnNodePortDlsEntry ::= SEQUENCE {
    ibmappnNodePortDlsName          DisplayString,
    ibmappnNodePortDlsMac           OCTET STRING,
    ibmappnNodePortDlsSap           OCTET STRING
}

ibmappnNodePortDlsName OBJECT-TYPE
SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory

```

```

DESCRIPTION
    "Administratively-assigned name for this APPN DLS port.
     The name can be from one to eight characters."
 ::= { ibmappnNodePortDlsEntry 1 }

ibmappnNodePortDlsMac OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (6))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local DLS MAC address."
 ::= { ibmappnNodePortDlsEntry 2 }

ibmappnNodePortDlsSap OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (1))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local DLS Sap address."
 ::= { ibmappnNodePortDlsEntry 3 }

-- ****
-- 
-- 

ibmappnNodePortTrTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodePortTrEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Port table (Token Ring specific)."
 ::= { ibmappnPortInformation 4 }

ibmappnNodePortTrEntry OBJECT-TYPE
    SYNTAX IbmappnNodePortTrEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "The TR Name is used as the index to this table."

INDEX
    {ibmappnNodePortTrName }
```

```

 ::= { ibmappnNodePortTrTable 1 }

IbmappnNodePortTrEntry ::= SEQUENCE {
    ibmappnNodePortTrName          DisplayString,
    ibmappnNodePortTrMac           OCTET STRING,
    ibmappnNodePortTrSap           OCTET STRING
}

ibmappnNodePortTrName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for this APPN port.
         The name can be from one to eight characters."

 ::= { ibmappnNodePortTrEntry 1 }

ibmappnNodePortTrMac OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (6))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local Token Ring MAC address."

 ::= { ibmappnNodePortTrEntry 2 }

ibmappnNodePortTrSap OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (1))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local Token Ring Sap address.

 ::= { ibmappnNodePortTrEntry 3 }

-- ****
-- APPN generic DLC Trace
--

ibmappnNodePortDlcTraceTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodePortDlcTraceEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Port table generic DLC trace table."

```

```

 ::= { ibmappnPortInformation 5 }

ibmappnNodePortDlcTraceEntry OBJECT-TYPE
SYNTAX IbmapnNodePortDlcTraceEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The Port name and a dynamic integer are the index to
this table."

INDEX
    {ibmappnNodePortDlcTracPortName,
     ibmappnNodePortDlcTracIndex}

 ::= { ibmappnNodePortDlcTraceTable 1 }

IbmappnNodePortDlcTraceEntry ::= SEQUENCE {
    ibmappnNodePortDlcTracPortName      DisplayString,
    ibmappnNodePortDlcTracIndex        INTEGER,
    ibmappnNodePortDlcTracDlcType     INTEGER,
    ibmappnNodePortDlcTracLocalAddr   DisplayString,
    ibmappnNodePortDlcTracRemoteAddr  DisplayString,
    ibmappnNodePortDlcTracMsgType    INTEGER,
    ibmappnNodePortDlcTracCmdType    INTEGER,
    ibmappnNodePortDlcTracUseWan    INTEGER
}

ibmappnNodePortDlcTracPortName OBJECT-TYPE
SYNTAX DisplayString
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The Port name associated with this this trace table entry."

 ::= { ibmappnNodePortDlcTraceEntry 1 }

ibmappnNodePortDlcTracIndex OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This index value is updated every time a new trace entry
is created which provides a means to retrieve only the
updated entries and also provides a simple method of
correlating the entries. The table will wrap when the
table is full, which will result in previous entries
being written over. The management station can over
come this by retrieving the table using this index to

```

```

retrieve only the new table entries."}

::= { ibmappnNodePortDlcTraceEntry 2 }

ibmappnNodePortDlcTracDlcType OBJECT-TYPE
SYNTAX INTEGER {
    other(1),                      -- none of the following
    sdlc(2),
    dls(3),
    socket(4),
    ethernet(5),
    tokenRing(6)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The type of DLC interface, distinguished according
     to the protocol immediately 'below' this layer."

::= { ibmappnNodePortDlcTraceEntry 3 }

ibmappnNodePortDlcTracLocalAddr OBJECT-TYPE
SYNTAX DisplayString
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Local address in format described below:

        other      = free form DisplayString
        ip         = ld. ld. ld. ld / 2d
        tr         = lx: lx: lx: lx: lx: lx . lx
        dls        = lx: lx: lx: lx: lx: lx . lx
        ethernet  = lx: lx: lx: lx: lx: lx . lx
        "
    "

::= { ibmappnNodePortDlcTraceEntry 4 }

ibmappnNodePortDlcTracRemoteAddr OBJECT-TYPE
SYNTAX DisplayString
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Remote Address in the format described below:
        other      = free form DisplayString
        ip         = ld. ld. ld. ld / 2d
        tr         = lx: lx: lx: lx: lx: lx . lx
        dls        = lx: lx: lx: lx: lx: lx . lx"

```

```

        ethernet = lx: lx: lx: lx: lx: lx . lx
        "
        ::= { ibmappnNodePortDlcTraceEntry 5 }

ibmappnNodePortDlcTracMsgType OBJECT-TYPE
    SYNTAX INTEGER {
--          enumeration values between 1 and 1999 are reserved
--          for potential undefined message types.
--          other(1),
--          unknown(2),
--          request(3),
--          confirm(4),
--          indication(5),
--          response(6)

--          enumeration values between 2000 and 3999 are reserved
--          for IP socket traces,

--          enumeration values between 4000 and 5999 are reserved
--          for DLS traces,

--          enumeration values between 6000 and 7999 are reserved
--          for TR   traces,
}

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates the type of trace record entry"
 ::= { ibmappnNodePortDlcTraceEntry 6 }

ibmappnNodePortDlcTracCmdType OBJECT-TYPE
    SYNTAX INTEGER {
--          enumeration values between 1 and 1999 are reserved
--          for potential undefined message types.

          testFrame(1),
          respFrame(2),
          curFrame(3),
          icrFrame(4),
}

```

```
respAck(5),
dfrmFrame(6),
xidFrame(7),
contFrame(8),
contedFrame(9),
iFrame(10),
enterBusy(12),
exitBusy(13),
haltFrame(14),
lsHalted(15),
restartLs(16),
lsRestarted(17),
netBioSnq(18),
netBioSnr(19),
gnetFrame(20),
netdFrame(21),
oobFrame(22),
alterSap(23),
testRsp(24),
haltLsNow(25),
testReq(26),

-- enumeration values between 2000 and 3999 are reserved
-- for IP socket traces.
ipTestFrame(2001),
ipRespFrame(2002),
ipCurFrame(2003),
ipIcrFrame(2004),
ipRespAck(2005),
ipDfrmFrame(2006),
ipXidFrame(2007),
ipContFrame(2008),
ipContedFrame(2009),
ipIFrame(2010),
ipEnterBusy(2012),
ipExitBusy(2013),
ipHaltFrame(2014),
ipLsHalted(2015),
ipRestartLs(2016),
ipLsRestarted(2017),
ipNetBioSnq(2018),
ipNetBioSnr(2019),
ipGnetFrame(2020),
ipNetdFrame(2021),
ipOobFrame(2022),
ipAlterSap(2023),
ipTestRsp(2024),
ipHaltLsNow(2025),
```

```

        ipTestReq(2026),

-- enumeration values between 4000 and 5999 are reserved
-- for DLS traces.

        dlsIpM(4124),

-- enumeration values between 6000 and 7999 are reserved for
-- TR traces.
        trTestFrame(6001),
        trRespFrame(6002),
        trCurFrame(6003),
        trIcrFrame(6004),
        trRespAck(6005),
        trDgrmFrame(6006),
        trXidFrame(6007),
        trContFrame(6008),
        trContedFrame(6009),
        trIFrame(6010),
        trEnterBusy(6012),
        trExitBusy(6013),
        trHaltFrame(6014),
        trLsHalted(6015),
        trRestartLs(6016),
        trLsRestarted(6017),
        trNetBioSnq(6018),
        trNetBioSnr(6019),
        trGnetFrame(6020),
        trNetdFrame(6021),
        trOobFrame(6022),
        trAlterSap(6023),
        trTestRsp(6024),
        trHaltLsNow(6025),
        trTestReq(6026)

    }

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates the command type of the trace entry."
::= { ibmappnNodePortDlcTraceEntry 7 }

ibmappnNodePortDlcTracUseWan OBJECT-TYPE
    SYNTAX INTEGER {
        other(1),
        notApplicable(2),
        useUnknown(3),

```

```

        useWan(4),
        useLan(5)
    }

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates the type of connection of the trace entry.
    For example, token ring and ethernet ports will have
    useLan as connection. For the dls port, it could be
    either useWan if connection is across Wan via dls
    sessions, or useLan if connection is to a local attached
    LAN."
::= { ibmappnNodePortDlcTraceEntry 8 }

-- ****
-- APPN Link Station Information
--

ibmappnNodeLsTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodeLsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This table contains detail information about the
        link station configuration and current status."
::= { ibmappnLinkStationInformation 1 }

ibmappnNodeLsEntry OBJECT-TYPE
    SYNTAX IbmappnNodeLsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This table is indexed by the link station name."

INDEX
    { ibmappnNodeLsName }

::= { ibmappnNodeLsTable 1 }

IbmappnNodeLsEntry ::= SEQUENCE {
    ibmappnNodeLsName          DisplayString,
    ibmappnNodeLsPortName       DisplayString,
    ibmappnNodeLsDlcType        INTEGER,
}

```

```

        ibmappnNodeLsDynamic          INTEGER,
        ibmappnNodeLsState            INTEGER,
-- ls defined data / xid info
        ibmappnNodeLsCpName          DisplayString,
        ibmappnNodeLsTgNum            INTEGER,
        ibmappnNodeLsLimResource     INTEGER,
        ibmappnNodeLsMigration       INTEGER,
        ibmappnNodeLsBlockNum         DisplayString,
        ibmappnNodeLsIdNum           DisplayString,
        ibmappnNodeLsCpCpSession     INTEGER,
-- ls parms (common) / xid info
        ibmappnNodeLsTargetPacingCount INTEGER,
        ibmappnNodeLsMaxSendBtuSize  INTEGER,
-- tg characteristics
        ibmappnNodeLsEffCap          INTEGER,
        ibmappnNodeLsConnCost         INTEGER,
        ibmappnNodeLsByteCost         INTEGER,
        ibmappnNodeLsSecurity         INTEGER,
        ibmappnNodeLsDelay            INTEGER,
        ibmappnNodeLsUsr1             INTEGER,
        ibmappnNodeLsUsr2             INTEGER,
        ibmappnNodeLsUsr3             INTEGER,
-- ls (performance data)
        ibmappnNodeLsInXidBytes      Counter,
        ibmappnNodeLsInMsgBytes       Counter,
        ibmappnNodeLsInXidFrames     Counter,
        ibmappnNodeLsInMsgFrames     Counter,
        ibmappnNodeLsOutXidBytes     Counter,
        ibmappnNodeLsOutMsgBytes      Counter,
        ibmappnNodeLsOutXidFrames    Counter,
        ibmappnNodeLsOutMsgFrames    Counter,
-- ls (propagation delay)
        ibmappnNodeLsEchoRsp          Counter,
        ibmappnNodeLsCurrentDelay     INTEGER,
        ibmappnNodeLsMaxDelay         INTEGER,
        ibmappnNodeLsMinDelay         INTEGER,
        ibmappnNodeLsMaxDelayTime    TimeTicks,
-- ls (Xid Statistics)
        ibmappnNodeLsGoodXids         Counter,
        ibmappnNodeLsBadXids          Counter,
-- Dlc specific
        ibmappnNodeLsSpecific          OBJECT IDENTIFIER,
        ibmappnNodeLsSubState          INTEGER,
        ibmappnNodeLsStartTime         TimeTicks,
        ibmappnNodeLsActiveTime        TimeTicks,
        ibmappnNodeLsCurrentStateTime TimeTicks
    }
}

```

```

ibmappnNodeLsName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for the link station.
         The name can be from one to eight characters."
    ::= { ibmappnNodeLsEntry 1 }

ibmappnNodeLsPortName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for the port.
         The name can be from one to eight characters."
    ::= { ibmappnNodeLsEntry 2 }

ibmappnNodeLsDlcType OBJECT-TYPE
    SYNTAX INTEGER {
        other(1),                      -- none of the following
        sdlc(2),
        dls(3),
        socket(4),
        ethernet(5),
        tokenRing(6)
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The type of DLC interface, distinguished according
         to the protocol immediately 'below' this layer."
    ::= { ibmappnNodeLsEntry 3 }

ibmappnNodeLsDynamic OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Identifies whether this resource is a dynamic link station.
         Dynamic link stations are created when adjacent nodes
         that have not been locally defined establish a connection
         with this node."

```

```

 ::= { ibmappnNodeLsEntry 4 }

ibmappnNodeLsState      OBJECT-TYPE
SYNTAX INTEGER          {
    inactive(1),
    pendactive(2),
    active(3),
    pendinact(4)
}
ACCESS read-write
STATUS mandatory
DESCRIPTION
    "State of this link station.

 ::= { ibmappnNodeLsEntry 5 }

ibmappnNodeLsCpName     OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Fully-qualified name of the adjacent node for this link
    station. The name can be from three to seventeen
    characters. Format is netid.cpname.

 ::= { ibmappnNodeLsEntry 6 }

ibmappnNodeLsTgNum      OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number associated with the TG to this link station.

 ::= { ibmappnNodeLsEntry 7 }

ibmappnNodeLsLimResource OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the link station is
    a limited resource. If it is, the TG
    is deactivated when there are no sessions.

 ::= { ibmappnNodeLsEntry 8 }

```

```

ibmappnNodeLsMigration OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether this link station will be used
         for connections to down-level or migration partners."
    ::= { ibmappnNodeLsEntry 9 }

ibmappnNodeLsBlockNum OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The block number is the first three digits of the node_id.
         These 3 hexidecimal digits identify the product and are not
         configurable."
    ::= { ibmappnNodeLsEntry 10 }

ibmappnNodeLsIdNum OBJECT-TYPE
    SYNTAX DisplayString (SIZE (5))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The ID number is the last 5 digits of the node_id.
         These 5 hexadecimal digits are administratively defined and
         combined with the 3 digit block number form the node_id.
         This node_id is used to identify the local node and is
         include in APPN alerts as well as being included in XIDs.
         A unique value is required for connections to SNA
         sub-area."
    ::= { ibmappnNodeLsEntry 11 }

ibmappnNodeLsCpCpSession OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether CP-CP sessions are
         supported by this link station."
    ::= { ibmappnNodeLsEntry 12 }

ibmappnNodeLsTargetPacingCount OBJECT-TYPE
    SYNTAX INTEGER

```

```
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Numeric value between 0 and 32767 inclusive indicating
     the desired pacing window size for BINDS on this TG.
     The number is significant only when fixed bind pacing
     is being performed."
 ::= { ibmappnNodeLsEntry 13 }

ibmappnNodeLsMaxSendBtuSize OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Numeric value between 0 and 32767 inclusive indicating
     the desired number of bytes in a Basic Transmission Unit
     (BTU) that can be sent on this TG.
     This is an administratively assigned value."
 ::= { ibmappnNodeLsEntry 14 }

ibmappnNodeLsEffCap OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The effective capacity is an integer value that indicates
     the kilo bits per second.
     It is derived from the link bandwidth and maximum load
     factor with the range of 0 thru 603,979,776.
     This is an administratively assigned value associated
     with the TG using this link station."
 ::= { ibmappnNodeLsEntry 15 }

ibmappnNodeLsConnCost OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Cost per connect time: a value representing
     the relative cost per unit of time to use
     the TG. Range is from 0, which means no cost,
     to 255, which indicates maximum cost.
     This is an administratively assigned value associated
     with the TG using this link station."
```

```

 ::= { ibmappnNodeLsEntry 16 }

ibmappnNodeLsByteCost OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative cost of transmitting a byte over this link.
     Range is from 0 (lowest cost) to 255.
     This is an administratively assigned value associated
     with the TG using this link station."

 ::= { ibmappnNodeLsEntry 17 }

ibmappnNodeLsSecurity OBJECT-TYPE
SYNTAX INTEGER {
    nonsecure(1),          --X'01'
    publicSwitchedNetwork(32), --X'20'
    undergroundCable(64),    --X'40'
    secureConduit(96),      --X'60'
    guardedConduit(128),    --X'80'
    encrypted(160),         --X'A0'
    guardedRadiation(192)   --X'C0'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The security is represented as an integer with a range of
     1 thru 255 with the most common values enumerated as
     defined above.
     This is an administratively assigned value associated
     with the TG using this link station."

 ::= { ibmappnNodeLsEntry 18 }

ibmappnNodeLsDelay OBJECT-TYPE
SYNTAX INTEGER {
    minimum(0),           --X'00'
    negligible(384),       --X'4C'
    terrestrial(9216),     --X'71'
    packet(147456),        --X'91'
    long(294912),          --X'99'
    maximum(2013265920)   --X'FF'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative amount of time that it takes for a signal to

```

travel the length of the logical link. This time is represented in micro seconds, with some of the more common values enumerated.

This is an administratively assigned value associated with the TG using this link station."

```
::= { ibmappnNodeLsEntry 19 }
```

ibmappnNodeLsUsr1 OBJECT-TYPE

SYNTAX INTEGER (0..255)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"First user-defined TG characteristic for this TG with a range of 0-255.

This is an administratively assigned value associated with the TG using this link station."

```
::= { ibmappnNodeLsEntry 20 }
```

ibmappnNodeLsUsr2 OBJECT-TYPE

SYNTAX INTEGER (0..255)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"Second user-defined TG characteristic for this TG with a range of 0-255.

This is an administratively assigned value associated with the TG using this link station."

```
::= { ibmappnNodeLsEntry 21 }
```

ibmappnNodeLsUsr3 OBJECT-TYPE

SYNTAX INTEGER (0..255)

ACCESS read-only

STATUS mandatory

DESCRIPTION

"Third user-defined TG characteristic for this TG with a range of 0-255.

This is an administratively assigned value associated with the TG using this link station."

```
::= { ibmappnNodeLsEntry 22 }
```

ibmappnNodeLsInXidBytes OBJECT-TYPE

SYNTAX Counter

ACCESS read-only

STATUS mandatory

```
DESCRIPTION
    "Number of XID bytes received."
 ::= { ibmappnNodeLsEntry 23 }

ibmappnNodeLsInMsgBytes OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of message (I-frame) bytes received."
 ::= { ibmappnNodeLsEntry 24 }

ibmappnNodeLsInXidFrames OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of XID frames received."
 ::= { ibmappnNodeLsEntry 25 }

ibmappnNodeLsInMsgFrames OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of message (I-frame) frames received."
 ::= { ibmappnNodeLsEntry 26 }

ibmappnNodeLsOutXidBytes OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of XID bytes sent."
 ::= { ibmappnNodeLsEntry 27 }

ibmappnNodeLsOutMsgBytes OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of message (I-frame) bytes sent."
```

```
: := { ibmappnNodeLsEntry 28 }

ibmappnNodeLsOutXidFrames OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of XID frames sent."

: := { ibmappnNodeLsEntry 29 }

ibmappnNodeLsOutMsgFrames OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of message (I-frame) frames sent."

: := { ibmappnNodeLsEntry 30 }

ibmappnNodeLsEchoRspns OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of responses returned from adjacent link station.
         A response should be returned for each test frame sent by
         this node.
         Test frames are sent to adjacent nodes periodically to
         verify connectivity and to measure that actual round trip
         time, that is the time the test frame is sent until the
         response is received."

: := { ibmappnNodeLsEntry 31 }

ibmappnNodeLsCurrentDelay OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The time that it took for the last test signal to be
         sent and returned from this link station to the
         adjacent links station.
         This time is represented in milliseconds.

: := { ibmappnNodeLsEntry 32 }

ibmappnNodeLsMaxDelay OBJECT-TYPE
```

```

SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The longest time it took for a test signal
     to be sent and returned from this link station to the
     adjacent links station.
    This time is represented in milliseconds ."

 ::= { ibmappnNodeLsEntry 33 }

ibmappnNodeLsMinDelay      OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The shortest time it took for a test signal
     to be sent and returned from this link station to the
     adjacent links station.
    This time is represented in milliseconds ."

 ::= { ibmappnNodeLsEntry 34 }

ibmappnNodeLsMaxDelayTime  OBJECT-TYPE
SYNTAX TimeTicks
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The time (since system up in hundredth of seconds)
     when the longest delay occurred.
    This time can be used to identify when this high
     water mark occurred in relation to the last initialization
     of the APPN node ."

 ::= { ibmappnNodeLsEntry 35 }

ibmappnNodeLsGoodXids      OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The total number of successful XIDs that have occurred
     on this link station since the time it was started ."

 ::= { ibmappnNodeLsEntry 36 }

ibmappnNodeLsBadXids       OBJECT-TYPE
SYNTAX Counter

```

```
ACCESS  read-only
STATUS  mandatory
DESCRIPTION
    "The total number of unsuccessful XIDs that have occurred
     on this link station since the time it was started."
::= { ibmappnNodeLsEntry 37 }

ibmappnNodeLsSpecific  OBJECT-TYPE
SYNTAX OBJECT IDENTIFIER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Identifies the DLC specific OBJECT IDENTIFIER
     that can provide additional information."
::= { ibmappnNodeLsEntry 38 }

ibmappnNodeLsSubState      OBJECT-TYPE
SYNTAX INTEGER      {
    inactive(1),
    sentReqOpnstn(2),
    pendXidExch(3),
    sentActAs(4),
    sentSetMode(5),
    active(6),
    sentDeactAsOrd(7),
    sentDiscOrd(8),
    sentDestroyTg(9),
    sentCreateTg(10),
    sentConnReq(11),
    pendRcvConnInd(12),
    pendSendConnRsp(13),
    sentConnRsp(14),
    pendDeact(15)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "State of this link station."
::= { ibmappnNodeLsEntry 39 }

ibmappnNodeLsStartTime      OBJECT-TYPE
SYNTAX TimeTicks
ACCESS read-only
STATUS mandatory
DESCRIPTION
```

```

        "The time (in hundredth of seconds) this link station
        has been active the last time since the time APPN was
        initialized."
        ::= { ibmappnNodeLsEntry 40 }

ibmappnNodeLsActiveTime      OBJECT-TYPE
    SYNTAX TimeTicks
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The time (in hundredth of seconds) this link station
        has been in the active state.
        A zero value indicates the link station has never been
        active."
        ::= { ibmappnNodeLsEntry 41 }

ibmappnNodeLsCurrentStateTime  OBJECT-TYPE
    SYNTAX TimeTicks
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The time (in hundredth of seconds) the link station is
        in the current state."
        ::= { ibmappnNodeLsEntry 42 }

-- ****
-- Link station table (TCP/IP specific)
--

ibmappnNodeLsIpTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodeLsIpEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Link station table (TCP/IP specific)."
        ::= { ibmappnLinkStationInformation 2 }

ibmappnNodeLsIpEntry OBJECT-TYPE
    SYNTAX IbmappnNodeLsIpEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "The IP Name is used as the index to this table."

```

```

INDEX
    { ibmappnNodeLsIpName }

::= { ibmappnNodeLsIpTable 1 }

IbmappnNodeLsIpEntry ::= SEQUENCE {
    ibmappnNodeLsIpName           DisplayString,
    ibmappnNodeLsIpState          INTEGER,
    ibmappnNodeLsLocalIpAddr      IpAddress,
    ibmappnNodeLsLocalIpPortNum   INTEGER,
    ibmappnNodeLsRemoteIpAddr     IpAddress,
    ibmappnNodeLsRemoteIpPortNum  INTEGER
}

ibmappnNodeLsIpName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for this link station. The
         name can be from one to eight characters."
    ::= { ibmappnNodeLsIpEntry 1 }

ibmappnNodeLsIpState      OBJECT-TYPE
    SYNTAX INTEGER { inactive(1),
                     pendactive(2),
                     active(3),
                     pendinact(4) }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "State of this link station."
    ::= { ibmappnNodeLsIpEntry 2 }

ibmappnNodeLsLocalIpAddr  OBJECT-TYPE
    SYNTAX IpAddress
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local IP address."
    ::= { ibmappnNodeLsIpEntry 3 }

ibmappnNodeLsLocalIpPortNum OBJECT-TYPE

```

```
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Local TCP/IP port number.
    The default listening port will be administratively
    assigned and will dynamically change if this node
    initiates a session with adjacent node."
::= { ibmappnNodeLsIpEntry 4 }

ibmappnNodeLsRemoteIpAddr OBJECT-TYPE
    SYNTAX IpAddress
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Remote IP address."
::= { ibmappnNodeLsIpEntry 5 }

ibmappnNodeLsRemoteIpPortNum OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Remote TCP/IP port number."
::= { ibmappnNodeLsIpEntry 6 }

-- *****
-- Ls Table (DLS specific)
--

ibmappnNodeLsDlsTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNodeLsDlsEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Ls Table (DLS specific)."
::= { ibmappnLinkStationInformation 3 }

ibmappnNodeLsDlsEntry OBJECT-TYPE
    SYNTAX IbmappnNodeLsDlsEntry
```

```

ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The DLS Name is used as the index to this table."

INDEX
    { ibmappnNodeLsDlsName }

::= { ibmappnNodeLsDlsTable 1 }

IbmappnNodeLsDlsEntry ::= SEQUENCE {
    ibmappnNodeLsDlsName          DisplayString,
    ibmappnNodeLsDlsState         INTEGER,
    ibmappnNodeLsLocalDlsMac     OCTET STRING,
    ibmappnNodeLsLocalDlsSap     OCTET STRING,
    ibmappnNodeLsRemoteDlsMac    OCTET STRING,
    ibmappnNodeLsRemoteDlsSap    OCTET STRING
}

ibmappnNodeLsDlsName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for this link station.
        The name can be from one to eight characters."
    ::= { ibmappnNodeLsDlsEntry 1 }

ibmappnNodeLsDlsState      OBJECT-TYPE
    SYNTAX INTEGER {
        inactive(1),
        pendactive(2),
        active(3),
        pendinact(4)
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "State of this link station."
    ::= { ibmappnNodeLsDlsEntry 2 }

ibmappnNodeLsLocalDlsMac OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (6))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION

```

```

    "Local MAC address."
 ::= { ibmappnNodeLsDlsEntry 3 }

ibmappnNodeLsLocalDlsSap OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Local SAP address."

 ::= { ibmappnNodeLsDlsEntry 4 }

ibmappnNodeLsRemoteDlsMac OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (6))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Remote MAC address."

 ::= { ibmappnNodeLsDlsEntry 5 }

ibmappnNodeLsRemoteDlsSap OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Remote SAP address."

 ::= { ibmappnNodeLsDlsEntry 6 }

-- *****
-- Ls Table (Token Ring specific)
--

ibmappnNodeLsTrTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNodeLsTrEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "Ls Table (Token Ring specific)."
 ::= { ibmappnLinkStationInformation 4 }

ibmappnNodeLsTrEntry OBJECT-TYPE
SYNTAX IbmappnNodeLsTrEntry

```

```

ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The TR Name is used as the index to this table."
INDEX
    {ibmappnNodeLsTrName}

::= { ibmappnNodeLsTrTable 1 }

IbmappnNodeLsTrEntry ::= SEQUENCE {
    ibmappnNodeLsTrName          DisplayString,
    ibmappnNodeLsTrState         INTEGER,
    ibmappnNodeLsLocalTrMac     OCTET STRING,
    ibmappnNodeLsLocalTrSap     OCTET STRING,
    ibmappnNodeLsRemoteTrMac    OCTET STRING,
    ibmappnNodeLsRemoteTrSap    OCTET STRING
}

ibmappnNodeLsTrName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for this link station.
        The name can be from one to eight characters."
    ::= { ibmappnNodeLsTrEntry 1 }

ibmappnNodeLsTrState      OBJECT-TYPE
    SYNTAX INTEGER {
        inactive(1),
        pendactive(2),
        active(3),
        pendinact(4)
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "State of this link station."
    ::= { ibmappnNodeLsTrEntry 2 }

ibmappnNodeLsLocalTrMac OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (6))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Local MAC address."

```

```

 ::= { ibmappnNodeLsTrEntry 3 }

ibmappnNodeLsLocalTrSap OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Local SAP address."

 ::= { ibmappnNodeLsTrEntry 4 }

ibmappnNodeLsRemoteTrMac OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (6))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Remote MAC address."

 ::= { ibmappnNodeLsTrEntry 5 }

ibmappnNodeLsRemoteTrSap OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Remote SAP address."

 ::= { ibmappnNodeLsTrEntry 6 }

-- *****
-- This table provides information about errors this node encountered
-- with connections to adjacent nodes. This includes all exceptional
-- conditions encountered establishing connections and all exceptional
-- conditions that result in terminating the connection.
-- *****

ibmappnNodeLsStatusTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNodeLsStatusEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "This table contains information related to exceptional
    and potential exceptional conditions that occur during
    the activation, XID exchange, and termination of the
    connection."

 ::= { ibmappnLinkStationInformation 5 }

```

```

ibmappnNodeLsStatusEntry OBJECT-TYPE
SYNTAX IbmapnNodeLsStatusEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
  "This table is indexed by the LsStatusIndex, which is an
  integer that is continuously updated until it eventually
  wraps. This provides the management station the ability
  to retrieve only the updates to the table by using the
  standard GET NEXT."

INDEX
  { ibmappnNodeLsStatusIndex }

 ::= { ibmappnNodeLsStatusTable 1 }

IbmappnNodeLsStatusEntry ::= SEQUENCE {
  ibmappnNodeLsStatusIndex          INTEGER,
  ibmappnNodeLsStatusTime          TimeTicks,
  ibmappnNodeLsStatusLsName        DisplayString,
  ibmappnNodeLsStatusCpName        DisplayString,
  ibmappnNodeLsStatusNodeId        OCTET STRING,
  ibmappnNodeLsStatusTgNum         INTEGER,
  ibmappnNodeLsStatusGeneralSense OCTET STRING,
  ibmappnNodeLsStatusNofRetry     INTEGER,
  ibmappnNodeLsStatusEndSense     OCTET STRING,
  ibmappnNodeLsStatusXidLocalSense OCTET STRING,
  ibmappnNodeLsStatusXidRemoteSense OCTET STRING,
  ibmappnNodeLsStatusXidByteInError INTEGER,
  ibmappnNodeLsStatusXidBitInError INTEGER,
  ibmappnNodeLsStatusDlcType       INTEGER,
  ibmappnNodeLsStatusLocalAddr     DisplayString,
  ibmappnNodeLsStatusRemoteAddr    DisplayString
}

ibmappnNodeLsStatusIndex      OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
  "This index is continuous index this table."
 ::= { ibmappnNodeLsStatusEntry 1 }

ibmappnNodeLsStatusTime      OBJECT-TYPE
SYNTAX TimeTicks
ACCESS read-only

```

```
STATUS mandatory
DESCRIPTION
  "Time (in hundreds of a second) since this node was last
  initialized."
 ::= { ibmappnNodeLsStatusEntry 2 }

ibmappnNodeLsStatusLsName      OBJECT-TYPE
  SYNTAX DisplayString (SIZE (1..8))
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Administratively-assigned name for this link station."
 ::= { ibmappnNodeLsStatusEntry 3 }

ibmappnNodeLsStatusCpName      OBJECT-TYPE
  SYNTAX DisplayString (SIZE (3..17))
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Administratively-assigned fully-qualified name of the
    adjacent node partner. This will be provided when the
    adjacent node has been defined at this node or when the
    XID sequence has proceeded far enough to identify the
    adjacent node. A blank CP name will indicate the name is
    unknown."
 ::= { ibmappnNodeLsStatusEntry 4 }

ibmappnNodeLsStatusNodeId      OBJECT-TYPE
  SYNTAX OCTET STRING
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Adjacent Node id"
 ::= { ibmappnNodeLsStatusEntry 5 }

ibmappnNodeLsStatusTgNum      OBJECT-TYPE
  SYNTAX INTEGER (0..256)
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Number associated with the TG to this link station
    with a range from 0 to 256. A value of 256 indicates
```

the tg number has not been negotiated and is unknown at this time."

`::= { ibmappnNodeLsStatusEntry 6 }`

`ibmappnNodeLsStatusGeneralSense OBJECT-TYPE`  
SYNTAX OCTET STRING  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"The error sense code associated with the start sequence of activation of a link up to the beginning of the XID sequence."

`::= { ibmappnNodeLsStatusEntry 7 }`

`ibmappnNodeLsStatusNofRetry OBJECT-TYPE`  
SYNTAX INTEGER {  
 retry(1),  
 noretry(2)  
}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Indicates whether Node Operator Facility will retry the start request to activate the link."

`::= { ibmappnNodeLsStatusEntry 8 }`

`ibmappnNodeLsStatusEndSense OBJECT-TYPE`  
SYNTAX OCTET STRING  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"The sense code associated with the termination of the link connection to adjacent node. This includes all sense information included in the disconnect received from the lower layer DLCs and also sense information indicating the link termination originated by upper layer APPN components."

`::= { ibmappnNodeLsStatusEntry 9 }`

`ibmappnNodeLsStatusXidLocalSense OBJECT-TYPE`  
SYNTAX OCTET STRING  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"The error sense code associated with the rejection of the

```

        XID. "

 ::= { ibmappnNodeLsStatusEntry 10 }

ibmappnNodeLsStatusXidRemoteSense      OBJECT-TYPE
SYNTAX OCTET STRING
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The error sense code adjacent node returned to this node
     indicating the reason the XID was rejected."

 ::= { ibmappnNodeLsStatusEntry 11 }

ibmappnNodeLsStatusXidByteInError      OBJECT-TYPE
SYNTAX INTEGER      {
    na(1000)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This identifies the actual byte in the XID that caused the
     error. The value of zero (0) indicates that the variable
     has no meaning."

 ::= { ibmappnNodeLsStatusEntry 12 }

ibmappnNodeLsStatusXidBitInError      OBJECT-TYPE
SYNTAX INTEGER      {
    na(8)    -- not applicable
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This identifies the actual bit within the error byte of the
     XID. This only has meaning when the byte in error is
     greater than zero."

 ::= { ibmappnNodeLsStatusEntry 13 }

ibmappnNodeLsStatusDlcType   OBJECT-TYPE
SYNTAX INTEGER      {
    other(1),
    sdlc(2),
    dls(3),
    socket(4),
    ethernet(5),
    tr(6)
}

```

```

        }

ACCESS read-only
STATUS mandatory
DESCRIPTION
  "This identifies DLC type that was being used when error
  occurred. This also is used to the format of the
  local and remote address provided.

  other    = free form DisplayString

  ip      = ld. ld. ld. ld / 2d

  tr      = lx: lx: lx: lx: lx: lx . lx

  dlsw    = lx: lx: lx: lx: lx: lx . lx

  ethernet = lx: lx: lx: lx: lx: lx . lx

  "

::= { ibmappnNodeLsStatusEntry 14 }

ibmappnNodeLsStatusLocalAddr   OBJECT-TYPE
  SYNTAX DisplayString
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "This contains a displayable string that identifies the
    DLC type and appropriate address. See DlcType above for
    details of the format."

::= { ibmappnNodeLsStatusEntry 15 }

ibmappnNodeLsStatusRemoteAddr  OBJECT-TYPE
  SYNTAX DisplayString
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "This contains a displayable string that identifies the
    DLC type and appropriate address. See DlcType above for
    details of the format."

::= { ibmappnNodeLsStatusEntry 16 }

-- ****
-- APPN SNMP Performance Information

```

--

```
ibmappnSnmpInPkts OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of messages delivered to the APPN SNMP sub-agent."
    ::= { ibmappnSnmpInformation 1 }

ibmappnSnmpInGetRequests OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of GET requests delivered to the APPN SNMP
         sub-agent."
    ::= { ibmappnSnmpInformation 2 }

ibmappnSnmpInGetNexts OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of GETNEXT requests delivered to the APPN SNMP
         sub-agent."
    ::= { ibmappnSnmpInformation 3 }

ibmappnSnmpInSetRequests OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of SET requests delivered to the APPN SNMP
         sub-agent."
    ::= { ibmappnSnmpInformation 4 }

ibmappnSnmpInTotalVars OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of VARIABLES included in both
         GET and GETNEXT requests to the APPN SNMP sub-agent."
```

```
: := { ibmappnSnmpInformation 5 }

ibmappnSnmpInGetVars OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of VARIABLES included in all
         GET requests to the APPN SNMP sub-agent."

: := { ibmappnSnmpInformation 6 }

ibmappnSnmpInGetNextVars OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of VARIABLES included in all
         GETNEXT requests to the APPN SNMP sub-agent."

: := { ibmappnSnmpInformation 7 }

ibmappnSnmpInSetVars OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of VARIABLES included in all
         SET requests to the APPN SNMP sub-agent."

: := { ibmappnSnmpInformation 8 }

ibmappnSnmpOutNoSuchNames OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of VARIABLES that could not
         be found by the APPN SNMP sub-agent."

: := { ibmappnSnmpInformation 9 }

ibmappnSnmpOutGenErrs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of undefined errors that
```

```
occurred processing SNMP request to the
APPN SNMP sub-agent."  
  
 ::= { ibmappnSnmpInformation 10 }  
  
-- *****  
  
-- This group provides global information about the
-- APPN node performance.  
  
-- The first section applies to the APPN control point
-- storage utilization.  
  
ibmappnMemorySize OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Size of the shared storage segment, as obtained  
by storage management from the underlying operating  
system."  
  
 ::= { ibmappnMemoryUse 1 }  
  
ibmappnMemoryUsed OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Number of bytes in the segment that are currently  
allocated to process."  
  
 ::= { ibmappnMemoryUse 2 }  
  
ibmappnMemoryWarnThresh OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Allocation threshold beyond which storage  
management considers the storage resources  
to be constrained."  
  
 ::= { ibmappnMemoryUse 3 }  
  
ibmappnMemoryCritThresh OBJECT-TYPE
```

```

SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Allocation threshold beyond which storage
     management considers the storage resources
     to be critically constrained."

 ::= { ibmappnMemoryUse 4 }

-- *****
-- The following are Counters maintained by the APPN CS component that
-- relate to total overall XID activity.
-----

ibmappnNodeDefLsGoodXids      OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The current number of successfull XIDs that have occurred
         on all defined link stations since the last time this
         node was initialized."
    ::= { ibmappnXidInformation 1 }

ibmappnNodeDefLsBadXids      OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The current number of unsuccessfull XIDs that have
         occurred on all defined link stations since the last
         time this node was initialized."
    ::= { ibmappnXidInformation 2 }

ibmappnNodeDynLsGoodXids      OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The current number of successfull XIDs that have
         occurred on all dynamic link stations since the last
         time this node was initialized."
    ::= { ibmappnXidInformation 3 }

```

```

ibmappnNodeDynLsBadXids      OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The current number of unsuccessfull XIDs that have
        occurred on all dynamic link stations since the last
        time this node was initialized."
    ::= { ibmappnXidInformation 4 }

-- **** The APPN Topology Group ****
ibmappnNn                  OBJECT IDENTIFIER ::= { ibmappn 2   }
ibmappnNnTopo               OBJECT IDENTIFIER ::= { ibmappnNn 1   }
ibmappnNnTopology           OBJECT IDENTIFIER ::= { ibmappnNn 3   }

-- This group will be used to represent the entire APPN network
-- topology, including Network nodes, virtual nodes and
-- all TGs associated with these nodes.
--
-- Network nodes
-- The APPN topology database consists of information about every
-- APPN network node. This information is learned over time
-- as each network node exchanges topology information with
-- each of its adjacent network nodes. The database consists
-- of information about each node and all of the transmissions
-- groups used by each node.

-- Virtual nodes
-- Information about virtual nodes (connection networks) is treated
-- the same as information about network node
-- and is replicated at each network node.
-- The node name is the only meaningful information. The other
-- node objects use default values. Each node that has defined
-- a TG with this virtual node as the destination also defines a
-- TG on this virtual node. There is a TG record for each node
-- that uses this virtual node.
--
-- The APPN node table represents the APPN topology
-- database with the APPN CP fully-qualified name
-- being used as the index to this table.
-- This entire table could be retrieved using the GET NEXT command,

```

```
-- however, due to the dynamics of APPN, nodes could come and
-- go and status could change as the table is being
-- retrieved. Although in most cases the data retrieved will be valid,
-- missing and invalid status could cause problems for
-- a management application that was graphically displaying
-- this data.
-- This potential problem can be eliminated by
-- retrieving the FRSN before and after completion
-- of retrieval of the APPN topology table.
-- If the FRSN has changed, then repeat the
-- retrieval of the entire topology table
-- until the FRSN remains unchanged.
-- Object 'appnNnFrsn' represents the last
-- change or update to this node's topology
-- database.
--
--
-- The format of the actual database is as follows:
--
-- Node table (entry for each node in network)
-- TG table (entry for each TG owned by node)
--
-- Due to SNMP ASN.1 limitations, we cannot represent
-- the TG table within the node table. We define
-- separate tables for nodes and TGs, adding the node
-- name to each TG entry to provide a means of
-- correlating each TG with its originating node.
```

```
ibmappnNnTopoMaxNodes    OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Maximum number of nodes allowed in the APPN topology
         database. This administratively assigned value must be
         equal to or greater than the maximum total number of end
         nodes and network nodes.
         If the number of nodes exceeds this value, APPN will issue
         an Alert and the node can no longer participate as a network
         node."
    ::= { ibmappnNnTopo 1 }

ibmappnNnTopoCurNumNodes OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
```

```
STATUS mandatory
DESCRIPTION
    "Current number of nodes in this node's topology database.
     If this value exceeds the maximum number of nodes allowed
     (NnTopoMaxNodes), APPN alert CPDB002 is
     issued."
 ::= { ibmappnNnTopo 2 }

ibmappnNnTopoInTdus OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of TDUs received from
     all adjacent NN since last initialization."
 ::= { ibmappnNnTopo 3 }

ibmappnNnTopoOutTdus OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of TDUs built by this node to be sent to
     all adjacent NN since last initialization."
 ::= { ibmappnNnTopo 4 }

ibmappnNnTopoNodeLowRsns          OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of topology node updates received by this
     node with a RSN less than the current RSN. Both even and
     odd RSN are included in this count.
     These TDUs are not errors, but result when TDUs are
     broadcast to all adjacent network nodes. No update to
     this node's topology database occurs, but this node will
     send a TDU with its higher RSN to the adjacent node that
     sent this low RSN."
 ::= { ibmappnNnTopo 5 }

ibmappnNnTopoNodeEqualRsns        OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
```

STATUS mandatory  
DESCRIPTION  
"Total number of topology node updates received by this node with a RSN equal to the current RSN. Both even and odd RSN are included in this count.  
These TDUs are not errors, but result when TDUs are broadcast to all adjacent network nodes. No update to this node's topology database occurs."  
:  
::= { ibmappnNnTopo 6 }

ibmappnNnTopoNodeGoodHighRsns OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology node updates received by this node with a RSN greater than the current RSN.  
This results in updating this nodes topology and broadcasting a TDU to all adjacent network nodes. It is not required to send a TDU to the sender of this update because that node already has the update."  
:  
::= { ibmappnNnTopo 7 }

ibmappnNnTopoNodeBadHighRsns OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology node updates received by this node with an odd RSN greater than the current RSN.  
These updates represent a topology inconsistency detected by one of the APPN network nodes.  
This results in updating this nodes topology and broadcasting a TDU to all adjacent network nodes."  
:  
::= { ibmappnNnTopo 8 }

ibmappnNnTopoNodeStateUpdates OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology Node records built as a result

of internally detected node state changes that affect APPN topology and routing. Updates are sent via TDUs to all adjacent network nodes."

```
: := { ibmappnNnTopo 9 }
```

**ibmappnNnTopoNodeErrors** OBJECT-TYPE  
 SYNTAX Counter  
 ACCESS read-only  
 STATUS mandatory  
 DESCRIPTION  
 "Total number of topology node records inconsistencies detected by this node. This occurs when this node attempts to update its topology database and detects a data inconsistency. This node will create a TDU with the current RSN incremented to the next odd number and broadcast it to all adjacent NNs."

```
: := { ibmappnNnTopo 10 }
```

**ibmappnNnTopoNodeTimerUpdates** OBJECT-TYPE  
 SYNTAX Counter  
 ACCESS read-only  
 STATUS mandatory  
 DESCRIPTION  
 "Total number of topology node records built for this node's resource due to timer updates. Updates are sent via TDUs to all adjacent network nodes. These updates insure other network nodes do not delete this node's resources from their topology database."

```
: := { ibmappnNnTopo 11 }
```

**ibmappnNnTopoNodePurges** OBJECT-TYPE  
 SYNTAX Counter  
 ACCESS read-only  
 STATUS mandatory  
 DESCRIPTION  
 "Total number of topology node records purged from this node's topology database. This occurs when a node has not been updated in a specified amount of time. The owning node is responsible for broadcasting updates for its resource that it wants kept in the network topology."

```
: := { ibmappnNnTopo 12 }
```

**ibmappnNnTopoTgLowRsns** OBJECT-TYPE

```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of topology TG updates received by this
    node with a RSN less than the current RSN. Both even and
    odd RSN are included in this count.
    These TDUs are not errors, but result when TDUs are
    broadcast to all adjacent network nodes. No update to
    this node's topology database occurs, but this node will
    send a TDU with it's higher RSN to the sender of the low
    RSN."
::= { ibmappnNnTopo 13 }

ibmappnNnTopoTgEqualRsns      OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of topology TG updates received by this
    node with a RSN equal to the current RSN. Both even and
    odd RSN are included in this count.
    These TDUs are not errors, but result when TDUs are
    broadcast to all adjacent network nodes. No update to
    this node's topology database occurs."
::= { ibmappnNnTopo 14 }

ibmappnNnTopoTgGoodHighRsns   OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of topology TG updates received by this
    node with a RSN greater than the current RSN.
    This results in updating this nodes topology and
    broadcasting the update to all adjacent network nodes."
::= { ibmappnNnTopo 15 }

ibmappnNnTopoTgBadHighRsns   OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Total number of topology TG updates received by this
```

node with an odd RSN greater than the current RSN.  
These updates represent a topology inconsistency detected  
by one of the APPN network nodes.  
This results in updating this nodes topology and  
broadcasting a TDU to all adjacent network nodes."

::= { ibmappnNnTopo 16 }

ibmappnNnTopoTgStateUpdates OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology TG records built as a result  
of internally detected node state changes that affect APPN  
topology and routing. Updates are sent via TDUs to all  
adjacent network nodes."

::= { ibmappnNnTopo 17 }

ibmappnNnTopoTgErrors OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology TG records inconsistencies  
detected by this node. This occurs when this node  
attempts to update its topology database and detects a  
data inconsistency. This node will create a TDU with  
the current RSN incremented to the next odd number and  
broadcast it to all adjacent NNs."

::= { ibmappnNnTopo 18 }

ibmappnNnTopoTgTimerUpdates OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Total number of topology TG records built for this  
node's resource due to timer updates. Updates are sent via  
TDUs to all adjacent network nodes. These updates insure  
other network nodes do not delete this node's resources  
from their topology database."

::= { ibmappnNnTopo 19 }

```
ibmappnNnTopoTgPurges OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Total number of topology TG records purged from this
         node's topology database. This occurs when a TG has not
         been updated in a specified amount of time. The owning
         node is responsible for broadcasting updates for its
         resource that it wants to keep in the network topology."
    ::= { ibmappnNnTopo 20 }

ibmappnNnTopoTotalRouteCalcs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of routes calculated for all class of services
         since the last initialization."
    ::= { ibmappnNnTopo 21 }

ibmappnNnTopoTotalRouteRejs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of route requests for all class of services that
         could not be calculated since last initialization."
    ::= { ibmappnNnTopo 22 }

ibmappnNnTopoRouteTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNnTopoRouteEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Table containing an entry for every Class of Service
         that it has calculated a route for."
    ::= { ibmappnNnTopo 23 }

ibmappnNnTopoRouteEntry OBJECT-TYPE
```

```

SYNTAX IbmappnNnTopoRouteEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The Class of Service name is the index for this table."

INDEX
    {ibmappnNnTopoRouteCos}

 ::= { ibmappnNnTopoRouteTable 1 }

IbmappnNnTopoRouteEntry ::= SEQUENCE {
    ibmappnNnTopoRouteCos          DisplayString,
    ibmappnNnTopoRouteTrees         Counter,
    ibmappnNnTopoRouteCalcs        Counter,
    ibmappnNnTopoRouteRejs         Counter
}

ibmappnNnTopoRouteCos   OBJECT-TYPE
    SYNTAX DisplayString
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The Class of Service for the route."
    ::= { ibmappnNnTopoRouteEntry 1 }

ibmappnNnTopoRouteTrees OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of routes tree caches built for this Class of
         Service since the last initialization."
    ::= { ibmappnNnTopoRouteEntry 2 }

ibmappnNnTopoRouteCalcs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of routes calculated since last initialization."
    ::= { ibmappnNnTopoRouteEntry 3 }

```

```

ibmappnNnTopoRouteRejs OBJECT-TYPE
  SYNTAX Counter
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
    "Number of route requests that could not
     be calculated since last initialization."
  ::= { ibmappnNnTopoRouteEntry 4 }

--Adjacent node table
--  Node name (only applies to adjacent nodes)
--  Number of out of sequence TDUs
--  Status of CP-CP sessions (ConWinner/ConLoser)
--  Last FRSN sent
--  Last FRSN received

ibmappnNnAdjNodeTable OBJECT-TYPE
  SYNTAX SEQUENCE OF IbmappnNnAdjNodeEntry
  ACCESS not-accessible
  STATUS mandatory
  DESCRIPTION
    "Table containing an entry for every node. The information
     kept in this table is the last FRSN sent and received,
     the status of the CP-CP sessions, and a gauge that
     indicates the number of outstanding TDUs."
  ::= { ibmappnNn 2 }

ibmappnNnAdjNodeEntry OBJECT-TYPE
  SYNTAX IbmappnNnAdjNodeEntry
  ACCESS not-accessible
  STATUS mandatory
  DESCRIPTION
    "The adjacent node name is the index for this table."

INDEX
  { ibmappnNnAdjNodeAdjName }

  ::= { ibmappnNnAdjNodeTable 1 }

IbmappnNnAdjNodeEntry ::= SEQUENCE {
  ibmappnNnAdjNodeAdjName          DisplayString,
  ibmappnNnAdjNodeCpCpSessStatus  INTEGER,
  ibmappnNnAdjNodeOutOfSeqTdus    Gauge,
}

```

```

ibmappnNnAdjNodeLastFrsnSent      INTEGER,
ibmappnNnAdjNodeLastFrsnRcvd      INTEGER
}

ibmappnNnAdjNodeAdjName          OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "An administratively-assigned fully-qualified
     name of this node's adjacent network node."

::= { ibmappnNnAdjNodeEntry 1 }

ibmappnNnAdjNodeCpCpSessStatus   OBJECT-TYPE
SYNTAX INTEGER {
    active(1),
    conLoserActive(2),
    conWinnerActive(3),
    inactive(4)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates the state of CP-CP sessions between this node
     and adjacent network and end nodes. Inactive indicates no
     CP-CP sessions exists between this node and the adjacent
     node. Active indicates CP-CP sessions are active using both
     the ConWinner and ConLoser sessions. The session initiated
     by this node is referred to as the ConWinner session and is
     used by this node to send to the adjacent node. The
     ConLoserr session is initiated by the adjacent node and
     is used by this node to receive from the adjacent node."

::= { ibmappnNnAdjNodeEntry 2 }

ibmappnNnAdjNodeOutOfSeqTdus    OBJECT-TYPE
SYNTAX Gauge
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of out of sequence Topology Database
     Updates (TDUs). In a quiesced state, this value is
     zero. In normal operation, the value varies
     depending on the network environment."

::= { ibmappnNnAdjNodeEntry 3 }

```

```
ibmappnNnAdjNodeLastFrsnSent OBJECT-TYPE
    SYNTAX INTEGER (0..65535)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Flow reduction sequence numbers (FRSNs) are associated
         with Topology Database Updates (TDUs) and are unique
         only within each APPN network node. A TDU can be
         associated with multiple APPN resources. This FRSN
         indicates the last TDU sent to this adjacent node."
    ::= { ibmappnNnAdjNodeEntry 4 }

ibmappnNnAdjNodeLastFrsnRcvd OBJECT-TYPE
    SYNTAX INTEGER (0..65535)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Flow reduction sequence numbers (FRSNs) are associated
         with Topology Database Updates (TDUs) and are unique
         only within each APPN network node. A TDU can be
         associated with multiple APPN resources. This FRSN
         indicates the last TDU received from this adjacent node."
    ::= { ibmappnNnAdjNodeEntry 5 }

--APPN Node Topology table

-- This table describes every known APPN Network node
-- and Virtual node.

ibmappnNnTopologyTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNnTopologyEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Portion of the APPN routing table
         that describes all of the APPN network nodes
         and virtual nodes known to this node."
    ::= { ibmappnNnTopology 1 }

ibmappnNnTopologyEntry OBJECT-TYPE
    SYNTAX IbmappnNnTopologyEntry
    ACCESS not-accessible
    STATUS mandatory
```

```

DESCRIPTION
    "The fully-qualified node name is used to
     index this table."

INDEX
    {ibmappnNnNodeName}

 ::= { ibmappnNnTopologyTable 1 }

IbmappnNnTopologyEntry ::= SEQUENCE {
    ibmappnNnNodeName          DisplayString,
    ibmappnNnNodeFrsn          INTEGER,
    ibmappnNnNodeEntryTimeLeft INTEGER,
    ibmappnNnNodeType          INTEGER,
    ibmappnNnNodeRsn           INTEGER,
    ibmappnNnNodeRouteAddResist INTEGER,
    ibmappnNnNodeCongested      INTEGER,
    ibmappnNnNodeIsrDepleted    INTEGER,
    ibmappnNnNodeEndptDepleted  INTEGER,
    ibmappnNnNodeQuiescing      INTEGER,
    ibmappnNnNodeGateway        INTEGER,
    ibmappnNnNodeCentralDirectory INTEGER,
    ibmappnNnNodeIsr            INTEGER,
    ibmappnNnNodeChainSupport   INTEGER
}

ibmappnNnNodeName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned network name that is locally
         defined at each network node in the format NETID.CPNAME."
    ::= { ibmappnNnTopologyEntry 1 }

ibmappnNnNodeFrsn          OBJECT-TYPE
    SYNTAX INTEGER (0..65535)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Flow reduction sequence numbers (FRSNs) are associated
         with Topology Database Updates (TDUs) and are unique
         only within each APPN network node. A TDU can be
         associated with multiple APPN resources. This FRSN
         indicates the last time this resource was updated at"

```

```
        this node."  
  
 ::= { ibmappnNnTopologyEntry 2 }  
  
ibmappnNnNodeEntryTimeLeft      OBJECT-TYPE  
SYNTAX INTEGER (0..31)  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Number of days before deletion of this  
    network node entry. Range is 0-31."  
  
 ::= { ibmappnNnTopologyEntry 3 }  
  
ibmappnNnNodeType      OBJECT-TYPE  
SYNTAX INTEGER {  
    networknode(1),  
    virtualnode(3)  
}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Type of APPN node."  
  
 ::= { ibmappnNnTopologyEntry 4 }  
  
ibmappnNnNodeRsn      OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Resource sequence number that is assigned and  
    controlled by the network node that owns this  
    resource. This is always an even 32-bit number  
    unless an error has occurred."  
  
 ::= { ibmappnNnTopologyEntry 5 }  
  
ibmappnNnNodeRouteAddResist    OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Route addition resistance  
    indicates the relative desirability  
    of using this node for intermediate session traffic.  
    The value, which can be any integer 0-255,  
    is used in route computation. The lower the value,
```

the more desirable the node is for intermediate routing."

```

 ::= { ibmappnNnTopologyEntry 6 }

ibmappnNnNodeCongested      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node is congested.
     This node is not included in route selection
     by other nodes when this congestion exists."

```

```

 ::= { ibmappnNnTopologyEntry 7 }

ibmappnNnNodeIsrDepleted OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether intermediate session
     routing resources are depleted. This node is
     not included in intermediate route selection
     by other nodes when resources are depleted."

```

```

 ::= { ibmappnNnTopologyEntry 8 }

ibmappnNnNodeEndptDepleted OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether session endpoint resources are depleted."

```

```

 ::= { ibmappnNnTopologyEntry 9 }

ibmappnNnNodeQuiescing      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node is quiescing.
     This node is not included in route selection
     by other nodes when the node is quiescing."

```

```

 ::= { ibmappnNnTopologyEntry 10 }

ibmappnNnNodeGateway        OBJECT-TYPE

```

```

SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node provide gateway functions."
::= { ibmappnNnTopologyEntry 11 }

ibmappnNnNodeCentralDirectory OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node is central directory."
::= { ibmappnNnTopologyEntry 12 }

ibmappnNnNodeIsr   OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node supports intermediate session
        routing (ISR)."
::= { ibmappnNnTopologyEntry 13 }

ibmappnNnNodeChainSupport OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node supports chaining."
::= { ibmappnNnTopologyEntry 14 }

--APPN transmission group (TG) table

-- This table describes the TGs associated with
-- the APPN network nodes.
-- The originating node is repeated here to provide a
-- means of correlating the TGs with the nodes.

ibmappnNnTgTopologyTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnNnTgTopologyEntry
    ACCESS not-accessible

```

```

STATUS mandatory
DESCRIPTION
  "Portion of the APPN topology database
  that describes all of the APPN transmissions groups
  used by the APPN network nodes."
 ::= { ibmappnNnTopology 2 }

ibmappnNnTgTopologyEntry OBJECT-TYPE
  SYNTAX IbmappnNnTgTopologyEntry
  ACCESS not-accessible
  STATUS mandatory
  DESCRIPTION
    "This table requires three indexes to provide a
    unique index. The indexes are the owning or originating
    CPname, the destination CPname, and the TG number."
INDEX
  {ibmappnNnTgOwner,
   ibmappnNnTgDest,
   ibmappnNnTgNum}

 ::= { ibmappnNnTgTopologyTable 1 }

IbmappnNnTgTopologyEntry ::= SEQUENCE {
  ibmappnNnTgOwner      DisplayString,
  ibmappnNnTgDest       DisplayString,
  ibmappnNnTgNum        INTEGER,
  ibmappnNnTgFrsn       INTEGER,
  ibmappnNnTgEntryTimeLeft INTEGER,
  ibmappnNnTgDestVirtual INTEGER,
  ibmappnNnTgDlcData    OCTET STRING,
  ibmappnNnTgRsn        INTEGER,
  ibmappnNnTgOperational INTEGER,
  ibmappnNnTgQuiescing  INTEGER,
  ibmappnNnTgCpCpSession INTEGER,
  ibmappnNnTgEffCap     INTEGER,
  ibmappnNnTgConnCost   INTEGER,
  ibmappnNnTgByteCost   INTEGER,
  ibmappnNnTgSecurity   INTEGER,
  ibmappnNnTgDelay      INTEGER,
  ibmappnNnTgModemClass INTEGER,
  ibmappnNnTgUsr1        INTEGER,
  ibmappnNnTgUsr2        INTEGER,
  ibmappnNnTgUsr3        INTEGER}

```

```
ibmappnNnTgOwner OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for the
         originating node for this TG. The format
         is NETID.CPNAME and is the same name
         specified in the node table."
    ::= { ibmappnNnTgTopologyEntry 1 }

ibmappnNnTgDest OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned fully-qualified
         network name for the destination node for this TG."
    ::= { ibmappnNnTgTopologyEntry 2 }

ibmappnNnTgNum OBJECT-TYPE
    SYNTAX INTEGER (0..255)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number associated with this
         transmission group. Range is 0-255."
    ::= { ibmappnNnTgTopologyEntry 3 }

ibmappnNnTgFrsn OBJECT-TYPE
    SYNTAX INTEGER (0..65535)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Flow reduction sequence numbers (FRSNs) are associated
         with Topology Database Updates (TDUs) and are unique
         only within each APPN network node. A TDU can be
         associated with multiple APPN resources. This FRSN
         indicates the last time this resource was updated at
         this node."
    ::= { ibmappnNnTgTopologyEntry 4 }

ibmappnNnTgEntryTimeLeft OBJECT-TYPE
    SYNTAX INTEGER (0..31)
```

```
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of days before deletion of this
     network node TG entry. Range is 0-31."
::= { ibmappnNnTgTopologyEntry 5 }

ibmappnNnTgDestVirtual OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the destination node is
     a virtual node."
::= { ibmappnNnTgTopologyEntry 6 }

ibmappnNnTgDlcData OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (0..9))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "DLC specific data related to the link connection
     network.
    Token-Ring      - MAC/SAP
    X.25 Switched - dial digits
    X.21 Switched - dial digits
    Circuit Swtch - dial digits"
::= { ibmappnNnTgTopologyEntry 7 }

ibmappnNnTgRsn OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Current owning node's resource sequence number
     for this resource."
::= { ibmappnNnTgTopologyEntry 8 }

ibmappnNnTgOperational OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the transmission group
```

```
        is operational."  
  
 ::= { ibmappnNnTgTopologyEntry 9 }  
  
ibmappnNnTgQuiescing OBJECT-TYPE  
SYNTAX INTEGER {yes(1), no(2)}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Indicates whether the transmission group  
is quiescing."  
  
 ::= { ibmappnNnTgTopologyEntry 10 }  
  
ibmappnNnTgCpCpSession OBJECT-TYPE  
SYNTAX INTEGER {yes(1), no(2)}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Indicates whether CP-CP sessions are supported on this TG."  
  
 ::= { ibmappnNnTgTopologyEntry 11 }  
  
ibmappnNnTgEffCap OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "The effective capacity is an integer value that indicates  
the kilo bits per second.  
It is derived from the link bandwidth and maximum load  
factor with the range of 0 thru 603,979,776.  
This is an administratively assigned value associated  
with this TG."  
  
 ::= { ibmappnNnTgTopologyEntry 12 }  
  
ibmappnNnTgConnCost OBJECT-TYPE  
SYNTAX INTEGER (0..255)  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
    "Cost per connect time: a value representing  
the relative cost per unit of time to use  
the TG. Range is from 0, which means no cost,  
to 255, which indicates maximum cost.  
This is an administratively assigned value associated
```

with this TG."

```
: := { ibmappnNnTgTopologyEntry 13 }
```

```
ibmappnNnTgByteCost OBJECT-TYPE
    SYNTAX INTEGER (0..255)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Relative cost of transmitting a byte over this link.
         Range is from 0 (lowest cost) to 255.
         This is an administratively assigned value associated
         with this TG."
```

```
: := { ibmappnNnTgTopologyEntry 14 }
```

```
ibmappnNnTgSecurity OBJECT-TYPE
    SYNTAX INTEGER {
        nonsecure(1),                      --X'01'
        publicSwitchedNetwork(32),          --X'20'
        undergroundCable(64),              --X'40'
        secureConduit(96),                 --X'60'
        guardedConduit(128),               --X'80'
        encrypted(160),                   --X'A0'
        guardedRadiation(192)             --X'C0'
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The security is represented as an integer with a range of
         1 thru 255 with the most common values enumerated as
         defined above.
         This is an administratively assigned value associated
         with this TG."
```

```
: := { ibmappnNnTgTopologyEntry 15 }
```

```
ibmappnNnTgDelay OBJECT-TYPE
    SYNTAX INTEGER {
        minimum(0),                         --X'00'
        negligible(384),                    --X'4C'
        terrestrial(9216),                  --X'71'
        packet(147456),                     --X'91'
        long(294912),                      --X'99'
        maximum(2013265920)                --X'FF'
    }
    ACCESS read-only
```

STATUS mandatory  
DESCRIPTION  
"Relative amount of time that it takes for a signal to travel the length of the logical link. This time is represented in micro seconds, with some of the more common values enumerated.  
This is an administratively assigned value associated with this TG."

`::= { ibmappnNnTgTopologyEntry 16 }`

**ibmappnNnTgModemClass** OBJECT-TYPE  
SYNTAX INTEGER (0..65535)  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"This is used to have multiple images for a connection network. For a connection network it is the same as in the TG vector; for a non-connection network it is X'00'."

`::= { ibmappnNnTgTopologyEntry 17 }`

**ibmappnNnTgUsr1** OBJECT-TYPE  
SYNTAX INTEGER (0..255)  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"First user-defined TG characteristic for this TG with a range of 0-255.  
This is an administratively assigned value associated with this TG."

`::= { ibmappnNnTgTopologyEntry 18 }`

**ibmappnNnTgUsr2** OBJECT-TYPE  
SYNTAX INTEGER (0..255)  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Second user-defined TG characteristic for this TG with a range of 0-255.  
This is an administratively assigned value associated with this TG."

`::= { ibmappnNnTgTopologyEntry 19 }`

```

ibmappnNnTgUsr3 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Third user-defined TG characteristic for this TG with
a range of 0-255.
This is an administratively assigned value associated
with this TG."
::= { ibmappnNnTgTopologyEntry 20 }

--APPN Node Topology table (using FRSN as index)

-- This table describes every known APPN Network node
-- and Virtual node.

ibmappnNnTopologyFRTTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNnTopologyFREntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
"Portion of the APPN routing table
that describes all of the APPN network nodes
and virtual nodes known to this node."
::= { ibmappnNnTopology 3 }

ibmappnNnTopologyFREntry OBJECT-TYPE
SYNTAX IbmappnNnTopologyFREntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
"This table is indexed by two columns:
FRSN, followed by fully-qualified node name."
INDEX
{ ibmappnNnNodeFRFrsn,
  ibmappnNnNodeFRName}
::= { ibmappnNnTopologyFRTTable 1 }

IbmappnNnTopologyFREntry ::= SEQUENCE {
  ibmappnNnNodeFRName          DisplayString,
  ibmappnNnNodeFRFrsn          INTEGER,
  ibmappnNnNodeFREntryTimeLeft INTEGER,

```

```

ibmappnNnNodeFRTYPE          INTEGER,
ibmappnNnNodeFRRsn           INTEGER,
ibmappnNnNodeFRRouteAddResist INTEGER,
ibmappnNnNodeFRCongested     INTEGER,
ibmappnNnNodeFRIsrDepleted   INTEGER,
ibmappnNnNodeFREndptDepleted INTEGER,
ibmappnNnNodeFRQuiescing     INTEGER,
ibmappnNnNodeFRGateway       INTEGER,
ibmappnNnNodeFRCentralDirectory INTEGER,
ibmappnNnNodeFRIsr          INTEGER,
ibmappnNnNodeFRChainSupport  INTEGER
}

ibmappnNnNodeFRName      OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned network name that is locally
     defined at each network node in the format NETID.CPNAME."
::= { ibmappnNnTopologyFREntry 1 }

ibmappnNnNodeFRFrsn        OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Flow reduction sequence numbers (FRSNs) are associated
     with Topology Database Updates (TDUs) and are unique
     only within each APPN network node. A TDU can be
     associated with multiple APPN resources. This FRSN
     indicates the last time this resource was updated at
     this node."
::= { ibmappnNnTopologyFREntry 2 }

ibmappnNnNodeFREntryTimeLeft OBJECT-TYPE
SYNTAX INTEGER (0..31)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of days before deletion of this
     network node entry. Range is 0-31."
::= { ibmappnNnTopologyFREntry 3 }

```

```

ibmappnNnNodeFRType      OBJECT-TYPE
SYNTAX INTEGER {
    networknode(1),
    virtualnode(3)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Type of APPN node."

::= { ibmappnNnTopologyFREntry 4 }

ibmappnNnNodeFRRsn      OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Resource sequence number that is assigned and
     controlled by the network node that owns this
     resource. This is always an even 32-bit number
     unless an error has occurred."

::= { ibmappnNnTopologyFREntry 5 }

ibmappnNnNodeFRRRouteAddResist   OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Route addition resistance
     indicates the relative desirability
     of using this node for intermediate session traffic.
     The value, which can be any integer 0-255,
     is used in route computation. The lower the value,
     the more desirable the node is for intermediate routing."

::= { ibmappnNnTopologyFREntry 6 }

ibmappnNnNodeFRCongested      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node is congested.
     This node is not be included in route selection
     by other nodes when this congestion exists."

::= { ibmappnNnTopologyFREntry 7 }

```

```
ibmappnNnNodeFRIsrDepleted OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether intermediate session
         routing resources are depleted. This node is
         not included in intermediate route selection
         by other nodes when resources are depleted."
    ::= { ibmappnNnTopologyFREntry 8 }

ibmappnNnNodeFREndptDepleted OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether session endpoint resources are depleted."
    ::= { ibmappnNnTopologyFREntry 9 }

ibmappnNnNodeFRQuiescing      OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node is quiescing.
         This node is not included in route selection
         by other nodes when the node is quiescing."
    ::= { ibmappnNnTopologyFREntry 10 }

ibmappnNnNodeFRGateway       OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node provide gateway functions."
    ::= { ibmappnNnTopologyFREntry 11 }

ibmappnNnNodeFRCentralDirectory OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node is central directory."
    ::= { ibmappnNnTopologyFREntry 12 }
```

```

ibmappnNnNodeFRIsr    OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node supports intermediate session
     routing (ISR)."

 ::= { ibmappnNnTopologyFREntry 13 }

ibmappnNnNodeFRChainSupport OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node supports chaining."

 ::= { ibmappnNnTopologyFREntry 14 }

--APPN transmission group (TG) table

-- This table describes the TGs associated with
-- the APPN network nodes.
-- The originating node is repeated here to provide a
-- means of correlating the TGs with the nodes.

ibmappnNnTgTopologyFRTTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnNnTgTopologyFREntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "Portion of the APPN topology database
     that describes all of the APPN transmissions groups
     used by the APPN network nodes."

 ::= { ibmappnNnTopology 4 }

ibmappnNnTgTopologyFREntry OBJECT-TYPE
SYNTAX IbmappnNnTgTopologyFREntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "This table is indexed by four columns:
     FRSN, TG owner fully-qualified node name,
     TG destination fully-qualified node name, and TG number."
INDEX

```

```

{ibmappnNnTgFRFrsn,
 ibmappnNnTgFROwner,
 ibmappnNnTgFRDest,
 ibmappnNnTgFRNum}

 ::= { ibmappnNnTgTopologyFRTTable 1 }

IbmappnNnTgTopologyFREntry ::= SEQUENCE {
    ibmappnNnTgFROwner      DisplayString,
    ibmappnNnTgFRDest       DisplayString,
    ibmappnNnTgFRNum        INTEGER,
    ibmappnNnTgFRFrsn       INTEGER,
    ibmappnNnTgFREntryTimeLeft INTEGER,
    ibmappnNnTgFRDestVirtual INTEGER,
    ibmappnNnTgFRDlcData    OCTET STRING,
    ibmappnNnTgFRRsn        INTEGER,
    ibmappnNnTgFROperational INTEGER,
    ibmappnNnTgFRQuiescing  INTEGER,
    ibmappnNnTgFRCpCpSession INTEGER,
    ibmappnNnTgFREffCap     INTEGER,
    ibmappnNnTgFRCConnCost  INTEGER,
    ibmappnNnTgFRByteCost   INTEGER,
    ibmappnNnTgFRSecurity   INTEGER,
    ibmappnNnTgFRDelay      INTEGER,
    ibmappnNnTgFRModemClass INTEGER,
    ibmappnNnTgFRUsr1       INTEGER,
    ibmappnNnTgFRUsr2       INTEGER,
    ibmappnNnTgFRUsr3       INTEGER}

ibmappnNnTgFROwner OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for the
        originating node for this TG. The format
        is NETID.CPNAME and is the same name
        specified in the node table."
    ::= { ibmappnNnTgTopologyFREntry 1 }

ibmappnNnTgFRDest OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only

```

```

STATUS mandatory
DESCRIPTION
    "Administratively-assigned fully-qualified
     network name for the destination node for this TG."
::= { ibmappnNnTgTopologyFREntry 2 }

ibmappnNnTgFRNum   OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number associated with this
     transmission group. Range is 0-255."
::= { ibmappnNnTgTopologyFREntry 3 }

ibmappnNnTgFRFrsn          OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Flow reduction sequence numbers (FRSNs) are associated
     with Topology Database Updates (TDUs) and are unique
     only within each APPN network node. A TDU can be
     associated with multiple APPN resources. This FRSN
     indicates the last time this resource was updated at
     this node."
::= { ibmappnNnTgTopologyFREntry 4 }

ibmappnNnTgFREntryTimeLeft      OBJECT-TYPE
SYNTAX INTEGER (0..31)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of days before deletion of this
     network node TG entry. Range is 0-31."
::= { ibmappnNnTgTopologyFREntry 5 }

ibmappnNnTgFRDestVirtual   OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the destination node is
     a virtual node."

```

```

 ::= { ibmappnNnTgTopologyFREntry 6 }

ibmappnNnTgFRDlcData OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (0..9))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "DLC specific data related to the link connection
     network.
    Token-Ring - MAC/SAP
    X.25 Switched - dial digits
    X.21 Switched - dial digits
    Circuit Swtch - dial digits"

 ::= { ibmappnNnTgTopologyFREntry 7 }

ibmappnNnTgFRRsn OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Current owning node's resource sequence number
     for this resource."

 ::= { ibmappnNnTgTopologyFREntry 8 }

ibmappnNnTgFROperational OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the transmission group
     is operational."

 ::= { ibmappnNnTgTopologyFREntry 9 }

ibmappnNnTgFRQuiescing OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the transmission group
     is quiescing."

 ::= { ibmappnNnTgTopologyFREntry 10 }

ibmappnNnTgFRCpCpSession OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}

```

```

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether CP-CP sessions are supported on this TG."
::= { ibmappnNnTgTopologyFREntry 11 }

ibmappnNnTgFREffCap OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The effective capacity is an integer value that indicates
    the kilo bits per second.
    It is derived from the link bandwidth and maximum load
    factor with the range of 0 thru 603,979,776.
    This is an administratively assigned value associated
    with this TG."
::= { ibmappnNnTgTopologyFREntry 12 }

ibmappnNnTgFRConnCost OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Cost per connect time: a value representing
    the relative cost per unit of time to use
    the TG. Range is from 0, which means no cost,
    to 255, which indicates maximum cost.
    This is an administratively assigned value associated
    with this TG."
::= { ibmappnNnTgTopologyFREntry 13 }

ibmappnNnTgFRByteCost OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative cost of transmitting a byte over this link.
    Range is from 0 (lowest cost) to 255.
    This is an administratively assigned value associated
    with this TG."
::= { ibmappnNnTgTopologyFREntry 14 }

```

```

ibmappnNnTgFRSecurity OBJECT-TYPE
SYNTAX INTEGER {
    nonsecure(1),                      --X'01'
    publicSwitchedNetwork(32),          --X'20'
    undergroundCable(64),              --X'40'
    secureConduit(96),                --X'60'
    guardedConduit(128),              --X'80'
    encrypted(160),                  --X'A0'
    guardedRadiation(192)             --X'C0'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The security is represented as an integer with a range of
     1 thru 255 with the most common values enumerated as
     defined above.
    This is an administratively assigned value associated
     with this TG."
::= { ibmappnNnTgTopologyFREntry 15 }

ibmappnNnTgFRDelay OBJECT-TYPE
SYNTAX INTEGER {
    minimum(0),                         --X'00'
    negligible(384),                   --X'4C'
    terrestrial(9216),                --X'71'
    packet(147456),                   --X'91'
    long(294912),                     --X'99'
    maximum(2013265920)              --X'FF'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative amount of time that it takes for a signal to
     travel the length of the logical link. This time is
     represented in micro seconds, with some of the more
     common values enumerated.
    This is an administratively assigned value associated
     with this TG."
::= { ibmappnNnTgTopologyFREntry 16 }

ibmappnNnTgFRModemClass OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This is used to have multiple images for a

```

```

connection network. For a connection network
it is the same as in the TG vector; for
a non-connection network it is X'00'."}

::= { ibmappnNnTgTopologyFREntry 17 }

ibmappnNnTgFRUsr1 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"First user-defined TG characteristic for this TG with
a range of 0-255.
This is an administratively assigned value associated
with this TG."

::= { ibmappnNnTgTopologyFREntry 18 }

ibmappnNnTgFRUsr2 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Second user-defined TG characteristic for this TG with
a range of 0-255.
This is an administratively assigned value associated
with this TG."

::= { ibmappnNnTgTopologyFREntry 19 }

ibmappnNnTgFRUsr3 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Third user-defined TG characteristic for this TG with
a range of 0-255.
This is an administratively assigned value associated
with this TG."

::= { ibmappnNnTgTopologyFREntry 20 }

-- ***** The APPN Local Topology Group *****
ibmappnLocalTopology OBJECT IDENTIFIER ::= { ibmappn 3 }
ibmappnLocalThisNode OBJECT IDENTIFIER ::= { ibmappnLocalTopology 1 }
ibmappnLocalGeneral OBJECT IDENTIFIER ::= { ibmappnLocalThisNode 1 }

```

```

ibmappnLocalNnSpecific OBJECT IDENTIFIER ::= { ibmappnLocalThisNode 2 }
ibmappnLocalTg      OBJECT IDENTIFIER ::= { ibmappnLocalThisNode 3 }
ibmappnLocalEnTopology OBJECT IDENTIFIER ::= { ibmappnLocalTopology 2 }

-- The LocalEnNodeTable and LocalEnTgTable will replace these OIs
--ibmappnLocalEnNode   OBJECT IDENTIFIER ::= { ibmappnLocalEnTopology 1 }
--ibmappnLocalEnTg     OBJECT IDENTIFIER ::= { ibmappnLocalEnTopology 2 }

--This MIB Group represents the local topology
--maintained in both APPN end nodes and network nodes.
--Although the same control vectors are used for both network
--and local topology, many of the attributes only apply to network
--nodes. This MIB group defines the required objects for retrieval
--of information about this node and the objects that represent
--the local topology about end nodes.
--
--This node could be either an network node or an end node. The
--definition must address both cases.
--
--1 Information about this node
--  a General information about this node, both NN and ENs.
--  b Information about this node that applies only to NNs.
--  c TG table      (repeated for each TG this node owns)
--
--2 Information about the end nodes known to this network node
--  (THIS SECTION ONLY APPLIES TO NETWORK NODES)
--  a End node table (entry for each end node )
--  b TG table      (repeated for each TG owned by the end nodes)
--
--

-----
-- General information section

ibmappnLocalNodeName    OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned fully-qualified name
         for this node. Format is NETID.CPNAME."
    ::= { ibmappnLocalGeneral 1 }

ibmappnLocalNodeType    OBJECT-TYPE

```

```

SYNTAX INTEGER {
    networknode(1),
    endnode(2),
    len(4)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Type of APPN node."

 ::= { ibmappnLocalGeneral 2 }

-- Network node unique information
--

ibmappnLocalNnRsn      OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Resource sequence number is assigned and
    controlled by the network node that owns this
    resource. This is always an even unsigned
    number unless an error has occurred."

 ::= { ibmappnLocalNnSpecific 1 }

ibmappnLocalNnRouteAddResist   OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Route addition resistance
    indicates the relative desirability
    of using this node for intermediate session traffic.
    The value, which can be any integer 0-255,
    is used in route computation. The lower the value,
    the more desirable the node is for intermediate routing."

 ::= { ibmappnLocalNnSpecific 2 }

ibmappnLocalNnCongested      OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether this node is congested."

```

Other network nodes stop routing traffic to this node while this flag is on."

```

 ::= { ibmappnLocalNnSpecific 3 }

ibmappnLocalNnIsrDepleted OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicate whether intermediated session
         routing resources are depleted.
         Other network nodes stop routing traffic through
         this node while this flag is on."

```

```

 ::= { ibmappnLocalNnSpecific 4 }

ibmappnLocalNnEndptDepleted OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether session endpoint resources
         are depleted."

```

```

 ::= { ibmappnLocalNnSpecific 5 }

ibmappnLocalNnQuiescing      OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node is quiescing."

```

```

 ::= { ibmappnLocalNnSpecific 6 }

ibmappnLocalNnGateway        OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the node is a gateway."

```

```

 ::= { ibmappnLocalNnSpecific 7 }

ibmappnLocalNnCentralDirectory OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only

```

```
STATUS mandatory
DESCRIPTION
    "Indicates whether the node is a central directory."
::= { ibmappnLocalNnSpecific 8 }

ibmappnLocalNnIsr    OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node supports intermediate
     session routing."
::= { ibmappnLocalNnSpecific 9 }

ibmappnLocalNnChainSupport OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the node supports chaining."
::= { ibmappnLocalNnSpecific 10 }

ibmappnLocalNnFrsn    OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Flow reduction sequence numbers (FRSNs) are associated
     with Topology Database Updates (TDUs) and are unique
     only within each APPN network node. A TDU can be
     associated with multiple APPN resources. This object
     is the last FRSN sent in a topology update to
     adjacent network nodes."
::= { ibmappnLocalNnSpecific 11 }

-- Local TG information
-- APPN Transmission Group (TG) Table

-- This table describes the TGs associated with
-- this node only.

ibmappnLocalTgTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnLocalTgEntry
```

```

ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "TG Table describes all of the TGs owned by this
    node. The TG destination can be a virtual
    node, network node, len, or end node."
 ::= { ibmappnLocalTg 1 }

ibmappnLocalTgEntry OBJECT-TYPE
SYNTAX IbmappnLocalTgEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "This table is indexed by the destination CPname
    and the TG number."
INDEX
    {ibmappnLocalTgDest,
     ibmappnLocalTgNum}

 ::= { ibmappnLocalTgTable 1 }

IbmappnLocalTgEntry ::= SEQUENCE {
    ibmappnLocalTgDest      DisplayString,
    ibmappnLocalTgNum       INTEGER,
    ibmappnLocalTgDestVirtual INTEGER,
    ibmappnLocalTgDlcData   OCTET STRING,

    ibmappnLocalTgRsn       INTEGER,
    ibmappnLocalTgQuiescing INTEGER,
    ibmappnLocalTgOperational INTEGER,
    ibmappnLocalTgCpCpSession INTEGER,
    ibmappnLocalTgEffCap    INTEGER,
    ibmappnLocalTgConnCost  INTEGER,
    ibmappnLocalTgByteCost  INTEGER,
    ibmappnLocalTgSecurity  INTEGER,
    ibmappnLocalTgDelay     INTEGER,
    ibmappnLocalTgModemClass INTEGER,
    ibmappnLocalTgUsr1      INTEGER,
    ibmappnLocalTgUsr2      INTEGER,
    ibmappnLocalTgUsr3      INTEGER
}

ibmappnLocalTgDest OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only

```

```

STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for the
    destination node for this TG.
    This is the fully-qualified network node
    name."
::= { ibmappnLocalTgEntry 1 }

ibmappnLocalTgNum OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number associated with this transmission group."
::= { ibmappnLocalTgEntry 2 }

ibmappnLocalTgDestVirtual OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the destination node is
    a Virtual node."
::= { ibmappnLocalTgEntry 3 }

ibmappnLocalTgDlcData OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (0..9))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "DLC specific data related to the link connection
    network.
    Token-Ring - MAC/SAP
    X.25 Switched - dial digits
    X.21 Switched - dial digits
    Circuit Swtch - dial digits"
::= { ibmappnLocalTgEntry 4 }

ibmappnLocalTgRsn OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "The resource sequence number is assigned and
    controlled by the network node that owns this

```

resource. This is always an even unsigned number unless an error has occurred."

```
: := { ibmappnLocalTgEntry 5 }
```

ibmappnLocalTgQuiescing OBJECT-TYPE  
SYNTAX INTEGER {yes(1), no(2)}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Indicates whether the Transmission Group is quiescing."

```
: := { ibmappnLocalTgEntry 6 }
```

ibmappnLocalTgOperational OBJECT-TYPE  
SYNTAX INTEGER {yes(1), no(2)}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Indicates whether the Transmission Group is operational."

```
: := { ibmappnLocalTgEntry 7 }
```

ibmappnLocalTgCpCpSession OBJECT-TYPE  
SYNTAX INTEGER {yes(1), no(2)}  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"Indicates whether the CP-CP Sessions are supported on this TG."

```
: := { ibmappnLocalTgEntry 8 }
```

ibmappnLocalTgEffCap OBJECT-TYPE  
SYNTAX INTEGER  
ACCESS read-only  
STATUS mandatory  
DESCRIPTION  
"The effective capacity is an integer value that indicates the actual kilo bits per second.  
It is derived from the link bandwidth and maximum load factor with the range of 0 thru 603,979,776."

```
: := { ibmappnLocalTgEntry 9 }
```

ibmappnLocalTgConnCost OBJECT-TYPE

```

SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Cost per connect time: a value representing
     the relative cost per unit of time to use
     the TG. Range is from 0, which means no cost,
     to 255."
 ::= { ibmappnLocalTgEntry 10 }

ibmappnLocalTgByteCost OBJECT-TYPE
    SYNTAX INTEGER (0..255)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Relative cost of transmitting a byte over this link.
         Range is from 0 (lowest cost) to 255."
 ::= { ibmappnLocalTgEntry 11 }

ibmappnLocalTgSecurity OBJECT-TYPE
    SYNTAX INTEGER {
        nonsecure(1),                      --X'01'
        publicSwitchedNetwork(32),          --X'20'
        undergroundCable(64),              --X'40'
        secureConduit(96),                 --X'60'
        guardedConduit(128),               --X'80'
        encrypted(160),                   --X'A0'
        guardedRadiation(192)             --X'C0'
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Security level for this TG."
 ::= { ibmappnLocalTgEntry 12 }

ibmappnLocalTgDelay OBJECT-TYPE
    SYNTAX INTEGER {
        minimum(0),                      --X'00'
        negligible(384),                  --X'4C'
        terrestrial(9216),                --X'71'
        packet(147456),                  --X'91'
        long(294912),                   --X'99'
        maximum(2013265920)             --X'FF'
    }
    ACCESS read-only

```

```
STATUS mandatory
DESCRIPTION
    "Relative amount of time that it takes for a signal to
     travel the length of the logical link. This time is
     represented in micro seconds, with some of the more
     common values enumerated."
 ::= { ibmappnLocalTgEntry 13 }

ibmappnLocalTgModemClass OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This is used to have multiple images for a
     connection network. For a connection network
     it is the same as in the TG vector and for
     a non-connection network it is zero."
 ::= { ibmappnLocalTgEntry 14 }

ibmappnLocalTgUsr1 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Value of the first user-defined TG
     characteristic for this TG.
     Range is 0-255."
 ::= { ibmappnLocalTgEntry 15 }

ibmappnLocalTgUsr2 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Value of the second user-defined TG
     characteristic for this TG.
     Range is 0-255."
 ::= { ibmappnLocalTgEntry 16 }

ibmappnLocalTgUsr3 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
```

```

"Value of the third user-defined TG
characteristic for this TG.
Range is 0-255."}

::= { ibmappnLocalTgEntry 17 }

-- This section applies only to network nodes.
-- It contains end node topology information known to serving
-- network node.
-- The first table contains information about all end nodes
-- known to this node.
--
-- The TG table contains information about all of the TGs owned
-- by these end nodes.

ibmappnLocalEnTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmapnLocalEnEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Portion of the APPN topology
         database that describes the end
         nodes known to this node."

::= { ibmappnLocalEnTopology 1 }

ibmappnLocalEnEntry OBJECT-TYPE
    SYNTAX IbmapnLocalEnEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This table is indexed by the end node CPname."

INDEX
    {ibmappnLocalEnName}
::= { ibmappnLocalEnTable 1 }

IbmappnLocalEnEntry ::= SEQUENCE {
    ibmappnLocalEnName          DisplayString,
    ibmappnLocalEnEntryTimeLeft INTEGER,
    ibmappnLocalEnType          INTEGER
}

ibmappnLocalEnName      OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))

```

```

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned fully-qualified
     name of end node in the format NETID.CPNAME."
 ::= { ibmappnLocalEnEntry 1 }

ibmappnLocalEnEntryTimeLeft   OBJECT-TYPE
    SYNTAX INTEGER (0..31)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of days before deletion of this
         end node entry. Range is 0-31."
 ::= { ibmappnLocalEnEntry 2 }

ibmappnLocalEnType   OBJECT-TYPE
    SYNTAX INTEGER {
        endnode(2),
        len(4)
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Type of APPN node (must always be a len or end node)."
 ::= { ibmappnLocalEnEntry 3 }

--APPN Local End node Transmission Group (TG) table

-- This table describes the TGs associated with
-- all of the end nodes known to this node.

ibmappnLocalEnTgTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnLocalEnTgEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Table describing all of the TGs owned by the
         end nodes known to this node.
         The TG destination can be a virtual
         node, network node, or end node."
 ::= { ibmappnLocalEnTopology 2 }

```

```

ibmappnLocalEnTgEntry OBJECT-TYPE
SYNTAX IbmapnLocalEnTgEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
  "This table requires multiple indexes to uniquely
  identify each TG. They are originating CPname,
  destination CPname, and the TG number."

INDEX
  {ibmappnLocalEnTgOrigin,
   ibmappnLocalEnTgDest,
   ibmappnLocalEnTgNum}

 ::= { ibmappnLocalEnTgTable 1 }

IbmappnLocalEnTgEntry ::= SEQUENCE {
  ibmappnLocalEnTgOrigin      DisplayString,
  ibmappnLocalEnTgDest       DisplayString,
  ibmappnLocalEnTgNum        INTEGER,
  ibmappnLocalEnTgEntryTimeLeft INTEGER,

  ibmappnLocalEnTgDestVirtual INTEGER,
  ibmappnLocalEnTgDlcData    OCTET STRING,

  ibmappnLocalEnTgOperational INTEGER,
  ibmappnLocalEnTgCpCpSession INTEGER,
  ibmappnLocalEnTgEffCap     INTEGER,
  ibmappnLocalEnTgConnCost   INTEGER,
  ibmappnLocalEnTgByteCost   INTEGER,
  ibmappnLocalEnTgSecurity   INTEGER,
  ibmappnLocalEnTgDelay     INTEGER,
  ibmappnLocalEnTgModemClass INTEGER,
  ibmappnLocalEnTgUsr1       INTEGER,
  ibmappnLocalEnTgUsr2       INTEGER,
  ibmappnLocalEnTgUsr3       INTEGER
}

ibmappnLocalEnTgOrigin      OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
  "Administratively-assigned name for the
  origination node for this TG.
  This is the fully-qualified network name."

 ::= { ibmappnLocalEnTgEntry 1 }

```

```

ibmappnLocalEnTgDest      OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for the
     destination node for this TG.
     This is the fully-qualified network name."

 ::= { ibmappnLocalEnTgEntry 2 }

ibmappnLocalEnTgNum   OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number associated with this transmission group."

 ::= { ibmappnLocalEnTgEntry 3 }

ibmappnLocalEnTgEntryTimeLeft   OBJECT-TYPE
SYNTAX INTEGER (0..31)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of days before deletion of this
     end node TG entry. Range is 0-31."

 ::= { ibmappnLocalEnTgEntry 4 }

ibmappnLocalEnTgDestVirtual   OBJECT-TYPE
SYNTAX INTEGER {yes(1), no(2)}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Indicates whether the destination node is
     a virtual node."

 ::= { ibmappnLocalEnTgEntry 5 }

ibmappnLocalEnTgDlcData   OBJECT-TYPE
SYNTAX OCTET STRING
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "DLC specific data related to the link connection
     network.
     Token-Ring      - MAC/SAP

```

```
X.25 Switched - dial digits
X.21 Switched - dial digits
Circuit Swtch - dial digits"

 ::= { ibmappnLocalEnTgEntry 6 }

ibmappnLocalEnTgOperational OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether the Transmission Group is operational."

 ::= { ibmappnLocalEnTgEntry 7 }

ibmappnLocalEnTgCpCpSession OBJECT-TYPE
    SYNTAX INTEGER {yes(1), no(2)}
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Indicates whether CP-CP sessions are supported on this TG."

 ::= { ibmappnLocalEnTgEntry 8 }

ibmappnLocalEnTgEffCap OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The effective capacity is an integer value that indicates
        the actual kilo bits per second.
        It is derived from the link bandwidth and maximum load
        factor with the range of 0 thru 603,979,776."

 ::= { ibmappnLocalEnTgEntry 9 }

ibmappnLocalEnTgConnCost OBJECT-TYPE
    SYNTAX INTEGER (0..255)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Cost per connect time: a value representing
        the relative cost per unit of time to use
        the TG. Range is from 0, which means no cost,
        to 255."

 ::= { ibmappnLocalEnTgEntry 10 }
```

```

ibmappnLocalEnTgByteCost OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative cost of transmitting a byte over this link.
    Range is from 0, which means no cost, to 255."
::= { ibmappnLocalEnTgEntry 11 }

ibmappnLocalEnTgSecurity OBJECT-TYPE
SYNTAX INTEGER {
    nonsecure(1),                      --X'01'
    publicSwitchedNetwork(32),          --X'20'
    undergroundCable(64),              --X'40'
    secureConduit(96),                --X'60'
    guardedConduit(128),              --X'80'
    encrypted(160),                  --X'A0'
    guardedRadiation(192)            --X'C0'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Security level for this TG."
::= { ibmappnLocalEnTgEntry 12 }

ibmappnLocalEnTgDelay OBJECT-TYPE
SYNTAX INTEGER {
    minimum(0),                         --X'00'
    negligible(384),                   --X'4C'
    terrestrial(9216),                --X'71'
    packet(147456),                  --X'91'
    long(294912),                     --X'99'
    maximum(2013265920)             --X'FF'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Relative amount of time that it takes for a signal to
    travel the length of the logical link. This time is
    represented in micro seconds, with some of the more
    common values enumerated."
::= { ibmappnLocalEnTgEntry 13 }

ibmappnLocalEnTgModemClass OBJECT-TYPE
SYNTAX INTEGER (0..65535)

```

```

ACCESS read-only
STATUS mandatory
DESCRIPTION
    "This is used to have multiple images for a
     connection network. For a connection network
     it is the same as in the TG vector and for
     a non connection network it is zero."

 ::= { ibmappnLocalEnTgEntry 14 }

ibmappnLocalEnTgUsr1 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "First user-defined TG characteristic
     for this TG. Range of values is 0-255."

 ::= { ibmappnLocalEnTgEntry 15 }

ibmappnLocalEnTgUsr2 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Second user-defined TG characteristic
     for this TG. Range of values is 0-255." 

 ::= { ibmappnLocalEnTgEntry 16 }

ibmappnLocalEnTgUsr3 OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Third user-defined TG characteristic
     for this TG. Range of values is 0-255." 

 ::= { ibmappnLocalEnTgEntry 17 }

-- **** The APPN Directory group ****
ibmappnDir      OBJECT IDENTIFIER ::= { ibmappn 5 }
ibmappnDirPerf  OBJECT IDENTIFIER ::= { ibmappnDir 1 }

-- The APPN Directory Group

-- The APPN Directory Database

```

```

-- Each APPN network node maintains directories containing
-- information on which LUs (applications) are available and
-- where they are located. LUs can be located within an APPN
-- network node or in any of the attached end nodes.

-- Max Cache Directory Entries
-- Current Number of Cache Entries
-- Current Number Home Entries
-- Current Number of Registered Entries
-- number of directed locates sent
-- number of directed locates received
-- number of broadcast locates sent
-- number of broadcast locates received
-- Number of locates returned with a found
-- Number of locates returned with a not found
-- Number of outstanding Locates
-- Directory table (Repeated for each Serving NN)

-- Serving Network Node Fully Qualified CP Name

-- LU Groups within Directory table (one for each LU)

-- Fully-qualified LU Name
-- Owning fully-qualified CP Name
-- TP Name
-- Resource location (local/domain/cross-domain)
-- Entry type (home/Register/cache)
-- Wildcard (yes/no)

```

```

ibmappnDirMaxCaches OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Maximum number of cache entries allowed. This
         is an administratively assigned value."

```

```
 ::= { ibmappnDirPerf 1 }
```

```

ibmappnDirCurCaches OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Current number of cache entries."

```

```
 ::= { ibmappnDirPerf 2 }
```

```
ibmappnDirCurHomeEntries OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Current number of home entries."
    ::= { ibmappnDirPerf 3 }

ibmappnDirRegEntries OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Current number of registered entries."
    ::= { ibmappnDirPerf 4 }

ibmappnDirInLocates OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of directed locates received."
    ::= { ibmappnDirPerf 5 }

ibmappnDirInBcastLocates OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of broadcast locates received."
    ::= { ibmappnDirPerf 6 }

ibmappnDirOutLocates OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Number of directed locates sent."
    ::= { ibmappnDirPerf 7 }

ibmappnDirOutBcastLocates OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
```

```
STATUS mandatory
DESCRIPTION
    "Number of broadcast locates sent."
::= { ibmappnDirPerf 8 }

ibmappnDirNotFoundLocates OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of directed locates returned with a 'not found'."
::= { ibmappnDirPerf 9 }

ibmappnDirNotFoundBcastLocates OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Number of broadcast locates returned with
     a not found."
::= { ibmappnDirPerf 10 }

ibmappnDirLocateOutstands OBJECT-TYPE
SYNTAX Gauge
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Current number of outstanding locates,
     both directed and broadcast. This value
     varies. A value of zero indicates
     that no locates are unanswered."
::= { ibmappnDirPerf 11 }

--APPN Directory table

-- This table contains information about all known
-- LUs and TPs.

ibmappnDirTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnDirEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
```

```

        "Table containing information about
        all known LUs and TPs."

 ::= { ibmappnDir 2 }

ibmappnDirEntry OBJECT-TYPE
    SYNTAX IbmapnDirEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This table is indexed by the LU name."

INDEX
    {ibmappnDirLuName}

 ::= { ibmappnDirTable 1 }

IbmappnDirEntry ::= SEQUENCE {
    ibmappnDirLuName          DisplayString,
    ibmappnDirServerName      DisplayString,
    ibmappnDirLuOwnerName     DisplayString,
    ibmappnDirLuLocation      INTEGER,
    ibmappnDirType            INTEGER,
    ibmappnDirWildCard        INTEGER
}

ibmappnDirLuName      OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Fully-qualified network LU name in the
        domain of the serving network node."

 ::= { ibmappnDirEntry 1 }

ibmappnDirServerName      OBJECT-TYPE
    SYNTAX DisplayString (SIZE (3..17))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Fully-qualified control point (CP) name of the
        network node server. For unassociated end node
        entries, the end node fully-qualified name
        is returned."

 ::= { ibmappnDirEntry 2 }

```

```

ibmappnDirLuOwnerName      OBJECT-TYPE
SYNTAX DisplayString (SIZE (3..17))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Fully-qualified CP name of the node at which
     the LU is located. This name is the same as the
     serving NN name when the LU is located at a
     network node or an unassociated end node. It is
     also the same as the fully-qualified LU name
     when this is the control point LU for this node."
::= { ibmappnDirEntry 3 }

```

```

ibmappnDirLuLocation        OBJECT-TYPE
SYNTAX INTEGER {
    local(1),      --Local
    domain(2),     --Domain
    xdomain(3)     --Cross Domain
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Specifies the location of the LU."
::= { ibmappnDirEntry 4 }

```

```

ibmappnDirType              OBJECT-TYPE
SYNTAX INTEGER {
    home(1),       --defined as home entry
    cache(2),      --learned over time
    registered(3)  --registered by end node
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Directory types are:
     1 - Home
          The LU is in the domain of the local network node
          and the LU information has been configured at the
          local node.

     2 - Cache
          The LU has previously been located by a broadcast
          search and the location information has been saved.

     3 - Register"

```

The LU is at an end node that is in the domain of the local network node. Registered entries are registered by the served end node."

```
: := { ibmappnDirEntry 5 }
```

```
ibmappnDirWildCard          OBJECT-TYPE
SYNTAX INTEGER {
    other(1),
    explicit-entry(2),
    partial-wildcard(3),
    full-wildcard(4)
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "1 - Other means unknown type of LU entry.
     2 - Explicited-entry means the full LUNAME will be used
         for locating this LU.
     3 - Partial-wildcard means only the non-blank portions
         of the LUNAME will be used for locating this LU.
     4 - Full-wildcard means all LUNAMES will be directed
         to this LU."
: := { ibmappnDirEntry 6 }
```

```
-- ***** The APPN Class of Service group *****
```

```
ibmappnCos OBJECT IDENTIFIER ::= { ibmappn 6 } --APPN COS
```

```
-- The APPN Class of Service (COS)
```

```
-- Class of Service is a means of expressing the quality of the routes
-- and the transmission priority of traffic which flows on these routes.
-- The quality of routes is specified by two tables, a COS weight table
-- for TGs and a COS weight table for nodes. These COS tables are
-- administratively assigned at each APPN node. Seven default tables
```

```
-- for TGs and a COS weight table for Nodes. These COS tables are
-- administratively assigned at each APPN node with seven default tables
-- being provided by IBM.
```

```
--
```

```
--
```

```
-- COS Name
```

```
-- Unqualified name identifying the class of service.
```

```
-- Transmission priority
```

```
--      Transmission priority associated with this class of service
-- COS Node Row Table
--      At least one node row must be specified. The default
--      COS tables specify 8 rows.
-- Node Row Weight
--      Numeric value between 0 and 255 inclusive indicating
--      the weight associated with this row.
-- Route addition resist (min)
--      Numeric value between 0 and 255 inclusive indicating
--      the minimum route addition resistance for this row.
-- Route addition resist (max)
--      Numeric value between 0 and 255 inclusive indicating
--      the maximum route addition resistance for this row.
-- Congestion      (min)
--      Indicates whether this class of service for this row
--      will accept congestion. Yes or No must be specified.
-- Congestion      (max)
--      Indicates whether this Class of Service for this row
--      will accept congestion. Yes or No must be specified.
--
-- COS TG Row table
--      At least one TG row must be specified with the defaults
--      COS tables specify 8 rows.
-- TG Row Weight
--      Numeric value between 0 and 255 inclusive indicating
--      the weight associated with this row.
-- Effective capacity (min)
--      Indicates the lowest acceptable value for this row.
-- Effective capacity (max)
--      Indicates the highest required value for this row.
-- Cost per connect time (min)
--      Indicates the lowest connect cost per unit time value
--      for this row. This value is between 0 and 255 inclusive.
-- Cost per connect time (max)
--      Indicates the highest connect cost per unit time value
--      for this row. This value is between 0 and 255 inclusive.
-- Cost per byte     (min)
--      Indicates the lowest cost per byte value
--      for this row. This value is between 0 and 255 inclusive.
-- Cost per byte     (max)
--      Indicates the highest cost per byte value
--      for this row. This value is between 0 and 255 inclusive.
-- Security        (min)
--      Indicates the lowest acceptable value for security
--      for this row. This value is one of seven values.
-- Security        (max)
--      Indicates the highest acceptable value for security
--      for this row. This value is one of seven values.
```

```
-- Propagation delay (min)
-- Indicates the lowest acceptable propagation delay value
-- for this row.
-- Propagation delay (max)
-- Indicates the highest acceptable propagation delay value
-- for this row.
-- User defined 1 (min)
-- Indicates the lowest acceptable value
-- for this row. This value is between 0 and 255 inclusive.
-- User defined 1 (max)
-- Indicates the highest acceptable value
-- for this row. This value is between 0 and 255 inclusive.
-- User defined 2 (min)
-- Same as user defined 1
-- User defined 2 (max)
-- Same as user defined 1
-- User defined 3 (min)
-- Same as user defined 1
-- User defined 3 (max)
-- Same as user defined 1
--
--
--
--Due to SNMP ASN.1 limitations the COS table is defined
--in the following format.
--
-- MODE name table
-- MODE Name (index)
-- COS Name
--
-- COS name table
-- COS Name (index)
-- Transmission priority
--
-- COS node row table
-- COS Name (index1)
-- Index2
-- Node Row Weight
-- Rte addition resist (min)
-- Rte addition resist (max)
-- Congestion (min)
-- Congestion (max)
--
-- COS TG row table
-- COS Name (index1)
-- Index
-- TG Row Weight
-- Effective capacity (min)
```

```

-- Effective capacity      (max)
-- Cost per conn time    (min)
-- Cost per conn time    (max)
-- cost per byte         (min)
-- cost per byte         (max)
-- Security               (min)
-- Security               (max)
-- Propagation delay     (min)
-- Propagation delay     (max)
-- User defined 1         (min)
-- User defined 1         (max)
-- User defined 2         (min)
-- User defined 2         (max)
-- User defined 3         (min)
-- User defined 3         (max)
--
-- ****

```

**ibmappnCosModeTable** OBJECT-TYPE  
SYNTAX SEQUENCE OF IbmappnCosModeEntry  
ACCESS not-accessible  
STATUS mandatory  
DESCRIPTION  
"Table representing all of the defined  
mode names for this node. The table  
contains the matching COS name."  
 $::= \{ ibmappnCos 1 \}$

**ibmappnCosModeEntry** OBJECT-TYPE  
SYNTAX IbmappnCosModeEntry  
ACCESS not-accessible  
STATUS mandatory  
DESCRIPTION  
"This table is indexed by the Mode Name."  
INDEX  
 $\{ ibmappnCosModeName \}$   
 $::= \{ ibmappnCosModeTable 1 \}$

IbmappnCosModeEntry ::= SEQUENCE {  
 ibmappnCosModeName DisplayString,  
 ibmappnCosModeCosName DisplayString  
}

**ibmappnCosModeName** OBJECT-TYPE

```

SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for this
    mode entry."

 ::= { ibmappnCosModeEntry 1 }

ibmappnCosModeCosName OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "An administratively assigned name for this
        Class of Service."

 ::= { ibmappnCosModeEntry 2 }

-- ****

ibmappnCosNameTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnCosNameEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "Table representing all of the defined class-of-service
        names for this node. The COS node and TG tables are
        accessed using the same index, which is the COS name."

 ::= { ibmappnCos 2 }

ibmappnCosNameEntry OBJECT-TYPE
    SYNTAX IbmappnCosNameEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "The COS name is the index to this table."

INDEX
    {ibmappnCosName}

 ::= { ibmappnCosNameTable 1 }

IbmappnCosNameEntry ::= SEQUENCE {
    ibmappnCosName          DisplayString,
    ibmappnCosTransPriority  INTEGER
}

```

}

```

ibmappnCosName          OBJECT-TYPE
    SYNTAX DisplayString (SIZE (1..8))
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Administratively-assigned name for this
         class of service."

::= { ibmappnCosNameEntry 1 }

ibmappnCosTransPriority OBJECT-TYPE
    SYNTAX INTEGER {
        low(1),                  --X'01'
        medium(2),                --X'02'
        high(3),                  --X'03'
        network(4)                --X'04'
    }
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Transmission priority for this
         class of service.  Values are:
          Low
          Medium
          High
          Network"
        "
::= { ibmappnCosNameEntry 2 }

ibmappnCosNodeRowTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IbmappnCosNodeRowEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION
        "This table contains all node-row information for all
         class of service in this node."

::= { ibmappnCos 3 }

ibmappnCosNodeRowEntry OBJECT-TYPE
    SYNTAX IbmappnCosNodeRowEntry
    ACCESS not-accessible
    STATUS mandatory
    DESCRIPTION

```

"The COS name is the first index and a integer  
is the second index to insure a unique index."

## INDEX

```
{ibmappnCosNodeRowName,
 ibmappnCosNodeRowIndex}
```

```
::= { ibmappnCosNodeRowTable 1 }
```

```
IbmappnCosNodeRowEntry ::= SEQUENCE {
    ibmappnCosNodeRowName          DisplayString,
    ibmappnCosNodeRowIndex         INTEGER,
--Node Row Group
    ibmappnCosNodeRowWgt          DisplayString,
    ibmappnCosNodeRowResistMin    INTEGER,
    ibmappnCosNodeRowResistMax    INTEGER,
    ibmappnCosNodeRowMinCongestAllow INTEGER,
    ibmappnCosNodeRowMaxCongestAllow INTEGER
}
```

```
ibmappnCosNodeRowName           OBJECT-TYPE
SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for this
     class of service."
```

```
::= { ibmappnCosNodeRowEntry 1 }
```

```
ibmappnCosNodeRowIndex          OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Index of COS name. This same value is used
     to access the node and TG COS tables.
     Range of values is 0-255."
```

```
::= { ibmappnCosNodeRowEntry 2 }
```

--Node Row Group

```
ibmappnCosNodeRowWgt           OBJECT-TYPE
SYNTAX DisplayString
ACCESS read-only
STATUS mandatory
DESCRIPTION
```

```
        "Weight to be associated with the nodes  
        that fit the criteria specified by this node row."  
  
 ::= { ibmappnCosNodeRowEntry 3 }  
  
ibmappnCosNodeRowResistMin      OBJECT-TYPE  
    SYNTAX INTEGER      (0..255)  
    ACCESS read-only  
    STATUS mandatory  
    DESCRIPTION  
        "Minimum route addition resistance value  
        for this node. Range of values is 0-255.  
        The lower the value, the more desirable  
        the node is for intermediate routing."  
  
 ::= { ibmappnCosNodeRowEntry 4 }  
  
ibmappnCosNodeRowResistMax      OBJECT-TYPE  
    SYNTAX INTEGER      (0..255)  
    ACCESS read-only  
    STATUS mandatory  
    DESCRIPTION  
        "Maximum route addition resistance value  
        for this node. Range of values is 0-255.  
        The lower the value, the more desirable  
        the node is for intermediate routing."  
  
 ::= { ibmappnCosNodeRowEntry 5 }  
  
ibmappnCosNodeRowMinCongestAllow OBJECT-TYPE  
    SYNTAX INTEGER {yes(1), no(2)}  
    ACCESS read-only  
    STATUS mandatory  
    DESCRIPTION  
        "Indicates whether low congestion will be  
        tolerated. The minimum and maximum parameters  
        will allow specifying either low-congested,  
        high-congested, or either to be used."  
  
 ::= { ibmappnCosNodeRowEntry 6 }  
  
ibmappnCosNodeRowMaxCongestAllow OBJECT-TYPE  
    SYNTAX INTEGER {yes(1), no(2)}  
    ACCESS read-only  
    STATUS mandatory  
    DESCRIPTION  
        "Indicates whether high congestion will be  
        tolerated. The minimum and maximum parameters
```

will allow specifying either low-congested,  
high-congested, or either to be used."

```
::= { ibmappnCosNodeRowEntry 7 }
```

```
-- COS TG row table
-- Index
-- TG Row Weight
-- Effective capacity (min)
-- Effective capacity (max)
-- Cost per conn time (min)
-- Cost per conn time (max)
-- cost per byte (min)
-- cost per byte (max)
-- Security (min)
-- Security (max)
-- Propagation delay (min)
-- Propagation delay (max)
-- User defined 1 (min)
-- User defined 1 (max)
-- User defined 2 (min)
-- User defined 2 (max)
-- User defined 3 (min)
-- User defined 3 (max)
--
```

```
ibmappnCosTgRowTable OBJECT-TYPE
SYNTAX SEQUENCE OF IbmappnCosTgRowEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "Table containing all the Tg-row information for all
     class of service defined in this node."
```

```
::= { ibmappnCos 4 }
```

```
ibmappnCosTgRowEntry OBJECT-TYPE
SYNTAX IbmappnCosTgRowEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
    "The TgRowName and the TgRowIndex are the index
     for this table."
```

```
INDEX
    { ibmappnCosTgRowName,
      ibmappnCosTgRowIndex }
```

```

 ::= { ibmappnCosTgRowTable 1 }

IbmappnCosTgRowEntry ::= SEQUENCE {
    ibmappnCosTgRowName                               DisplayString,
    ibmappnCosTgRowIndex                             INTEGER,
--TG Row Group
    ibmappnCosTgRowWgt                               DisplayString,
    ibmappnCosTgRowEffCapMin                         INTEGER,
    ibmappnCosTgRowEffCapMax                         INTEGER,
    ibmappnCosTgRowConnCostMin                       INTEGER,
    ibmappnCosTgRowConnCostMax                      INTEGER,
    ibmappnCosTgRowByteCostMin                      INTEGER,
    ibmappnCosTgRowByteCostMax                      INTEGER,
    ibmappnCosTgRowSecurityMin                      INTEGER,
    ibmappnCosTgRowSecurityMax                      INTEGER,
    ibmappnCosTgRowDelayMin                          INTEGER,
    ibmappnCosTgRowDelayMax                          INTEGER,
    ibmappnCosTgRowUsr1Min                          INTEGER,
    ibmappnCosTgRowUsr1Max                          INTEGER,
    ibmappnCosTgRowUsr2Min                          INTEGER,
    ibmappnCosTgRowUsr2Max                          INTEGER,
    ibmappnCosTgRowUsr3Min                          INTEGER,
    ibmappnCosTgRowUsr3Max                          INTEGER
}

ibmappnCosTgRowName          OBJECT-TYPE
SYNTAX DisplayString (SIZE (1..8))
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Administratively-assigned name for this
     class of service."

 ::= { ibmappnCosTgRowEntry 1 }

ibmappnCosTgRowIndex         OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Index of COS name. This same value is used
     to access the node and TG COS tables."

 ::= { ibmappnCosTgRowEntry 2 }

--TG Row

ibmappnCosTgRowWgt          OBJECT-TYPE

```

```
SYNTAX DisplayString
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Weight to be associated with the nodes
     that fit the criteria specified by this tg-row."
::= { ibmappnCosTgRowEntry 3 }

ibmappnCosTgRowEffCapMin    OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Minimum acceptable speed for this Class of Service.
         The effective capacity is an integer value that indicates
         the actual kilo bits per second.
         It is derived from the link bandwidth and maximum load
         factor with the range of 0 thru 603,979,776."
::= { ibmappnCosTgRowEntry 4 }

ibmappnCosTgRowEffCapMax    OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Maximum acceptable speed for this Class of Service.
         The effective capacity is an integer value that indicates
         the actual kilo bits per second.
         It is derived from the link bandwidth and maximum load
         factor with the range of 0 thru 603,979,776."
::= { ibmappnCosTgRowEntry 5 }

ibmappnCosTgRowConnCostMin OBJECT-TYPE
    SYNTAX INTEGER (0..255)
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "Minimum acceptable cost per connect time
         for this Class of Service.
         Cost per connect time: a value representing
         the relative cost per unit of time to use
         the TG. Range is from 0, which means no cost,
         to 255."
::= { ibmappnCosTgRowEntry 6 }
```

```

ibmappnCosTgRowConnCostMax OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum acceptable cost per connect time
     for this Class of Service.
    Cost per connect time: a value representing
     the relative cost per unit of time to use
     the TG. Range is from 0, which means no cost,
     to 255."
::= { ibmappnCosTgRowEntry 7 }

ibmappnCosTgRowByteCostMin OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Minimum acceptable cost per byte
     for this Class of Service."
::= { ibmappnCosTgRowEntry 8 }

ibmappnCosTgRowByteCostMax OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum acceptable cost per byte
     for this Class of Service."
::= { ibmappnCosTgRowEntry 9 }

ibmappnCosTgRowSecurityMin OBJECT-TYPE
SYNTAX INTEGER {
    nonsecure(1),          --X'01'
    publicSwitchedNetwork(32), --X'20'
    undergroundCable(64),   --X'40'
    secureConduit(96),      --X'60'
    guardedConduit(128),    --X'80'
    encrypted(160),         --X'A0'
    guardedRadiation(192)   --X'C0'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Minimum acceptable security"

```

```

for this Class of Service."}

::= { ibmappnCosTgRowEntry 10 }

ibmappnCosTgRowSecurityMax OBJECT-TYPE
SYNTAX INTEGER {
    nonsecure(1),                      --X'01'
    publicSwitchedNetwork(32),          --X'20'
    undergroundCable(64),              --X'40'
    secureConduit(96),                --X'60'
    guardedConduit(128),              --X'80'
    encrypted(160),                  --X'A0'
    guardedRadiation(192)             --X'C0'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum acceptable security
     for this Class of Service."

::= { ibmappnCosTgRowEntry 11 }

ibmappnCosTgRowDelayMin OBJECT-TYPE
SYNTAX INTEGER {
    minimum(0),                         --X'00'
    negligible(384),                   --X'4C'
    terrestrial(9216),                --X'71'
    packet(147456),                   --X'91'
    long(294912),                     --X'99'
    maximum(2013265920)              --X'FF'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Minimum acceptable propagation delay for this class of service.
     Relative amount of time that it takes for a signal to travel
     the length of the logical link. This time is represented in
     micro seconds, with the more values enumerated."
::= { ibmappnCosTgRowEntry 12 }

ibmappnCosTgRowDelayMax OBJECT-TYPE
SYNTAX INTEGER {
    minimum(0),                         --X'00'
    negligible(384),                   --X'4C'
    terrestrial(9216),                --X'71'
    packet(147456),                   --X'91'
    long(294912),                     --X'99'
}

```

```

maximum(2013265920)          --X'FF'
}
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Maximum acceptable propagation delay for this class of service.
Relative amount of time that it takes for a signal to travel
the length of the logical link. This time is represented in
micro seconds, with the more values enumerated."

 ::= { ibmappnCosTgRowEntry 13 }

ibmappnCosTgRowUsr1Min OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Minimum acceptable value for this
user defined characteristic.
Range of values is 0-255."

 ::= { ibmappnCosTgRowEntry 14 }

ibmappnCosTgRowUsr1Max OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Maximum acceptable value for this
user defined characteristic.
Range of values is 0-255."

 ::= { ibmappnCosTgRowEntry 15 }

ibmappnCosTgRowUsr2Min OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"Minimum acceptable value for this
user defined characteristic.
Range of values is 0-255."

 ::= { ibmappnCosTgRowEntry 16 }

ibmappnCosTgRowUsr2Max OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only

```

```
STATUS mandatory
DESCRIPTION
    "A Maximum acceptable value for this
     user defined characteristic."
 ::= { ibmappnCosTgRowEntry 17 }

ibmappnCosTgRowUsr3Min OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Minimum acceptable value for this
     user defined characteristic.
     Range of values is 0-255."
 ::= { ibmappnCosTgRowEntry 18 }

ibmappnCosTgRowUsr3Max OBJECT-TYPE
SYNTAX INTEGER (0..255)
ACCESS read-only
STATUS mandatory
DESCRIPTION
    "Maximum acceptable value for this
     user defined characteristic.
     Range of values is 0-255."
 ::= { ibmappnCosTgRowEntry 19 }

END
```

### 3.0 Acknowledgements

Thanks go to David Chen, Leo Temoshenko, and Mike Allen for their contribution and support through the development process.

### 4.0 Security Considerations

Security issues are not discussed in this memo.

## 5.0 Authors' Addresses

William F. McKenzie  
IBM Networking Systems  
P. O. Box 12195  
Research Triangle Park, NC 27709  
US

Phone: +1 919 254 5705  
EMail: mckenzie@ralvma.vnet.ibm.com

Jia-bing R. Cheng  
IBM Networking Systems  
P. O. Box 12195  
Research Triangle Park, NC 27709  
US

Phone: +1 919 254 4434  
EMail: cheng@ralvm6.vnet.ibm.com