

Examples of *multiaudience* package use

Boris Veytsman

Date: 2015/07/11 22:49:40

Contents

1	Introduction	3
2	The \CurrentAudience command	3
3	The \showto command	3
4	The shownto environment	3
5	Use of verbatim text	4
6	Syntactic sugar	4
6.1	Not for admins	4

1 Introduction

We defined three audiences:

```
\SetNewAudience{admins}  
\SetNewAudience{devs}  
\SetNewAudience{execs}
```

2 The \CurrentAudience command

The current audience is \CurrentAudience.

The current audience is execs,devs.

3 The \showto command

Note the nesting here:

```
\showto{admins}{This text is visible to admins only\footnote{And  
admins see a footnote}.}  
\showto{admins, devs}{This text is visible to admins and  
devs. \showto{devs}{This text is visible to devs.}}  
\showto{-, admins}{This text is \emph{not} visible to admins.}  
This text is visible to everybody\footnote{And everybody sees a  
footnote}.
```

This text is visible to admins and devs. This text is visible to devs. This text is *not* visible to admins. This text is visible to everybody¹.

4 The shownto environment

```
\begin{shownto}{admins}  
    This is for admins only.  
\end{shownto}  
  
\begin{shownto}{-, admins}  
    This is for everybody \emph{but} admins.  
\end{shownto}
```

This is for everybody *but* admins.

¹And everybody sees a footnote

5 Use of verbatim text

```
\begin{shownto}{-,execs}
We cannot use \texttt{verbatim} inside shownto, but we can use
\texttt{input} with \texttt{verbatim} inside.
```

We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a\$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\input{verbatim}

We also can use \texttt{path} and \texttt{url} from hyperref package:
\path{a\$2}, \url{http://borisv.lk.net/cv/cv.html\#Publications}.
\end{shownto}

Another option is the use of \SaveVerb and friends from *fancyvrb* package:

```
\begin{SaveVerbatim}{SavedVerb}
This is a verbatim line: ~!@#$%^&*{}:"‘’<>?
\end{SaveVerbatim}

\begin{shownto}{-,devs}
\UseVerbatim{SavedVerb}
\end{shownto}
```

6 Syntactic sugar

We have a special footnote command\Footnote{admins}{This footnote is
for admins only.}.

We have a special footnote command.

```
\begin{Subsection}{admins}[Admins-only subsection]{This subsection is
visible only to admins}
We have special sectioning commands.
\end{Subsection}

\begin{Subsection}{-,admins}[Not for admins]{This subsection is not
visible to admins}
Another example. \shownto{devs}{This is visible to devs only.}
\end{Subsection}
```

6.1 This subsection is not visible to admins

Another example. This is visible to devs only.