

# The HEP-MATH package\*

## Extended math macros

Jan Hajer<sup>†</sup>

2023/07/01

### Abstract

The HEP-MATH package provides some additional features beyond the MATHTOOLS and AMSMATH packages.

To use the package place `\usepackage{hep-math}` in the preamble.

The MATHTOOLS [1] package is loaded, which in turn loads the *AMS-LATEX* AMSMATH [2] package. Horizontal spacing in inline equations and page breaks in block equations are marginally adjusted.

`\left` Spacing around `\left` and `\right` is fixed with the MLEFTRIGHT package [3].

`\right`

## 1 Macros

`\mathdef` The `\mathdef<name>[<arguments>]{<code>}` macro (re-)defines macros only within math mode without changing the text mode definition.

`\i` The imaginary unit `\i` and the differential `\d` are defined using this functionality.

`\d` The `\overline` macro is adjusted to work also outside of math mode using the SOULUTF8 [4] package.

`\oset` A better looking over left right arrow is defined i.e.  $\vec{\partial}$  using a new `\oset{<over>}{<math>}` functionality.

`\overleft` Diagonal matrix `\diag`, signum `\sgn`, trace `\tr`, `\Tr`, and `\rank` operators are defined.

`\overright` The real and imaginary projectors are redefined to look like ordinary operators.

`\overleftright` `\cos` and `\tan` are adjusted to have the same height as `\sin`.

`\diag` `\arccsc` and other inverse trigonometric functions are defined.

`\Re`

### 1.1 Fractions and units

`\Im`

`\sin` The correct spacing for units is provided by the macro `\unit[<value>]{<unit>}` from the UNITS package [5] which can also be used in text mode. The macro `\inv[<power>]{<text>}` allows to avoid math mode also for inverse units such as  $5 \text{ fb}^{-1}$  typeset via `\unit[5]{\inv{fb}}`.

`\cos` The `\frac{<number>}{<number>}` macro is accompanied by `\nicefrac{<number>}{<number>}`, `\textfrac{<number>}{<number>}`, and `\flatfrac{<number>}{<number>}` leading to  $\frac{1}{2}$ ,  $\frac{1}{2}$ ,  $\frac{1}{2}$ , and  $\frac{1}{2}$ . The `\textfrac` macro is mostly intended if a font with oldstyle numerals is used.

`\unit`

\*This document corresponds to HEP-MATH v1.2.

`\inv`

<sup>†</sup>jan.hajer@tecnico.ulisboa.pt

`\nicefrac`

`\flatfrac`

`\textfrac`

Some macros of the PHYSICS package [6] are reimplemented with a more conventional typesetting in mind. Finer details about mathematical typesetting can be found in [7].

## 1.2 Differentials and derivatives

**\differential** The three macros `\differential{<symbol>}`, `\newderivative {\name}{<symbol>}`, and `\newpartialderivative {\name}{<symbol>}` allow to define a differential with correct spacing, a derivative using this differential, and if necessary a partial derivative that can handle three dimensional derivatives.

**\newpartialderivative** These macros are used for the usual differential and derivative, producing  $dx$  via `\d x` and

<code>\d</code>	$\text{\dv}[f]x$	$\text{\dv*}[f]x^n$	$\text{\dv}[f]x^{\sim n}$	$\text{\dv*}[f]x^{\sim n}$
<code>\dv</code>	$\frac{df}{dx}$	$d^n f / dx^n$	$\frac{d^n f}{dx^n}$	$d^n f / dx^n$
	$\text{\dv xf}$	$\text{\dv*xf}$	$\text{\dv x*f}$	$\text{\dv*x*f}$
	$\frac{d}{dx} f$	$d/dx f$	$\frac{d}{dx} f$	$d/dx f$

via `\dv*[<f>]{<x>}^{<n>}`. Upright differential can be produced via `\renewcommand{\diffsymbol}{\mathrm{d}}`. The differential takes care of the correct spacing as long as it is placed at the end of the integral  $\int f(x) dx$ . In order to archive correct spacing when it is placed at the beginning of the integral it is advisable to place the whole expression in a `\mathop{\int \d x} f(x)` such that  $\int dx f(x)$ .

**\pd** Similarly a partial differential and derivative are defined that can be used according to  
**\pdv** `\pdv*[<f>]{<x>}^{<a>}{<y>}^{<b>}{<z>}^{<c>}`.

<code>\pdv[f]x</code>	$\text{\pdv}[f]x[y]$	$\text{\pdv}[f]x^{\sim 3}$	$\text{\pdv}[f]x^{\sim 2}[y]$
$\frac{\partial f}{\partial x}$	$\frac{\partial^2 f}{\partial x \partial y}$	$\frac{\partial^3 f}{\partial x^3}$	$\frac{\partial^3 f}{\partial x^2 \partial y}$
$\text{\pdv}[f]x^{\sim 2}[y]^{\sim 3}$	$\text{\pdv}[f]x[y]^{\sim 3}$	$\text{\pdv x}[y]f$	
$\frac{\partial^5 f}{\partial x^2 \partial y^3}$	$\frac{\partial^4 f}{\partial x \partial y^3}$	$\frac{\partial^2}{\partial x \partial y} f$	

**\var** Similarly a functional variation and functional derivative are defined.

**\fdv** The `\cancel{<characters>}` macro from the CANCEL package [8] and the `\slashed{<character>}` macro from the SLASHED package [9] allow to `\cancel` math and use the Dirac slash notation i.e.  $\not{f}$ , respectively.  
**\cancel**  
**\slashed**

## 1.3 Paired delimiters

<code>\abs</code>	$ x $	<code>\norm x</code>	$\ x\ $	<code>\norm[2] x</code>	$\ x\ _2$	<code>\norm*[2] x</code>	$\ x\ _2$
<code>\norm</code>							
<code>\eval</code>							
<code>\order</code>	$\mathcal{O}(x)$	$x_o^{\sim \infty}$	$x_0^{\infty}$	$\text{\eval x}_o^{\sim \infty}$	$x^{\infty}$	$\text{\eval* x}_o^{\sim \infty}$	$x^{\infty}$

**\newpair** The `\newpair{<name>}{<left delim>}{<right delim>}_{<subscript>}^{<superscript>}` macro is defined and used for the definition of (anti-)commutators and Poisson brackets.

<code>\comm</code>	$\{x, y\}$	<code>\pb xy</code>	$[x, y]$	<code>\comm xy</code>	$\{x, y\}$
<code>\acomm</code>					

They can easily be redefined using e.g. \newpair\comm\lbrack\rbrack\_-.

\bra Macros for the bra-ket notation are introduced.

<code>\ket</code>	<code>\bra x</code>	<code>\ket x</code>	<code>\braket xy</code>	<code>\ketbra xy</code>
<code>\braket</code>	$\langle x  $	$  x \rangle$	$\langle x   y \rangle$	$  x \rangle \langle y  $
<code>\ketbra</code>	<code>\mel xyz</code>	<code>\ev x</code>	<code>\ev[\Omega] x</code>	<code>\vev x</code>

\mel Macros for row and column vectors are introduced together with a symbol for transpose vectors.

```
\ev \column{x,y,z} \row{x,y,z}^\trans
\vev
\column \begin{pmatrix} x \\ y \\ z \end{pmatrix} (x, y, z)^\text{T}
\row
```

## 2 Environments

**eqnarray** The `eqnarray` environment is deprecated, the `split`, `multiline`, `align`, `multlined`, `aligned`, `alignedat`, and `cases` environments of the `AMSMATH` and `MATHTOOLS` packages should be used instead.

**equation** Use the equation environment for short equations.

```
\begin{equation}
  \left = \right .
\end{equation} .
```

**multiline** Use the `multiline` environment for longer equations.

```
\begin{multiline}
  left = right 1 \\
  + right 2 \ .
\end{multiline}
```

**split** Use the `split` sub environment for equations in which multiple equal signs should be aligned.

```
\begin{equation} \begin{split}
  \text{left} &= \text{right } 1 \\
  &= \text{right } 2 \ .
\end{split} \end{equation} \quad (3)
```

**align** Use the `align` environment for the vertical alignment and horizontal distribution of multiple equations.

```
\begin{subequations} \begin{align}
  \text{left} &= \text{right} \ , \ & \boxed{\text{left}} &= \boxed{\text{right}} \ , \quad (4a) \\
  \text{left} &= \text{right} \ , \ \\
  \text{left} &= \text{right} \ , \ & \boxed{\text{left}} &= \boxed{\text{right}} \ , \quad (4b) \\
  \text{left} &= \text{right} \ .
\end{align} \end{subequations}
```

**aligned** Use the `aligned` environment within a `equation` environment if the aligned equations should be labeled with a single equation number.

**multlined** Use the `multlined` environment if either `split` or `align` contain very long lines.

```
\begin{equation} \begin{split}
  left &= right 1 \\ &=
  \begin{multlined}[t]
    right 2 \\ + right 3 .
  \end{multlined}
\end{split} \end{equation}
```

$$\left. \begin{aligned} \boxed{\text{left}} &= \boxed{\text{right 1}} \\ &= \boxed{\text{right 2}} \\ &\quad \boxed{\text{+ right 3}} . \end{aligned} \right\} \quad (5)$$

- alignat** Use the `alignat` environment together with the `\mathllap` macro for the alignment of multiple equations with vastly different lengths.

```
\begin{subequations}
\begin{alignat}{2}
  \text{left} &= \text{long right} && , \\ 
  \text{le. 2} &= \text{ri. 2} & \text{le. 3} &= \text{ri. 3} .
\end{alignat}
\end{subequations}
```

$$\left. \begin{aligned} \boxed{\text{left}} &= \boxed{\text{long right}} , \\ \boxed{\text{le. 2}} &= \boxed{\text{ri. 2}} , \quad \boxed{\text{le. 3}} = \boxed{\text{ri. 3}} . \end{aligned} \right\} \quad (6a)$$

$$\left. \begin{aligned} \boxed{\text{le. 2}} &= \boxed{\text{ri. 2}} , \quad \boxed{\text{le. 3}} = \boxed{\text{ri. 3}} . \end{aligned} \right\} \quad (6b)$$

As a rule of thumb if you have to use `\notag`, `\nonumber`, or perform manual spacing via `\quad` you are probably using the wrong environment.

## A Implementation

<`*package`>

Load the `MATHTOOLS` package [1] which loads the `AMSMATH` package [2]. Allow page breaks within equations if necessary. Adjust the thick and med mu skips slightly.

```
1 \RequirePackage{mathtools}
2 \mathtoolsset{centercolon}
3 \allowdisplaybreaks[1]
4 \thickmuskip=5mu plus 3mu minus 1mu
5 \medmuskip=4mu plus 2mu minus 3mu
```

- \mathdef** Define the `\mathdef{<name>}[<arguments>]{<macro>}` macro which (re-)defines macros in math mode only. This macro is implemented using the `XPARSE` package [10].

```
6 \RequirePackage{xparse}
7 \DeclareDocumentCommand{\mathdef}{m0{0}om}{%
8   \expandafter\let\csname hep@text\string#1\endcsname=\relax
9   \expandafter\newcommand\csname hep@math\string#1\relax
10 \IfNoValueTF{#3}{\endcsname[#2]}{\endcsname[#2][#3]}{#4}
11 \ DeclareRobustCommand#1{%
12   \ifmmode
13     \expandafter\let\expandafter\next\csname%
14     hep@math\string#1\endcsname%
15   \else
16     \expandafter\let\expandafter\next\csname%
17     hep@text\string#1\endcsname%
18   \fi
19   \next
20 }%
```

21 }

\i Provide an upright imaginary unit in math mode.

```
22 \newcommand{\imaginaryunit}{\text{i}}
23 \AtBeginDocument{\mathdef{\i}{\imaginaryunit}}
```

\overline Redefine \overline to be a text macro using the SOULUTF8 package [4]. Extend it as a math macro with the original definition from the AMSMATH package [2].

```
24 \RequirePackage{soulutf8}
25 % \def\overline#1{{\renewcommand{\ULdepth}{-1.9ex}{}\uline{#1}}}
26 \newcommand\textoverline[1]{{\setul{-1.9ex}{}\ul{#1}}}
27 \let\overline\textoverline
28 \DeclareRobustCommand{\overline}[1]{\overline{#1}}
29 \mathdef{\overline}{\overline}
30 \newcommand\hep@widebar[1]{%
31   \mkern2.5mu\overline{\mkern-2.5mu#1\mkern-.5mu}\mkern.5mu%
32 }
33 \newcommand\widebar[1]{%
34   \settowidth{\dimen0}{\ensuremath{#1}}%
35   \ifdim\dimen0>.475em\hep@widebar{#1}\else\bar{#1}\fi%
36 }
```

\oset Define a new overset macro \oset[*offset*]{*over*}{*base*}

```
37 \newcommand{\oset}[3][-1pt]{%
38   \text{\raisebox{.2ex}{$\mathop{#3}\limits^{\scriptscriptstyle\sim}$}}%
39   \vbox to#1{\kern-2\ex@\hbox{$\scriptscriptstyle#2$}\vss}%
40 }%
41 }
```

\overleftright Define a over left right arrow \overleftright{*base*}.

```
42 \newcommand{\overleft}{[1]{\oset{\leftarrow}{#1}}
43 \newcommand{\overright}{[1]{\oset{\rightarrow}{#1}}
44 \newcommand{\overleftright}{[1]{\oset{\leftrightarrow}{#1}}}
```

\eqnarray Undefine the eqnarray environment if not prevented by package option.

```
45 % \newif\ifhep@eqnarray\hep@eqnarraytrue
46 % \ifhep@eqnarray\else
47 %   \let\eqnarray\@undefined
48 %   \let\endeqnarray\@undefined
49 % \fi
```

## A.1 Operators

\tr Provide the \diag, \sgn, and some other operators.

```
\Tr
\rank 50 \DeclareMathOperator{\tr}{tr}
\erf 51 \DeclareMathOperator{\Tr}{Tr}
\Res
\sgn
\sgn
\diag
```

```

52 \DeclareMathOperator{\rank}{rank}
53 \DeclareMathOperator{\erf}{erf}
54 \DeclareMathOperator{\Res}{Res}
55 \DeclareMathOperator{\sgn}{sgn}
56 \DeclareMathOperator{\diag}{diag}
57 \let\det\relax\DeclareMathOperator{\det}{det}

\Re Redefine the real and imaginary projectors.
\Im
58 \let\Re\relax\DeclareMathOperator{\Re}{Re}
59 \let\Im\relax\DeclareMathOperator{\Im}{Im}

\transpose Define a transpose symbol.
\trans
60 \RequirePackage{amssymb}
61 \newcommand*{\hep@transpose}[2]{\raisebox{\depth}{$\mathop{\mathit{#1}\intercal}\limits^{\mathit{#2}}$}}
62 \newcommand*{\transpose}{\mathop{\mathit{\mathit{mathpalette}\hep@transpose{}}}\limits^{\mathit{mathpalette}\hep@transpose{}}}
63 \let\trans\transpose

A.1.1 Trigonometric functions

\cos Adjust the height of cos and tan to be equal to sin.
\tan
64 \let\cos\undefined\DeclareMathOperator{\cos}{cos\vphantom{i}}
65 \let\tan\undefined\DeclareMathOperator{\tan}{tan\vphantom{i}i}

\arccsc Define arc operators.
\arcsec
\arccot
66 \DeclareMathOperator{\arccsc}{arccsc}
67 \DeclareMathOperator{\arcsec}{arcsec}
68 \DeclareMathOperator{\arccot}{arccot}

\asin Define shorthand for arc operators.
\acos
\atan
69 \DeclareMathOperator{\asin}{asin}
70 \DeclareMathOperator{\acos}{acos}
\acsc
71 \DeclareMathOperator{\atan}{atan}
\asec
72 \DeclareMathOperator{\acsc}{acsc}
73 \DeclareMathOperator{\asec}{asec}
74 \DeclareMathOperator{\acot}{acot}

\csch Define csch and sech operators.
\sech
75 \DeclareMathOperator{\csch}{csch}
76 \DeclareMathOperator{\sech}{sech}

```

## A.2 Units and fractions

\unit Load the UNITS package [5] which provides the \units and \nicefrac macros. Patch the \unit macros to behave like \mathinner within an equation

```
77 \RequirePackage{units}
```

```

78 \let\oldunit\unit
79 \renewcommand{\unit}[2][]{%
80   \ifthenelse{\boolean{mmode}}{%
81     \mathinner{\oldunit[#1]{#2}}%
82   }{%
83     \oldunit[#1]{#2}%
84   }%
85 }
86 \let\oldunitfrac\unitfrac
87 \renewcommand{\unitfrac}[3][]{%
88   \ifthenelse{\boolean{mmode}}{%
89     \mathinner{\oldunitfrac[#1]{#2}{#3}}%
90   }{%
91     \oldunitfrac[#1]{#2}{#3}%
92   }%
93 }

```

\inv Provide a macro for the inverse, useful in combination with the unit macro in text mode.

```
94 \newcommand{\inv}[2][1]{#2\ensuremath{^{-#1}}}
```

`\textfrac` Provide the `\textfrac` macro useful in combination with a font using lining numerals.

```
95 \newcommand{\textfrac}[2]{\ensuremath{\text{\normalsize\nicefrac{\text{#1}}{\text{#2}}}}}
```

\flatfrac Provide a flat fraction.

```

96 \DeclarePairedDelimiterX{\hep@flatfrac}[2]{.}{.}{%
97   \kern-\nulldelimiterspace#1\delimsize/%
98   \hep@left@delim#2\kern-\nulldelimiterspace%
99 }
100 \NewDocumentCommand{\flatfrac}{somm}{%
101   \mathinner{%
102     \IfBooleanTF{#1}{%
103       \hep@flatfrac*{#3}{#4}%
104     }{%
105       \IfNoValueTF{#2}{\hep@left@delim#3\hep@left@delim#4}{%
106         \hep@flatfrac[#2]{#3}{#4}%
107       }%
108     }%
109   }%
110 }%
111 }

```

### A.2.1 Differentials and derivatives

\int Redefine \int.

```
112 \let\hep@int\int
113 \RenewDocumentCommand{\int}{oe{_}^}{%
114   \def\temp{\hep@int_{\IfValueT{#2}{#2}}^{\IfValueT{#3}{#3}}}%
115   \IfValueTF{#1}{\mathop{\temp#1}}{\temp}%
```

116 }

\differential Define a generic differential \differential.

```
117 \newcommand{\differential}[1]{\mathop{}\!\#1}
```

`\newderivative` Define a generic derivative.

```

118 \newcommand\newderivative[2]{
119   \NewDocumentCommand{\#1}{somse{^}}{%
120     \IfBooleanTF{\#4}{%
121       \IfBooleanTF{\#1}{\nicefrac}{\frac}%
122     }{%
123       \IfBooleanTF{\#1}{\flatfrac}{\dfrac}%
124     }{%
125       \mathop{\mathrm{differential}}\nolimits^{\#2} \IfValueT{\#5}{^{\#5\!-1}} \IfValueT{\#2}{^{\#2}}%
126     }{%
127       \mathop{\mathrm{differential}}\nolimits^{\#2} \IfValueT{\#3}{^{\#3}} \IfValueT{\#5}{^{\#5}}%
128     }%
129   }%
130 }

```

`newpartialderivative` Define a generic partial derivative

```

131 \newcommand{\newpartialderivative}[2]{%
132   \NewDocumentCommand{\#1}{s o s E{^}{1} o E{^}{1} o E{^}{1}}{%
133     \def\hep@one{\IfValueTF{\##6}{\##7}{0}}%
134     \def\hep@two{\IfValueTF{\##8}{\##9}{0}}%
135     \def\hep@sum{\the\numexpr\##5+\hep@one+\hep@two\relax}%
136     \IfBooleanTF{\##4}{%
137       \IfBooleanTF{\##1}{\nicefrac}{\frac}\%%
138     }{%
139       \IfBooleanTF{\##1}{\flatfrac}{\dfrac}\%%
140     }{%
141       \mathop{\mathrm{differential}}\nolimits\ifnum\hep@sum=1\relax\else{}^{\hep@sum}\!\fi\!%
142       \IfValueT{\##2}{\##2}\%%
143     }{%
144       \mathop{\mathrm{differential}}\nolimits\!^2\!\mathop{\mathrm{differential}}\nolimits\!^2\!%
145       \IfValueT{\##6}{\mathop{\mathrm{differential}}\nolimits\!^2\!\mathop{\mathrm{differential}}\nolimits\!^2\!}{}%
146       \IfValueT{\##8}{\mathop{\mathrm{differential}}\nolimits\!^2\!\mathop{\mathrm{differential}}\nolimits\!^2\!}{}%
147     }\%%
148   }%
149 }

```

\diffsymbol Define the differential  $d$  and the usual derivative.

```
\diff
  \d 150 \providecommand{\differential}{\mathrm{d}}
\derivative 151 \newcommand{\diff}{\mathrm{d}\!\!} \differential \differential
  \dv 152 \AtBeginDocument{\mathdef{\d}{\diff}}
  153 \newderivative{\derivative}{\differential}
  154 \newcommand\dv{\derivative}
```

```

\partialdifferential Define the partial differential and derivative.
  \pd
\partialderivative155 \newcommand{\partialdifferential}{\differential{\partial}}
  \pdv156 \newcommand{\pd}{\partialdifferential}
  157 \newpartialderivative{\partialderivative}{\partial}
  158 \newcommand{\pdv}{\partialderivative}

\gaugediffsymbol Define the gauge covariant differential \D.
  \gaugediff
    \D159 \providetcommand{\gaugediffsymbol}{\D}
    160 \newcommand{\gaugediff}{\differential{\gaugediffsymbol}}
    161 \newcommand{\D}{\gaugediff}

\covariantdiff Define the covariant differential \cd.
  \cd
    162 \newcommand{\covariantdiff}{\differential{\nabla}}
    163 \newcommand{\cd}{\covariantdiff}

\variation Define the functional variation and derivative.
  \var
functionalderivative164 \newcommand{\variation}{\differential{\delta}}
  \fdv165 \newcommand{\var}{\variation}
  166 \newpartialderivative{\functionalderivative}{\delta}
  167 \newcommand{\fdv}{\functionalderivative}

\cancel Load the CANCEL [8] and SLASHED [9] packages which provide the \cancel and \slashed macros.
\slashed
  168 \RequirePackage{cancel}
  169 \RequirePackage{slashed}
  170 \declare{slashed}{}{/}{.14}{0}{L}
  171 \declare{slashed}{}{/}{.06}{0}{D}
  172 \declare{slashed}{}{/}{.055}{0}{pd}

A.3 Paired delimiters

\left Load the MLEFTRIGHT package [3] and adjust the spacing around \left and \right.
\right
  173 \RequirePackage{mleftright}
  174 \mleftright

\noargumentsymbol Allow for macros to have an empty argument using the ETOOLBOX package [11].
\optionalarg
  175 \RequirePackage{etoolbox}
  176 \newcommand{\noargumentsymbol}{\cdot\cdot\cdot}
  177 \newcommand{\optionalarg}[1]{\ifblank{#1}{\noargumentsymbol}{#1}{}}

\abs Absolute value and norm.
\|norm
  178 \DeclarePairedDelimiterX{\abs}[1]{\lvert}{\rvert}{\optionalarg{#1}}
  179 \DeclarePairedDelimiterX{\norm}[1]{\lVert}{\rVert}{\optionalarg{#1}}
  180 \DeclarePairedDelimiterXPP{\norm}[2]{\lVert}{\rVert}{\optionalarg{#1}}{\optionalarg{#2}}
  181 \NewDocumentCommand{\norm}{s}{%
```

### A.3.1 Set and Probability

\midbar Define a generic midbar.

```

217 \newcommand{\hep@left@delim}{\mathopen{}}
218 \providecommand{\midbar}[1][]{%
219   \nonscript\:#1\vert\allowbreak\nonscript\:\hep@left@delim%
220 }

```

Check if `nfssect-cfr` is loaded and patch the global `\set` macro into the `cfr` namespace

```

221 \RequirePackage{xpatch}
222 \@ifundefined{exfs@merge@families}{}{%
223   \xpatchcmd{\exfs@merge@families}{\set}{\cfr@set}{}{%
224   \xpatchcmd{\exfs@merge@families}{\set}{\cfr@set}{}{%
225   \xpatchcmd{\exfs@merge@families}{\set}{\cfr@set}{}{%
226 }%

```

`\suchthat` Define a `\set` macro that allows a midbar via `\suchthat`.

```

\set
227 \providecommand{\suchthat}{\midbar}
228 \DeclarePairedDelimiterX{\set}[1]{\{}{\}}
229   \renewcommand{\suchthat}{\midbar[\delimsizes]\#1}%
230 }

```

`\probabilitiesymbol` Redefine the `\Pr` macro to a macro that takes a `\given` macro and generates a midbar.

```

\given
\Pr
231 \providecommand{\probabilitiesymbol}{\operatorname{\Pr}}
232 \providecommand{\given}{\midbar}
233 \DeclarePairedDelimiterXPP{\hep@Pr}[1]{\{}{\}}
234   \probabilitiesymbol(){}{%
235   \renewcommand{\given}{\midbar[\delimsizes]\#1}%
236 }
237 \let\Pr\relax
238 \NewDocumentCommand{\Pr}{s o}{%
239   \IfValueTF{#2}{%
240     \IfBooleanTF{#1}{\hep@Pr*}{\hep@Pr}\#2}%
241   }{%
242     \probabilitiesymbol%
243   }%
244 }

```

### A.3.2 Commutators

`\newpair` Define the `\newpair` macro that generates pairs surrounded by brackets.

```

245 \NewDocumentCommand{\newpair}{m m m e{_} e{^}}{%
246   \IfNoValueTF{#4}{%
247     \IfNoValueTF{#5}{%
248       \DeclarePairedDelimiterX{\#1}[2]{\#2}{\#3}%
249     }{%
250       \DeclarePairedDelimiterXPP{\#1}[2]{\{}{\#2}{\#3}{\^{\#5}}% 
251     }%
252   }{%
253     \DeclarePairedDelimiterXPP{\#1}[2]{\{}{\#2}{\#3}{\_{\#4}}% 
254   }%

```

```

255      \optionalargument{##1},\optionalargument{##2}%
256  }%
257 }

```

\innerproduct Poissonbracket, commutator and anti-commutator.

```

\poissonbracket
  \pb 258 \newpair\innerproduct\langle\rangle
  \commutator 259 \newpair\poissonbracket\{ \brace\}
  \comm 260 \newpair\commutator\{ \brace\}
\anticommutator 261 \newcommand\pb{\poissonbracket}
  \acomm 262 \newcommand\comm{\commutator}
  \acommm 263 \newcommand\acommm{\poissonbracket}

```

### A.3.3 Bra-ket notation

\braketspace Define the space within braket notation.

```

264 % \providetoken\braketspace{\mskip1mu}
265 \providetoken\braketouterspace{\mskip1mu}
266 \providetoken\braketinnerspace{\mskip3mu}
267 \newcommand\hep@midvert{%
268   \braketinnerspace\delimsize\vert\braketinnerspace\hep@left@delim%
269 }

```

\braket Define the braket macro.

```

270 \DeclarePairedDelimiterX\braket[2]{\langle}{\rangle}{%
271   \braketouterspace#1\hep@midvert#2\braketouterspace%
272 }

```

\bra Define the bra macro.

```

273 \DeclarePairedDelimiterXPP\hep@bra[1]{%
274   }{\langle}{\rvert}{\braketinnerspace}%
275   }{\braketouterspace#1\braketinnerspace}%
276 }
277 \NewDocumentCommand{\bra}{smt\ket sgt\ketbra sgg}{%
278   \IfBooleanTF{#6}{%
279     \IfBooleanTF{#1}{\braket*{#2}{#8}}{\braket{#2}{#8}}%
280     \IfBooleanTF{#7}{\bra*{#9}}{\bra{#9}}%
281   }{%
282     \IfBooleanTF{#3}{%
283       \IfBooleanTF{#1}{\braket*}{%
284         \IfBooleanTF{#4}{\braket*{\braket}}{\braket}{#2}{#5}%
285       }%
286     }{%
287       \IfBooleanTF{#1}{\hep@bra*}{\hep@bra}{#2}%
288     }%
289   }%
290 }

```

```
\ket Define the ket macro.
```

```
291 \DeclarePairedDelimiterX\ket[1]{%
292   \braketinnerspace}{\lvert}{\rangle}{%
293 }{%
294   \braketinnerspace\hep@left@delim#1\braketouterspace%
295 }
```

```
\ketbra Define the ketbra macro.
```

```
296 \NewDocumentCommand{\ketbra}{s m m}{%
297   \IfBooleanTF{#1}{%
298     \ket*{#2}\bra*{#3}%
299   }{%
300     \ket{#2}\bra{#3}%
301   }%
302 }
```

```
\matrixelement Define the matrixelement macro.
```

```
\mel
303 \DeclarePairedDelimiterX\matrixelement[3]{%
304   \langle}{\rangle
305 }{%
306   \braketouterspace#1\hep@midvert#2\hep@midvert#3\braketouterspace%
307 }
308 \newcommand\matrixel{\matrixelement}
309 \newcommand\mel{\matrixelement}
```

```
\expectationvalue Define the expectationvalue and vev macros.
```

```
\ev
\vev
310 \DeclarePairedDelimiterX\hep@expvalue[1]{\langle}{\rangle}{%
311   \braketouterspace#1\braketouterspace%
312 }%
313 \NewDocumentCommand{\expectationvalue}{s o m}{%
314   \IfNoValueTF{#2}{%
315     \IfBooleanTF{#1}{\hep@expvalue*}{\hep@expvalue}{#3}%
316   }{%
317     \IfBooleanTF{#1}{\matrixelement*}{\matrixelement}{#2}{#3}{#2}%
318   }%
319 }
320 \newcommand\ev{\expectationvalue}
321 \newcommand\vev[1]{\expectationvalue[0]{#1}}
```

```
</package>
```

## B Test

```
<*test>
```

```
322 \documentclass{article}
323
```

```

324 \usepackage{hep-math}
325
326 \begin{document}
327
328 \begin{gather}
329   \bra{x}\ket{y}
330   \braket{x}{y} \\
331   \dv[f]{x}^3
332   \pdv[f]{x}[y]^2[z]^3
333   \fdv[f]{x}^3[y] \\
334   \set{x \suchthat x \in X}
335 \end{gather}
336
337 \end{document}
338
</test>

```

## C Readme

```

<*readme>

339 # The 'hep-math' package
340
341 Extended math macros
342
343 ## Introduction
344
345 The 'hep-math' package provides some additional features beyond the
346 'mathtools' and 'amsmath' packages.
347
348 To use the package place '\usepackage{hep-math}' in the preamble.
349
350 ## Author
351
352 Jan Hajer
353
354 ## License
355
356 This file may be distributed and/or modified under the conditions of the
357 'LaTeX' Project Public License, either version 1.3c of this license or
358 (at your option) any later version. The latest version of this license is
359 in 'http://www.latex-project.org/lppl.txt' and version 1.3c or later is
360 part of all distributions of LaTeX version 2005/12/01 or later.

```

</readme>

## References

- [1] L. Madsen, M. Høgholm, W. Robertson, and J. Wright. ‘The mathtools package: Mathematical tools to use with amsmath’ (2004). CTAN: **mathtools**.

- [2] *L<sup>A</sup>T<sub>E</sub>X Team*. ‘The `amsmath` package: AMS mathematical facilities for L<sup>A</sup>T<sub>E</sub>X’ (1994). CTAN: `amsmath`. URL: [ams.org/tex/amslatex](https://ctan.org/tex/amslatex).
- [3] H. Oberdiek. ‘The `mleftright` package: Variants of delimiters that act as maths open/close’ (2010). CTAN: `mleftright`.
- [4] H. Oberdiek. ‘The `soulutf8` package: Permit use of UTF-8 characters in `soul`’ (2007). CTAN: `soulutf8`.
- [5] A. Reichert. ‘The `units` and `nicefrac` packages: Typeset units’ (1998). CTAN: `units`.
- [6] S. C. de la Barrera. ‘The `physics` package: Macros supporting the Mathematics of Physics’ (2012). CTAN: `physics`.
- [7] E. Gregorio. ‘T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X and math’ (2020). URL: [latex-project.org/publications/2020-egreg-TUB-tb127gregorio-math.pdf](https://latex-project.org/publications/2020-egreg-TUB-tb127gregorio-math.pdf).
- [8] D. Arseneau. ‘The `cancel` package: Place lines through maths formulae’ (2013). CTAN: `cancel`.
- [9] D. Carlisle. ‘The `slashed` package: Put a slash through characters’ (1987). CTAN: `slashed`.
- [10] *L<sup>A</sup>T<sub>E</sub>X3 Project*. ‘The `xparse` package: A generic document command parser’ (1999). CTAN: `xparse`.
- [11] P. Lehman and J. Wright. ‘The `etoolbox` package: e-T<sub>E</sub>X tools for L<sup>A</sup>T<sub>E</sub>X’ (2007). CTAN: `etoolbox`.