

The `overarrows` package*

Julien Labb  

<https://github.com/julienlabbe/latex-packages>

July 11, 2024

Abstract

A L  T  X package to create custom arrows over math expressions, mainly for vectors (but arrows can as well be drawn below). Arrows stretch with content, scale with math styles, and have a correct kerning when a subscript follows.

Short example:

```
\NewOverArrowCommand{\overrightharpoon}{%
  end=\rightharpoonup
}

\begin{align*}
&\overrightharpoon{v} \& \overrightharpoon{v}_{\text{subscript}} \\
&\overrightharpoon{ABCD} \& \overrightharpoon{*v}_{\text{subscript}}
\end{align*}
```

$$\begin{array}{c} \overrightarrow{v} \\ \overrightarrow{ABCD} \end{array} \qquad \begin{array}{c} \overrightarrow{v}_{\text{subscript}} \\ \overrightarrow{v}_{\text{subscript}} \end{array}$$

Predefined commands are also provided:

- to typeset vectors:

$$\vec{v} \quad \overrightarrow{AB},$$

- to draw arrows of various shapes above math expressions:

$$\overrightarrow{AB} \quad \overleftarrow{AB} \quad \overleftrightarrow{AB} \quad \overrightarrow{AB} \quad \overleftarrow{AB} \quad \overrightarrow{AB} \quad \overleftarrow{AB} \quad \overrightarrow{AB},$$

- to draw arrows of various shapes under math expressions:

$$\overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB} \quad \overleftarrow{AB}.$$

*This document corresponds to `overarrows` v1.2, dated 2024/07/11.

Contents

1	Presentation of the package	4
2	Introduction	4
2.1	Vector arrows	4
2.2	Stack and arrow macros	5
2.3	Extensible arrows	5
3	Quick start	6
3.1	Loading the package <code>overarrows</code>	6
3.2	Commands creation	6
3.3	Start and end of the arrow	6
3.4	Size and position of the arrow	8
3.5	Symbols assemblage	9
3.6	Drawing the arrow with TikZ	11
3.7	Drawing the arrow with PSTricks	12
3.8	Drawing the arrow with L ^A T _E X picture environment	12
4	User interface	13
4.1	Package options	13
4.1.1	<code>esvect</code> configuration	13
4.1.2	Predefined commands	14
4.1.3	Other options	16
4.2	Commands	17
4.2.1	Macro for commands creation	17
4.2.2	Useful macros for symbols assemblage	19
4.2.3	Useful lengths for TikZ, PSTricks or picture environment	19
4.2.4	Vectors macros	20
4.2.5	Predefined commands	21
4.3	Keys	22
4.3.1	Arrow position and length settings	22
4.3.2	Subscripts detection setting	25
4.3.3	Symbols assemblage settings	25
4.3.4	TikZ settings	27
4.3.5	PSTricks settings	28
4.3.6	Picture environment settings	29
4.4	Advanced commands and keys	30
4.4.1	Advanced commands	30
4.4.2	Advanced keys	30
5	Complements	31
5.1	Know issues	31
5.1.1	Math font change	31
5.1.2	Detection of non standard subscripts	31
5.2	Package dependencies	32
5.3	Alternatives	32
5.4	Changelog	33
6	Implementation	33

1 Presentation of the package

The `overarrows` package allows to create commands for drawing arrows over math expressions. These arrows:

- are fully customisable, at command definition, through a key-value interface;
- stretch with the content and can cover many characters, like in \overrightarrow{AB} ;
- scale with math styles¹, like in $\overrightarrow{v}_{\overline{u}\overline{w}}$.

Commands created with the `overarrows` package are provided with a starred variant, that removes the extra end space generated by the arrow. This is particularly useful when the command is followed by a subscript. For example, the velocity of the center of mass can be written with exactly the same kerning when scalar v_{cm} or vector $\overrightarrow{v}_{\text{cm}}$ (no extra space before the subscript, unlike the output of the unstarred variant: $\overrightarrow{v}_{\text{cm}}$).

The `overarrows` package was primitively written for vectors, but in a highly customisable way. It can be used to define a large variety of arrows, using math symbols, or drawing commands from PGF/TikZ or PSTricks. It's also possible to create commands that draw the arrows under. Some predefined commands are provided, giving², for arrow over:

$$\overrightarrow{\alpha + \beta} \quad \overleftarrow{\alpha + \beta} \quad \overleftrightarrow{\alpha + \beta} \quad \overrightarrow{\alpha + \beta} \quad \overleftarrow{\alpha + \beta} \quad \overbrace{\alpha + \beta} \quad \overline{\alpha + \beta} \quad \overline{\alpha + \beta}$$

and for arrow under :

$$\overunder{\alpha + \beta} \quad \overleftunder{\alpha + \beta} \quad \overleftrightarrow{\alpha + \beta} \quad \overunder{\alpha + \beta} \quad \overleftunder{\alpha + \beta} \quad \overbrace{\alpha + \beta} \quad \overline{\alpha + \beta} \quad \overline{\alpha + \beta}$$

2 Introduction

2.1 Vector arrows

Vectors are commonly typeset in bold face, or with an arrow above³. For this second convention, `TEX/LATeX` provides the command `\vec`, which accents its content (using the `\mathaccnt` command) with the character ↗ (`\mathchar"017E` in Computer Modern font). But ↗ isn't extensible⁴, and gives: \vec{v} , \vec{AB} or $\vec{\text{grad}}$ (there's no command `\widevec` analogous to `\widehat`).

An extensible alternative is given by the command `\overrightarrow`, available in `TEx/LATeX`, and which is redefined by the commonly used `amsmath` package. But its arrow, built with the `\rightarrow` symbol →, is too large, using the default *Computer Modern* font: \overrightarrow{AB} . Another alternative is the `esvect` package, which provides the `\vv` command and a set of custom arrows: \overrightarrow{AB} , \overleftarrow{AB} , \overleftrightarrow{AB} , \overleftarrow{AB} , \overrightarrow{AB} , \overleftarrow{AB} , \overrightarrow{AB} .

¹ `\displaystyle`, `\textstyle`, `\scriptstyle` and `\scriptscriptstyle`.

² Displayed here with the `old-arrows`[→]P.¹⁶ option.

³ See, for example: International Organization for Standardization. (2019). *Quantities and units – Part 2: Mathematics* (ISO Standard No. 80000-2:2019). <https://www.iso.org/standard/64973.html>.

⁴ In fact, with the unicode engines `LuaTeX` and `XeTeX`, the command `\mathaccnt` can now define extensible accents. This is used by the `unicode-math` package, which also set the arrows displayed by `\vec` and `\overrightarrow` in a coherent manner.

2.2 Stack and arrow macros

It's worth looking at the definition of `amsmath \overrightarrow` command:

```
\long macro:->\mathpalette {\overarrow@ \rightarrowfill@ }
```

Three macros are used here:

`\mathpalette` adapts the output to the current math style;

`\overarrow@` is the *stack macro*, that puts the arrow above the content;

`\rightarrowfill@` is the *arrow macro*, that holds the content of the arrow.

The command `\vv` from `esvect` is defined with a very similar way, using its own stack macro (`\overvect@`) and arrow macro (`\vectfill@`).

The `overarrows` package uses the same mechanism. Arrow and stack macros are set, at command creation, through a key-value interface provided by the `pgfkeys` package (after creation, however, the command definition is static and the key-value interface is not used).

2.3 Extensible arrows

Arrows drawn by the commands `\overrightarrow` or `\vv` are built by joining math symbols, and made extensible by repetition of the central symbol⁵. Thus, the line of the macro `\overrightarrow` is made by repetition of command `\relbar` — (which simply corresponds to the minus sign), while `\vv` use its own command `\relbareda` -.

This method may generate some undesirable spacing issues, when symbols badly overlap. See, for example, the output of `amsmath \overrightarrow` (left) and `esvect \vv` (right) in `\scriptscriptstyle` math style (scaled by a factor 4):

$$\overrightarrow{\text{long vector}} \quad \overrightarrow{\text{long vector}}$$

While the arrow on the left lets guess where the symbols — overlap, the arrow on the right present unwanted spaces and show clearly its composition as association of the symbols -, - and →.

By default, the `overarrows` package uses the same mechanism to extend arrows according to their contents. Settings and tools are provided to perform fine tuning and avoid spacing issues. As example, see below the `\overrightarrow` and `\vv` commands, as redefined by `overarrows` (in `\scriptscriptstyle` and scaled by a factor 4):

$$\overrightarrow{\text{long vector}} \quad \overrightarrow{\text{long vector}}$$

The `overarrows` package also provides an alternative mechanism. When used, the length `\overarrowlength` is set, according to the arrow command content, and can be employed, for example, to draw arrows using PGF/TikZ, PSTricks or the L^AT_EX picture environment.

⁵Using the T_EX `\cleaders` command.

3 Quick start

3.1 Loading the package `overarrows`

To load the `overarrows`, simply add in preamble, before the “`\begin{document}`”:

```
\usepackage{overarrows}
```

Options can be given, in a comma-separated list. For example, to use the predefined commands shown in the section 1, page 4, write:

```
\usepackage[allcommands, old-arrows]{overarrows}
```

This define the commands (described in section 4.2.5, page 21):

- `\overrightarrow`^{P. 21}
- `\overleftarrow`^{P. 21}
- `\overleftrightarrow`^{P. 21}
- `\overrightharpoonup`^{P. 21}
- `\overrightharpoondown`^{P. 21}
- `\overleftharpoonup`^{P. 21}
- `\overleftharpoondown`^{P. 21}
- `\overbar`^{P. 21}
- `\underrightarrow`^{P. 22}
- `\underleftarrow`^{P. 22}
- `\underleftrightarrow`^{P. 22}
- `\underrightharpoonup`^{P. 22}
- `\underrightharpoondown`^{P. 22}
- `\underleftharpoonup`^{P. 22}
- `\underleftharpoondown`^{P. 22}
- `\underbar`^{P. 22}

Note that the `old-arrows`^{P. 16} option may give bad results, if math fonts have been changed. Simply remove the option in this case.

Many other options are available. See the complete list, page 13.

3.2 Commands creation

Commands are created with `\NewOverArrowCommand`^{P. 17}. This macro take two mandatory arguments : the name of the command and the arrow configuration as comma-separated list of key-values. By default, a right arrow is set:

```
\NewOverArrowCommand{\myovercmd}{}
$ \myovercmd{test}$
```

\overrightarrow{test}

Commands are defined with a starred variant, designed to handle subscripts:

```
$ v_{\sub} \qqquad \myovercmd{v}_{\sub} \qqquad \myovercmd*{v}_{\sub} $
```

v_{\sub} $\overrightarrow{v}_{\sub}$ \overleftarrow{v}_{\sub}

3.3 Start and end of the arrow

Extremities of the arrow are set by the keys `start`^{P. 25} and `end`^{P. 25}. For example, an arrow starting with a hook (symbol `\lhook`) and ending with two heads (symbol `\twoheadrightarrow`) is defined by:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow,
}
```

Note that `\twoheadrightarrow` must be defined, as it is not in L^AT_EX. This can be done with the package `amssymb`, by adding in preamble:

```
\usepackage{amssymb}
```

But with the previous definition, the result of the command `\overhooktwoheadrightarrow` is faulty:

```
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```



The problem comes from symbols junction and the trimming used to obtain their overlap. It can be solved with the keys `trim start`^{P. 25} and `trim end`^{P. 26}, which are numbers and set the corresponding trimming in math units (typically $1/18 \text{ em}$). Appropriate values gives better results:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow,
  trim start=1.5, trim end=2,
}
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```



If the math font differs from the default *Computer Modern*, the central part of the arrow may have inappropriate position or line width. This is because the default symbol used for the arrow line is `\relbar` [from the `esvect` package⁶. If needed, try to set the `middle`^{P. 25} key with the symbol `\relbar` [. The trimming should also be adapted:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow, middle=\relbar,
  trim start=0, trim end=3, trim middle=5,
}
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```



Finding the correct values for `trim start`^{P. 25}, `trim end`^{P. 26} and `trim middle`^{P. 25} may need many trials. For this purpose, the macro `\TestOverArrow`^{P. 18} displays the result of a command for different lengths and math styles:

⁶Except if the `unicode-math` package is used with a math font that provides the `\harpoonright` symbol (see the `middle config=auto` key).

```
\TestOverArrow{\overhooktwoheadrightarrow}
```

$\displaystyle \overhooktwoheadrightarrow$	$\textstyle \overhooktwoheadrightarrow$	$\scriptstyle \overhooktwoheadrightarrow$	$\scriptscriptstyle \overhooktwoheadrightarrow$
$\overhooktwoheadrightarrow v$	$\overhooktwoheadrightarrow v$	$\overhooktwoheadrightarrow v$	$\overhooktwoheadrightarrow v$
$\overhooktwoheadrightarrow AB$	$\overhooktwoheadrightarrow AB$	$\overhooktwoheadrightarrow AB$	$\overhooktwoheadrightarrow AB$
$\overhooktwoheadrightarrow \text{grad}$	$\overhooktwoheadrightarrow \text{grad}$	$\overhooktwoheadrightarrow \text{grad}$	$\overhooktwoheadrightarrow \text{grad}$
$\overhooktwoheadrightarrow \text{my long vector}$			

3.4 Size and position of the arrow

A command \OverRightarrow , built with the symbols \Relbar and \Rightarrow , gives:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start=\Relbar,
  middle=\Relbar,
  end=\Rightarrow,
  trim=4,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$$\overrightarrow{v} \quad \overrightarrow{AB}$$

The key $\text{trim} \rightarrow P.26$ sets $\text{trim start} \rightarrow P.25$, $\text{trim middle} \rightarrow P.25$ and $\text{trim end} \rightarrow P.26$ with the same value.

The previous arrow is visually too big. The macro $\smallermathstyle \rightarrow P.19$ allows to obtain a better result:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start={\smallermathstyle\Relbar},
  middle={\smallermathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$$\overrightarrow{v} \quad \overrightarrow{AB}$$

Note that $\smallermathstyle \rightarrow P.19$ should not be used for $\text{end} \rightarrow P.25$, because this last is formatted with the same math style as $\text{start} \rightarrow P.25$.

It would be better to add an extra space between the arrow and the content of the command. This can be done with the key $\text{space after arrow} \rightarrow P.24$:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start={\smallermathstyle\Relbar},
  middle={\smallermathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
  space after arrow=0.25ex,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$$\overrightarrow{v} \quad \overrightarrow{AB}$$

Default arrows are slightly shifted to the right. For a left arrow, this should be reversed, using the keys `shift left`^{P.23} and `shift right`^{P.23}. These keys set the corresponding shifts, in math units. Example:

```
\NewOverArrowCommand{\OverLeftarrow}{%
  start={\smaller\mathstyle\Leftarrow},
  middle={\smaller\mathstyle\Relbar},
  end=\Relbar,
  trim=4,
  space after arrow=0.25ex,
  shift left=0, shift right=2,
}
$ \OverLeftarrow{v} \qquad \OverLeftarrow{AB} $
```

$$\overleftarrow{v} \qquad \overleftarrow{AB}$$

Finally, the key `arrow under`^{P.23} places the arrow below the content, instead of above (and `space before arrow`^{P.24} sets the space upon it):

```
\NewOverArrowCommand{\UnderLeftRightarrow}{%
  start={\smaller\mathstyle\Leftarrow},
  middle={\smaller\mathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
  arrow under,
  space before arrow=0.5ex,
  shift left=0, shift right=0,
}
$ \UnderLeftRightarrow{v} \qquad \UnderLeftRightarrow{AB} $
```

$$v \qquad \overleftarrow{AB}$$

3.5 Symbols assemblage

Many L^AT_EX math symbols are built by assemblage, using the macro `\joinrel`⁷ which remove 3 math units of horizontal space. The `overarrows` package provides a flexible version of `\joinrel`, called `\xjoinrel`^{P.19}, which remove an arbitrary number of math units, given as optional argument.

Symbols association is then simple. As example, one can define a triple tail macro `\tttail` from the symbol `\succ` :

```
\newcommand*{\tttail}{\succ\xjoinrel[10]\succ\xjoinrel[10]\succ}
$ \tttail $
```



Thus defined, the macro `\tttail` can be used in arrow definition:

⁷For example, the symbol `\models` is defined as `\mathrel{|}\joinrel\Relbar` and corresponds to the assemblage of a vertical line `|` and the symbol `\Relbar`. The command `\mathrel` modifies the spacing according to the math relation class ; `\Relbar` corresponds to the equal sign (it's definition is `\mathrel{=}`).

```
\NewOverArrowCommand{\overrightarrowtail}{%
  start={\tttail},
  end={\rightarrow},
  trim start=12,
  shift left=0, shift right=0,
  space after arrow=.2ex,
  min length=24,
}
$ \overrightarrowtail{v} \qquad \overrightarrowtail{AB} $
```



Here the `min length`^{P.23} key was added to ensure a minimum length (in math units) when the content of the command is small (as for a single character).

The previous arrow would be better with a smaller tail, and this can be done with the macro `\smallermathstyle`^{P.19}. But a small tail and a normal sized head are not aligned; as `{\smallermathstyle\ttail}\xjoinrel[8]\rightarrow` gives:



The solution comes from the command `\vcenter` which centers materials on math axis. The tail must then be wrapped in a `\hbox`:

```
\NewOverArrowCommand{\overrightarrowtail}{%
  start={\vcenter{\hbox{$\smallermathstyle\ttail$}}},
  end={\rightarrow},
  trim start=12,
  shift left=0, shift right=0,
  space after arrow=.2ex,
  min length=24,
}
$ \overrightarrowtail{v} \qquad \overrightarrowtail{AB} $
```



Text symbols, namely symbols that are not defined in math mode, can also be used. They should yet be enclosed in the `\text` macro, from the `amsmath` package, to be correctly displayed and correctly scaled according to math style. With, for example, the arrow heads given by the symbols 40 and 41 of the *lasy* font:

```
\newcommand*{\leftarrowhead}{\usefont{U}{lasy}{m}{n}\symbol{40}}
\newcommand*{\rightarrowhead}{\usefont{U}{lasy}{m}{n}\symbol{41}}
\NewOverArrowCommand{\overrightarrowtail}{%
  start=\text{\rightarrowhead},
  end=\text{\leftarrowhead},
  trim start=0.7, trim end=0.7,
  min length=20,
  shift leftright=-2,
}
$ \overrightarrowtail{AB} \qquad \overrightarrowtail{AB} $
```



3.6 Drawing the arrow with TikZ

In addition to the default method presented previously (assemblage of symbols, as described in section 2.3, page 5), the `overarrows` package has an alternative method to draw the arrow. This one allows the use of graphic languages such as PGF/TikZ.

Drawing arrows with TikZ requires to load the `tikz` package and its library `arrows.meta`. This can be simply done by passing the `tikzP.16` option to the `overarrows` package⁸:

```
\usepackage[tikz]{overarrows}
```

To use PGF/TikZ language, the optional argument `tikz` must be passed to `\NewOverArrowCommandP.17`. TikZ pictures are not extensible. That's why the `overarrows` package provides three lengths that can be used in TikZ commands:

- `\overarrowlengthP.20` for the arrow length,
- `\overarrowthicknessP.20` and `\overarrowssmallerthicknessP.20` for the arrow thickness.

These lengths are computed at each utilisation of a command created with the `tikz` optional argument.

Without any other configuration, a right arrow is drawn:

```
\NewOverArrowCommand[tikz]{\overrightarrow}{}
$ \overrightarrow{v} \qquad \overrightarrow{AB} $
```



Keys to use Tikz are described in section 4.3.4, page 27. Main keys are: `tikz optionsP.27`, `path optionsP.27` and `pathP.27`. It's also possible to append settings with `add tikz optionsP.27` and `add path optionsP.27`. The full TikZ command used to draw the arrow can as well be entirely redefined with the key `tikz commandP.28`.

Here is an example of an arrow drawn with TikZ⁹:

```
\NewOverArrowCommand[tikz]{\overarchedleftrightarrow}{%
  add tikz options={y=\overarrowlength},
  add tikz options={line width=\overarrowssmallerthickness},
  path options={arrows={<[scale=0.5]->[scale=0.5]}},
  path={(0,0) arc (-250:70:0.5 and 0.1)},
  center arrow,
  min length=25,
  space after arrow=0.4ex,
}
$ \overarchedleftrightarrow{v} \qquad \overarchedleftrightarrow{ABCD} $
```



⁸Note that the `tikzP.16` option isn't mandatory to use TikZ commands in `overarrows`. The `tikz` package and its library `arrows.meta` can be loaded independently.

⁹TikZ arrows are very powerful, but much slower to draw than the default method using assemblage of math symbols.

3.7 Drawing the arrow with PSTRicks

In addition to PGF/TikZ, the arrow can be drawn with PSTRicks macros. For this, the optional argument `pstricks` must be passed to `\NewOverArrowCommand`^{P. 17}. Like with `tikz`, the three lengths `\overarrowlength`^{P. 20}, `\overarrowthickness`^{P. 20} and `\overarrowsmallerthickness`^{P. 20} can be used in PSTRicks commands. By default, a right arrow is drawn:

```
\NewOverArrowCommand[pstricks]{\overpstarrow}{}
$ \overpstarrow{v} \qquad \overpstarrow{AB} $
```



The `pstricks` package has to be loaded (for example, using the `pstricks`^{P. 16} option of the `overarrows` package)

Keys to use PSTRicks commands are described in section 4.3.5, page 28. The main keys are `pstricks command`^{P. 28}, `psset`^{P. 28}, `arrow`^{P. 28}, `geometry`^{P. 28} and `line thickness`^{P. 29}. Examples:

```
\NewOverArrowCommand[pstricks]{\overreddisks}{%
  psset={linecolor=red}, arrow=*>, center arrow,
}
$ \overreddisks{v} \qquad \overreddisks{AB} $
```



```
\NewOverArrowCommand[pstricks]{\ellipticarrow}{%
  pstricks command=%
  \psellipticarcn{->}%~^A avoid space before coordinates
  (0.5\overarrowlength,0.2\overarrowlength)%~^A avoid space before coordinates
  (0.5\overarrowlength,0.2\overarrowlength)
  {170}{10}
},
geometry={(0,0.2\overarrowlength)(\overarrowlength,0.4\overarrowlength)},
line thickness={\overarrowsmallerthickness},
center arrow,
}
$ \ellipticarrow{v} \qquad \ellipticarrow{AB} $
```



3.8 Drawing the arrow with L^AT_EX picture environment

Without any other package, arrows can also be drawn with the L^AT_EX `picture` environment. In this case, the optional argument `picture` must be passed to `\NewOverArrowCommand`^{P. 17}. As with `tikz` or `pstricks`, the three lengths `\overarrowlength`^{P. 20}, `\overarrowthickness`^{P. 20} and `\overarrowsmallerthickness`^{P. 20} are available and can be used in `picture` drawing commands. By default, a right vector is drawn:

```
\NewOverArrowCommand[picture]{\overpictarrow}{}
$ \overpictarrow{v} \qquad \overpictarrow{AB} $
```



If `overarrows` is loaded with the option `pstarprows`^{P. 17}, the package `pict2e` is used and a PSTRicks style vector arrows is set. This gives:

```
\NewOverArrowCommand[picture]{\overpictarrow}{}
$ \overpictarrow{v} \qquad \overpictarrow{AB} $
```



Keys to use L^AT_EX picture environment are described in section 4.3.6, page 29. The main keys are `picture command`^{P. 29}, `geometry`^{P. 29} an `line thickness`^{P. 29}. Here is an example:

```
\NewOverArrowCommand[picture]{\overbandedarrow}{%
  picture command={%
    \qbezier
    (0.0\overarrowlength,0)
    (0.5\overarrowlength,0)
    (0.9\overarrowlength,0.2\overarrowlength)
    \put(0.9\overarrowlength,0.2\overarrowlength)
    {\vector(2,1){0.2\overarrowlength}}
  },
  geometry={(0.0\overarrowlength,0.4\overarrowlength)(0,0)},
  line thickness={\overarrowsmalldothickness},
  center arrow,
  space after arrow=0.4ex,
}
$ \overbandedarrow{v} \qquad \overbandedarrow{AB} $
```



4 User interface

4.1 Package options

The `overarrows` package accepts many options, given as a comma-separated list `<options>` at package loading: `\usepackage[<options>]{overarrows}`.

The option `esvect` is set by default. This can be overridden with `noesvect`.

4.1.1 esvect configuration

esvect

Loads the `esvect` package and redefines its vector commands `\vv`^{P. 20} through the `overarrows` mechanism. Original `esvect` `\vv` macro is still available with `\esvectvv`^{P. 20}. The `esvect` font description is fixed to allow any font sizes.

The `esvect` package provides the symbol `\relbareda`

which is smaller and often more flexible than the classic one `\relbar`

`\relbareda` fits with the standard *Computer Modern* math font, but can be unsuitable with other fonts.

The `esvect` package also provides the right arrow command `\fldr`. The shape of the arrow depends on the option passed to the `esvect` package:

(option a),

(option b),

(option c),

(option d),

(option e),

(option f),

(option g) or

(option h). Note that by default `overarrows` loads the `esvect` package with the option f (while `esvect` default is d). This can be changed with one of the eight options described below: `esvecta`, `esvectb`, `esvectc`, `esvectd`, `esvecte`, `esvectf`, `esvectg` and `esvecth`.

This option is set by default and can be unset with `noesvect`.

noesvect

Prevents the loading of the `esvect` package and the definition of the command \vv^{\rightarrow} .^{P.20.}

esvecta

Loads the `esvect` package with the `a` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvectb

Loads the `esvect` package with the `b` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvectc

Loads the `esvect` package with the `c` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvectd

Loads the `esvect` package with the `d` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvecte

Loads the `esvect` package with the `e` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvectf

Loads the `esvect` package with the `f` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvectg

Loads the `esvect` package with the `g` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

esvecth

Loads the `esvect` package with the `h` option.

`\fldr` corresponds to the symbol \rightarrow . `\vv` command gives : \vec{v} \overrightarrow{AB} $\overrightarrow{\text{grad}}$.

4.1.2 Predefined commands

The `overarrows` package provides sixteen predefined commands, eight with the arrow over, and eight with the arrow under. By default, these commands are not defined, and must be activated by the corresponding option. Beware that commands are created without checking if already defined by another package (`\overleftarrow`, `\overrightarrow`, `\overleftrightarrow`, `\underleftarrow`, `\underrightarrow` and `\underleftrightarrow` are, for example, part of the `ams-math` package).

Three options are also available to define set of commands.

Set of commands

allcommands

Defines all sixteen predefined commands.

overcommands

Defines all eight predefined commands with arrow over.

undercommands

Defines all eight predefined commands with arrow under.

Over arrows

overrightarrow

Defines the \overrightarrow{v} command: \vec{v} , \vec{AB} , $\vec{\text{grad}}$.

overleftarrow

Defines the \overleftarrow{v} command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

overleftrightarrow

Defines the \overleftrightarrow{v} command: \overleftrightarrow{v} , \overleftrightarrow{AB} , $\overleftrightarrow{\text{grad}}$.

overrightharpoonup

Defines the \overrightharpoonup{v} command: \overrightarrow{v} , \overrightarrow{AB} , $\overrightarrow{\text{grad}}$.

overrightharpoondown

Defines the \overrightharpoondown{v} command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

overleftharpoonup

Defines the \overleftharpoonup{v} command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

overleftharpoondown

Defines the \overleftharpoondown{v} command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

overbar

Defines the \overbar{v} command: \overline{v} , \overline{AB} , $\overline{\text{grad}}$.

Under arrows

underrightarrow

Defines the \underrightarrow{v} command: \underline{v} , \underline{AB} , $\underline{\text{grad}}$.

underleftarrow

Defines the \underleftarrow{v} command: \underline{v} , \underline{AB} , $\underline{\text{grad}}$.

underleftrightarrow

Defines the $\backslash\text{underleftrightarrow}^{\rightarrow P.22}$ command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

underrightharpoonup

Defines the $\backslash\text{underrightharpoonup}^{\rightarrow P.22}$ command: \underline{v} , \underline{AB} , $\underline{\text{grad}}$.

underrightharpoondown

Defines the $\backslash\text{underrightharpoondown}^{\rightarrow P.22}$ command: \overline{v} , \overline{AB} , $\overline{\text{grad}}$.

underleftharpoonup

Defines the $\backslash\text{underleftharpoonup}^{\rightarrow P.22}$ command: \underline{v} , \underline{AB} , $\underline{\text{grad}}$.

underleftharpoondown

Defines the $\backslash\text{underleftharpoondown}^{\rightarrow P.22}$ command: \overleftarrow{v} , \overleftarrow{AB} , $\overleftarrow{\text{grad}}$.

underbar

Defines the $\backslash\text{underbar}^{\rightarrow P.22}$ command: \underline{v} , \underline{AB} , $\underline{\text{grad}}$.

4.1.3 Other options

old-arrows

Loads the `old-arrows` package with its option `old`. This provides the symbols $\backslash\text{varleftarrow}$ \leftarrow and $\backslash\text{varrightarrow}$ \rightarrow , used then by default for predefined command.

When the `old-arrows` option is set, the commands $\backslash\text{overrightarrow}^{\rightarrow P.21}$, $\backslash\text{overleftarrow}^{\rightarrow P.21}$, $\backslash\text{overleftrightarrow}^{\rightarrow P.21}$, $\backslash\text{underrightarrow}^{\rightarrow P.22}$, $\backslash\text{underleftarrow}^{\rightarrow P.22}$ and $\backslash\text{underleftrightarrow}^{\rightarrow P.22}$ give respectively :
 \overrightarrow{AB} , \overleftarrow{AB} , \overleftrightarrow{AB} , \overline{AB} , \underline{AB} and $\overleftarrow{\underline{AB}}$

tikz

Loads the package `tikz` with its library `arrows.meta`.

Note that TikZ arrows, drawn with the `tikz` method, are always available, even if this option is not set, provided the `tikz` package and its library are loaded independently.

pstricks

Loads the package `pstricks-add`.

Note that, as it, this will compile with `LATeX`, `LuLaTEx` and `XeLATeX`, but not with `pdfLATEX` (see the PSTricks documentation). PSTricks arrows, drawn with the `pstricks` method, are always available, even if this option is not set, provided the `pstricks` package is loaded independently.

pstarrows

Loads the `pict2e` package, with its option `pstarrows`. Vectors using `LATEX picture` environment gives then \overrightarrow{AB} instead of \vec{AB} .

Note that this affect all vectors drawn in `LATEX picture` environments, and that this setting can be changed on the fly with the commands `\pstarrows` and `\ltxarrows` from the `pict2e` package.

subscripts

Sets the default value of the key `detect subscripts`^{P.25} to `true`.

This option also impacts the command `\vv`^{P.20} and all predefined commands, so that they automatically use their starred variant when a subscript follows.

subother

New: v1.1 2023/02/15

Sets to 12 (*other* catcode category) the catcode of the “`_`” symbol used for subscript detection, when this is enabled by the key `detect subscripts`^{P.25} (see the section 5.1.2, page 31).

subactive

New: v1.1 2023/02/15

Sets to 13 (*active* catcode category) the catcode of the “`_`” symbol used for subscript detection, when this is enabled by the key `detect subscripts`^{P.25} (see the section 5.1.2, page 31).

debug

Writes the meaning of defined commands in `LATEX` log.

4.2 Commands

4.2.1 Macro for commands creation

```
\NewOverArrowCommand[⟨method⟩]{⟨command⟩}{⟨keys⟩}
\RenewOverArrowCommand[⟨method⟩]{⟨command⟩}{⟨keys⟩}
\ProvideOverArrowCommand[⟨method⟩]{⟨command⟩}{⟨keys⟩}
\DeclareOverArrowCommand[⟨method⟩]{⟨command⟩}{⟨keys⟩}
```

Creates the command `⟨command⟩` and its starred variant `⟨command⟩*`. The starred variant `⟨command⟩*` removes the extra end space generated by the arrow, which is suitable, as example, when a subscript follows.

`⟨command⟩` can be given with or without backslash (prior to the version 1.2, only the name, without backslash, was accepted).

`\NewOverArrowCommand` raises an error if `⟨command⟩` is already defined.

`\RenewOverArrowCommand` raises an error if `⟨command⟩` is undefined.

`\ProvideOverArrowCommand` sets `⟨command⟩` if the command is undefined and does nothing if it is already defined, without raising any error.

`\DeclareOverArrowCommand` sets `⟨command⟩`, whether the command is already defined or not, without raising any error.

Updated: v1.2 2024/07/11

The $\langle method \rangle$ used to draw the arrow must be:

- `symb` to draw the arrow by symbols assemblage (default);
- `tikz` to draw the arrow with PGF/TikZ;
- `pstricks` to draw the arrow with PSTricks;
- `picture` to draw the arrow with the L^AT_EX `picture` environment.

With no $\langle method \rangle$ argument, the `symb` method is chosen.

$\langle keys \rangle$ is a comma-separated list of keys-values. Available keys depends of the $\langle method \rangle$ chosen and are described in section 4.3, page 22.

```
\NewOverArrowCommand[tikz]{\myoverarrow}{arrows={Bar-Bar}, center arrow}
$ \myoverarrow{v} \qquad \myoverarrow{ABCD}
```

```
\TestOverArrow[<pattern>]{<command>}
\TestOverArrow*[<pattern>]{<command>}
```

Displays the result of the command $\langle command \rangle$ for patterns of various lengths and for the four math styles. A custom $\langle pattern \rangle$ can be added to the predefined ones.

The starred variant `\TestOverArrow*` displays a full report, including kerning tests of the commands $\langle command \rangle$ and $\langle command \rangle^*$.

$\langle command \rangle$ can be given with or without backslash (prior to the version 1.2, only the name, without backslash, was accepted).

```
\TestOverArrow*[my~pattern]{vv}
```

Test of `\vv` and `\vv*` macros

`\vv` for different math styles

<code>\displaystyle</code>	<code>\textstyle</code>	<code>\scriptstyle</code>	<code>\scriptscriptstyle</code>
\vec{v}	\vec{v}	\vec{v}	\vec{v}
\overrightarrow{AB}	\overrightarrow{AB}	\overrightarrow{AB}	\overrightarrow{AB}
$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$
$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$
$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$

`\vv` kerning

$$\vec{t}_{\vec{u}_{\vec{v}}} \quad \vec{i}_0 \quad \vec{v} = \vec{v}_x + \vec{v}_y + \vec{v}_z = v_x \vec{i} + v_y \vec{j} + v_z \vec{k}$$

`\vv*` kerning

$$\vec{t}_{\vec{u}_{\vec{v}}} \quad \vec{i}_0 \quad \vec{v} = \vec{v}_x + \vec{v}_y + \vec{v}_z = v_x \vec{i} + v_y \vec{j} + v_z \vec{k}$$

4.2.2 Useful macros for symbols assemblage

Math symbols assemblage is the default method used to draw arrows. The macros `\xjoinrel` and `\smallermathstyle` are designed to help combine and format math symbols.

`\xjoinrel[<number>]`

Removes an horizontal space of $\langle number \rangle$ math units (3.5 mu by default). Must be used in math mode. Useful to assemble math symbols and create new ones.

```
\newcommand*{\triplebar}{\Relbar\xjoinrel[14]\relbar}
\newcommand*{\triplebararrow}{\Relbar\xjoinrel[15]\rightarrow}
\scalebox{2}{\$ \triplebar \quad \triplebararrow \$} \par
\scalebox{2}{\$ \triplebar\xjoinrel\triplebararrow \$}
```



`\smallermathstyle`

Applies the next math style, smaller than the current. That is:

- uses `\scriptstyle` if the current math style is `\displaystyle` or `\textstyle`;
- uses `\scriptscriptstyle` if the current math style is `\scriptstyle`;
- does nothing if the current math style is `\scriptscriptstyle`.

```
\$ \displaystyle AB \quad \textstyle AB
\quad \scriptstyle AB \quad \scriptscriptstyle AB \$\par
\$ \displaystyle AB \quad \smallermathstyle AB
\quad \smallermathstyle AB \quad \smallermathstyle AB \$
```

$$\begin{array}{cccc} AB & AB & AB & AB \\ AB & AB & AB & AB \end{array}$$

4.2.3 Useful lengths for TikZ, PStricks or picture environment

Arrows drawn with graphic languages, like PGF/TikZ, PStricks or the L^AT_EX `picture` environment, are not extensible. The three lengths `\overarrowlength`, `\overarrowthickness` and `\overarrowsmallerthickness` are computed at each utilisation of a command set with the `tikz`, `pstricks` or `picture` method, so they can be used in drawing commands.

```
\NewOverArrowCommand[tikz]{\overparabola}{%
  path options={x=\overarrowlength, line width=\overarrowsmallerthickness},
  path={(0,0) parabola [parabola height=0.2\overarrowlength] (1,0)},
  arrows={-}, center arrow, min length=30,
}
\$ \displaystyle \overparabola{v} \quad \overparabola{ABCD} \$\par
\$ \scriptstyle \overparabola{v} \quad \overparabola{ABCD} \$\par
```



\overarrowlength

Is set to the width of the arrow command content, or, if larger, to the minimal arrow length set through the key `min length`^{P.23}.

\overarrowthickness

Is set to the default rule thickness of the current math style. That is:

- `\fontdimen 8 \textfont 3` in `\displaystyle` or `\textstyle`;
- `\fontdimen 8 \scriptfont 3` in `\scriptstyle`;
- `\fontdimen 8 \scriptscriptfont 3` in `\scriptscriptstyle`.

Updated: v1.2 2024/07/11

These settings are adapted when the package `unicode-math` is loaded (using `\Umathoverbarrule` with `LuaLaTeX` or `\fontdimen 54, family 2` with `XeLaTeX` — see the manual of `unicode-math`).

\overarrowsmallerthickness

Is set to the default rule thickness of the next smaller math style. That is:

- `\fontdimen 8 \scriptfont 3` in `\displaystyle` or `\textstyle`;
- `\fontdimen 8 \scriptscriptfont 3` in `\scriptstyle` or `\scriptscriptstyle`.

Updated: v1.2 2024/07/11

These settings are adapted when the package `unicode-math` is loaded (using `\Umathoverbarrule` with `LuaLaTeX` or `\fontdimen 54, family 2` with `XeLaTeX` — see the manual of `unicode-math`).

4.2.4 Vectors macros

The macro `\vv`, dedicated to vectors, is automatically defined when the option `esvect`^{P.13} is set (which is the default). It is a clone of the `\vv` command provided by the `esvect` package, but its starred variant has a correct kerning when followed by a subscript.

`\vv{<content>}`
`\vv*{<content>}`

Draws a vector arrow upon math `<content>`. The shape of the arrow depends on the corresponding options described in section 4.1.1, page 13 : `esvecta`^{P.14}, `esvectb`^{P.14}, `esvectc`^{P.14}, `esvectd`^{P.14}, `esvecte`^{P.14}, `esvectf`^{P.14}, `esvectg`^{P.14}, `esvecth`^{P.14}.

The starred variant `\vv*` suppresses the end space created by the arrow.

```
$ \vv{\imath_0} \quad \vv{e}_r \quad \vv{L}_{\Delta} $  
$ \vv*{\imath_0} \quad \vv*{e}_r \quad \vv*{L}_{\Delta} $
```

$$\begin{array}{ccc} \vec{\imath}_0 & \vec{e}_r & \vec{L}_{\Delta} \\ \vec{\imath}_0 & \vec{e}_r & \vec{L}_{\Delta} \end{array}$$

\esvectvv

Is simply the backup of the original `esvect` `\vv` command.

```
$ \esvectvv{\imath}{0} \quad \esvectvv{e}{r} \quad \esvectvv{L}{\Delta} $\\
$ \esvectvv*{\imath}{0} \quad \esvectvv*{e}{r} \quad \esvectvv*{L}{\Delta} $
```

$$\begin{array}{ccc} \vec{\imath}_0 & \vec{e}_r & \vec{L}_\Delta \\ \overrightarrow{\imath}_0 & \overrightarrow{e}_r & \overrightarrow{L}_\Delta \end{array}$$

4.2.5 Predefined commands

Predefined commands are defined if the corresponding option is set (see section 4.1.2, page 14). The commands `\overrightarrow`, `\overleftarrow`, `\overleftrightarrow`, `\underrightarrow`, `\underleftarrow` and `\underleftrightarrow` are affected by the option `old-arrows`^{P.16}.

Over arrows

`\overrightarrow`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrows`^{P.16} is set.

`\overleftarrow`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrows`^{P.16} is set.

`\overleftrightarrow`

$$\overleftrightarrow{v} \quad \overleftrightarrow{AB} \quad \overleftrightarrow{\text{grad}}$$

The shape of the arrows is smaller if the option `old-arrows`^{P.16} is set.

`\overrightharpoonup`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

`\overrightharpoondown`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

`\overleftharpoonup`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

`\overleftharpoondown`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

`\overbar`

$$\overline{v} \quad \overline{AB} \quad \overline{\text{grad}}$$

Under arrows

`\underrightarrow`

\underline{v} \underline{AB} $\underline{\text{grad}}$

The shape of the arrow is smaller if the option `old-arrows`^{P. 16} is set.

`\underleftarrow`

\overleftarrow{v} \overleftarrow{AB} $\overleftarrow{\text{grad}}$

The shape of the arrow is smaller if the option `old-arrows`^{P. 16} is set.

`\underleftrightarrow`

\overleftrightarrow{v} \overleftrightarrow{AB} $\overleftrightarrow{\text{grad}}$

The shape of the arrows is smaller if the option `old-arrows`^{P. 16} is set.

`\underrightharpoonup`

\underline{v} \underline{AB} $\underline{\text{grad}}$

`\underrightharpoondown`

\overline{v} \overline{AB} $\overline{\text{grad}}$

`\underleftharpoonup`

\underline{v} \underline{AB} $\underline{\text{grad}}$

`\underleftharpoondown`

\overleftarrow{v} \overleftarrow{AB} $\overleftarrow{\text{grad}}$

`\underbar`

\underline{v} \underline{AB} $\underline{\text{grad}}$

4.3 Keys

The customisation of arrows is done at command creation through a key-value interface provided by the `pgfkeys` package (with `/overarrows/` as key path).

4.3.1 Arrow position and length settings

These keys are available whatever the method chosen at command creation (see section 4.2.1, page 17 for the documentation of commands creation).

Length

```
min length={⟨number⟩}                                (no default, see below for the initial value)
```

Sets the minimal arrow length to $\langle number \rangle$ math units. The arrow length is set from content width, or, if larger, to this value.

The initial value of `min length` depends on the $\langle method \rangle$ chosen at command creation (see section 4.2.1, page 17 for the documentation of commands creation):

- $\langle number \rangle = 0$ for the `symb` method (method by default);
- $\langle number \rangle = 12$ for the `tikz` method;
- $\langle number \rangle = 12$ for the `pstricks` method;
- $\langle number \rangle = 18$ for the `picture` method.

```
\NewOverArrowCommand{\overlongarrow}{\min length=50}
$ \overlongarrow{v} \qquad \overlongarrow{ABCDEF} $
```



Placement

```
arrow under                                         (default autoconfig, initially unset)
arrow under=autoconfig|noconfig
```

Places the arrow under, instead of over.

`arrow under` or `arrow under=autoconfig` also configures suitably the key `detect subscripts`^{P.25} to `false` and the key `before arrow`^{P.24} to get an additional space over the arrow.

`arrow under=noconfig` does not do any additional configuration.

```
\NewOverArrowCommand{\underhooks}{%
  start={\lhook}, end={\rhook}, trim=1,
  arrow under, shift leftright=-4,
}
$ \underhooks{v} \qquad \underhooks{AB} $
```



Horizontal shifts

```
shift left={⟨number⟩}                                (no default, initially 2)
```

Shifts the left side of the arrow by $\langle number \rangle$ math units (positive number means a shift to the right).

```
shift right={⟨number⟩}                               (no default, see below for the initial value)
```

Shifts the right side of the arrow by $\langle number \rangle$ math units (positive number means a shift to the left).

The initial value of `shift right` depends on the $\langle method \rangle$ chosen at command creation (see section 4.2.1, page 17 for the documentation of commands creation):

- $\langle number \rangle = 0$ for the `symb` method (method by default);

- $\langle number \rangle = -2$ for the tikz, pstricks and picture methods.

```
\NewOverArrowCommand{\lookback}{%
  start=\leftarrow, end=\rightarrow,
  shift left=-50, shift right=-10,
}
$ \lookback{\text{look back}} $
```

\leftarrow look back \rightarrow

shift leftright=[$\langle number \rangle$] (no default)

Sets `shift left`^{P.23} and `shift right`^{P.23} to the same $\langle number \rangle$ value.

center arrow

Sets `shift left`^{P.23} and `shift right`^{P.23} to zero.

left arrow (default 2)

Sets `shift left`^{P.23} to zero and `shift right`^{P.23} to $\langle number \rangle$.

right arrow (default 2)

Sets `shift right`^{P.23} to zero and `shift left`^{P.23} to $\langle number \rangle$.

Vertical adjunct

before arrow={ $\langle vertical material \rangle$ } (initially empty)
after arrow={ $\langle vertical material \rangle$ } (initially empty)

Adds the $\langle vertical material \rangle$ before or after the arrow.

Over and under arrow commands are typeset through the TeX `\ialign` command, which aligns contents, like a tabular. The $\langle vertical material \rangle$ is inserted between the rows, with TeX `\noalign` command.

These keys are essentially used to add some extra space between the arrow and the content of the command. They can be set in a handier way with the keys `space before arrow` and `space after arrow`.

space before arrow={ $\langle length \rangle$ } (no default)

Adds a space of $\langle length \rangle$ before the arrow. This sets the keys `before arrow`.

space after arrow={ $\langle length \rangle$ } (no default)

Adds a space of $\langle length \rangle$ after the arrow. This sets the keys `after arrow`.

```
\NewOverArrowCommand{\overharpoonsdown}{%
  start=\leftharpoonup, end=\rightharpoonup, center arrow,
  space before arrow=-0.2ex, space after arrow=0.3ex,
}
$ \dot{\overharpoonsdown{v}} \qquad \ddot{\overharpoonsdown{AB}} $
```



4.3.2 Subscripts detection setting

This key is available whatever the method chosen at command creation (see section 4.2.1, page 17 for the documentation of commands creation).

detect subscripts=true|false (default true, see below for the initial value)

Removes automatically the extra end space created by the arrow, if a subscript immediately follows the command.

By default, the initial value of **detect subscripts** is **false**. When the option **subscripts^{P.17}** is set, the initial value of **detect subscripts** is **true**.

Note that the detection may fail when the standard subscript command is changed or altered (see the section 5.1.2, page 31).

```
\NewOverArrowCommand{\autosub}{detect subscripts}
$ \imath_0 \qquad \autosub{\imath}_0 \qquad
{\autosub{\imath}}_0 \qquad \autosub*{\imath}_0 $
```

\imath_0 $\overrightarrow{\imath}_0$ $\overrightarrow{\imath}_0$ $\overrightarrow{\imath}_0$

4.3.3 Symbols assemblage settings

The following keys are available for arrows drawn with the default **symb** method (see section 4.2.1, page 17 for the documentation of commands creation).

start={⟨command⟩} (no default, initially \relbar)

middle={⟨command⟩} (no default, initially set by **middle config=auto**)

end={⟨command⟩} (no default, see below for the initial value)

Sets the **⟨command⟩** used to draw the start (left), middle (center) or end (right) part of the arrow. The **middle** one is repeated, if necessary, to extend the arrow. It is set, initially by **middle config=auto**. By default, the **end** symbols is initially \rightarrow . When the option **old-arrows^{P.16}** is set, the initial value of **end** is \varrightarrows .

start and **end** symbols are typeset in the same group. **middle** is typeset alone. This means that, if a command, like \smallermathstyle ^{P.19}, is used to alter the symbols, it should be applied both to **start** and **middle** (but not to **end**).

```
\NewOverArrowCommand{\smalleroverrightarrow}{%
  start={\smallermathstyle\relbar},
  middle={\smallermathstyle\relbareda},
  end={\rightarrow},
  space after arrow={0.2ex},
}
$ \smalleroverrightarrow{v} \qquad \smalleroverrightarrow{AB} $
```

\vec{v} \overrightarrow{AB}

trim start={⟨number⟩} (no default, initially 7)

Trims **⟨number⟩** math units from the right side of the **start** symbol.

trim middle={⟨number⟩} (no default, initially set by **middle config=auto**)

Trims **⟨number⟩** math units from both left and right sides of the **middle** symbol.

trim end={⟨number⟩} (no default, initially 7)
Trims ⟨number⟩ math units from the left side of the `end` symbol.

trim={⟨number⟩} (no default)
Sets `trim start`^{P. 25}, `trim middle`^{P. 25} and `trim end` to the same ⟨number⟩ value.

no trimming
Clears `trim start`^{P. 25}, `trim middle`^{P. 25} and `trim end`.

middle config=auto|relbar|relbareda|harrowextender (no default)
Sets a suitable configuration for the keys `middle`^{P. 25} and `trim middle`^{P. 25}:

- For `middle config = relbar`, `middle`^{P. 25} is set to `\relbar` — and `trim middle`^{P. 25} to 2.5.
- For `middle config = relbareda`, `middle`^{P. 25} is set to `\relbareda` - and `trim middle`^{P. 25} to 1.
- For `middle config = harrowextender`, `middle`^{P. 25} is set to `\harrowextender` and `trim middle`^{P. 25} to 0.

For `middle config = auto`, if `\harrowextender` is provided by the math font¹⁰, `middle`^{P. 25} is set with `middle config = harrowextender`. If `\harrowextender` isn't available, `middle`^{P. 25} is set with `middle config = relbareda` if the option `esvect`^{P. 13} is set (which is the default) and `middle config = relabar` if not.

New: v1.2 2024/07/11

Updated: v1.2 2024/07/11

amsmath (default `mimic`)
amsmath=mimic|strict

Loads a configuration coherent with `amsmath \overrightarrow` command.

amsmath or amsmath=mimic sets the corresponding keys suitably:

```
start={\relbar}      middle={\relbar}      end={\rightarrow}
trim start=7       trim middle=2        trim end=7
shift leftright=0   after arrow={}     before arrow={}
```

`amsmath=strict` makes, in addition, the command uses the internal macros of `amsmath \overrightarrow` (`no trimming`, `fill macro={\arrowfill@}`, `stack macro={\overarrow@}`). Note that many configuration keys becomes ineffective.

esvect (default `mimic`)
esvect=mimic|strict

Loads a configuration coherent with `amsmath \vv` command.

esvect or esvect=mimic sets the corresponding keys suitably:

```
start={\relbared}    middle={\relbareda}    end={\fldr}
trim start=1.5      trim middle=0        trim end=1.5
space before arrow=-.7pt space after arrow=-.3pt right arrow=2
```

`esvect=strict` makes, in addition, the command uses the internal macros of `esvect \vv` (`no trimming`, `fill macro={\traitfill@}`, `stack macro={\overvect@}`). Note that many configuration keys becomes ineffective.

¹⁰See the documentation of the package `unicode-math`.

4.3.4 TikZ settings

If, at command creation (see section 4.2.1, page 17 for the documentation of commands creation), the `tikz` method is chosen, then the arrow is drawn by the command:

```
\tikz[<tikz options>]{<tikz command>}
```

where `tikz options` and `tikz command`^{P.28} are two keys described below. When `tikz command` is let unset, the drawing command turns into:

```
\tikz[<tikz options>]{\draw[<path options>] <path>;}
```

The best way to customise `tikz` arrows is then to set the keys `tikz options`, `path options` and `path`, preferably through the handy alternatives: `add tikz options`, `add path options`, `arrows`, `line thickness` or `thinner`^{P.28}.

```
\NewOverArrowCommand[tikz]{\overdotteddoublearrow}{%
    add tikz options={blue}, add path options={densely dotted},
    arrows={->[scale=0.5]>[scale=0.5]}, thinner,
    min length=20, space after arrow={0.3ex},
}
$ \overdotteddoublearrow{v} \qquad \overdotteddoublearrow{AB} $
```

The following keys are available when the `tikz` method is chosen.

tikz options ={<TikZ options>}	(no default, initially <code>x=\overarrowlength</code> , <code>line width=\overarrowthickness</code>)
Sets TikZ options to <TikZ options>.	
path options ={<path options>}	(no default, initially <code>arrows=-Classical TikZ Rightarrow, cap=round</code>)
Sets TikZ path options to <path options>.	
path ={<path specification>}	(no default, initially <code>(0,0)--(1,0)</code>)
Sets TikZ path specification to <path> (the ending semicolon is automatically appended).	
add tikz options ={<TikZ options>}	(no default)
Appends the options <TikZ options> to the key <code>tikz options</code> .	
add path options ={<path options>}	(no default)
Appends the options <path options> to the key <code>path options</code> .	
arrows ={<arrow specification>}	(no default)
Appends the option <code>arrows={<arrow specification>}</code> to the key <code>path options</code> .	
line thickness ={<length>}	(no default)
Appends the option <code>line width={<length>}</code> to the key <code>path options</code> .	

thinner

Sets the keys `line thickness` with `\overarrowsmallerthickness`.

tikz command={*TikZ command*} (initially unset)

Sets the *TikZ command* used to draw the arrow. If left unset, the value `\draw[path options] path;` is used.

4.3.5 PSTricks settings

New: v1.2 2024/07/11 If, at command creation (see section 4.2.1, page 17 for the documentation of commands creation), the `pstricks` method is chosen, then the arrow is drawn by:

```
\begin{pspicture}<geometry>%
  \psset{linewidth=<line thickness>}%
  \psset{<psset>}%
  <pstricks command>%
\end{pspicture}
```

where `geometry`, `line thickness`^{P.29} `psset` and `pstricks command` are four keys described below.

```
\NewOverArrowCommand[pstricks]{\overloopandarrow}{
  pstricks command=%
  \pscurve{->}(0,0)
  (0.6\overarrowlength,0.05\overarrowlength)
  (0.5\overarrowlength,0.1\overarrowlength)
  (0.4\overarrowlength,0.05\overarrowlength)
  (\overarrowlength,0)
},
geometry={(0,0)(\overarrowlength,0.2\overarrowlength)},
space after arrow=2pt, min length=20,
geometry={(0,0)(\overarrowlength,0.2\overarrowlength)},
}
$ \overloopandarrow{v} \qquad \overloopandarrow{AB} $
```



The following keys are available when the `pstricks` method is chosen.

pstricks command={*pstricks command*}

(no default, initially `\psline{->}(0,0)(\overarrowlength,0)`)

Sets the `pspicture` command to *pstricks command*.

arrow={*arrow*}

(no default, initially `->`)

Sets `pstricks` command with `\psline{<arrow>}(0,0)(\overarrowlength,0)`.

psset={*pstricks setting*}

(no default, initially empty)

Sets *pstricks setting* with `\psset`.

geometry={*pstricks geometry specification*}

(no default, initially `(0,-0.5ex)(\overarrowlength,1ex)`)

Sets the `pspicture` geometry to *pstricks geometry specification*.

line thickness={ $\langle length \rangle$ } (no default)

Sets the line thickness to $\langle length \rangle$.

thinner

Sets the keys **line thickness** with `\overarrowsmallerthickness`.

4.3.6 Picture environment settings

If, at command creation (see section 4.2.1, page 17 for the documentation of commands creation), the **picture** method is chosen, then the arrow is drawn by:

```
\begin{picture}<geometry>%
  \linethickness{<line thickness>}%
  <picture command>%
\end{picture}%
```

where **geometry**, **line thickness** and **picture command** are three keys described below.

```
% ^~A \arc and \roundcap commands are from the pict2e package
% ^~A this example needs \usepackage{pict2e} in the preamble
\NewOverArrowCommand[picture]{\overarc}{%
  picture command={%
    \roundcap
    \put(0.5\overarrowlength,0){\arc[180,0]{0.6\overarrowlength}}
  },
  geometry={%
    (1.2\overarrowlength,0.5\overarrowlength)(-0.1\overarrowlength,0.2ex)
  },
  thinner, center arrow,
}
$ \overarc{v} \qquad \overarc{AB}
```

The following keys are available when the **picture** method is chosen.

picture command={ $\langle picture\ command \rangle$ } (no default, initially `\put(0,0){\vector(1,0){\overarrowlength}}`)

Sets picture command to $\langle picture\ command \rangle$.

geometry={ $\langle picture\ geometry\ specification \rangle$ } (no default, initially `(\overarrowlength,1ex)(0,-0.5ex)`)

Sets picture geometry to $\langle picture\ geometry\ specification \rangle$.

line thickness={ $\langle length \rangle$ } (no default)

Sets the picture line thickness to $\langle length \rangle$.

thinner (no default)

Sets the keys **line thickness** with `\overarrowsmallerthickness`.

4.4 Advanced commands and keys

The following commands and keys are used in the implementation of the `overarrows` package. They can also be employed for an advanced configuration of the commands created, although unnecessary in the vast majority of cases.

4.4.1 Advanced commands

`\SetOverArrowsSubscriptCommand{<command>}`

New: v1.1 2023/02/15

Sets to `<command>` the command used for subscript detection, when this is enabled by the key `detect subscripts`^{P.25} (see the section 5.1.2, page 31).

`\SetOverArrowsMethod[<stack mechanism>]{<name>}[<pre code>]{<keys def>}`
`\SetOverArrowsMethod*{<name>}[<pre code>]{<keys def>}`

Defines the method `<name>`, to be used in commands `\NewOverArrowCommand`^{P.17}, `\RenewOverArrowCommand`^{P.17}, `\ProvideOverArrowCommand`^{P.17} or `\DeclareOverArrowCommand`^{P.17}. When the `<name>` method is chosen, corresponding keys are defined by `<keys def>`. This must set, in particular, the keys `no stack macro hook`^{P.31} and `no arrow macro hook`^{P.31}. Optional code `<pre code>` is evaluated before the keys definition.

The unstarred variant automatically defines the key `no stack macro hook`^{P.31}, according to the value of the optional `<stack mechanism>`. This one must be:

`fill` if `arrow macro` creates extensible arrows (typically with `\cleaders`).

In this case, the arrow macro (defined by `no arrow macro hook`^{P.31}) is called with the math style, passed as argument (it can be, for example, the macro `\rightarrowfill@` used by `amsmath \overrightarrow`). `fill` is the mechanism used by the `symb` method.

`lens` if `arrow macro` creates fixed-length arrows, and needs the computation of lengths `\overarrowlength`^{P.20}, `\overarrowthickness`^{P.20} and `\overarrowsmallerthickness`^{P.20}. In this case, the arrow macro (defined by `no arrow macro hook`^{P.31}) is called without argument. `lens` is the mechanism used by the `tikz` and `picture` methods.

Without optional `<stack mechanism>`, `fill` is used. The starred variant does not set the key `no stack macro hook`^{P.31}.

4.4.2 Advanced keys

`stack macro=<stack definition>`

(no default, initially unset)

Defines the stack macro to be `<stack definition>`. Stack macro is a command which takes three arguments: the arrow macro set by `arrow macro`, the math style, and the command content (under or over the arrow). `<stack definition>` can be, for example, the macro `\overarrow@` used by `amsmath \overrightarrow`.

`arrow macro=<arrow definition>`

(no default, initially unset)

Defines the arrow macro (used in the stack macro) by to be `<arrow definition>`.

no stack macro hook={\langle code\rangle} (no default)

Sets the ⟨code⟩ executed if **stack macro** is left unset, after user evaluation of ⟨keys⟩ in $\backslash\text{NewOverArrowCommand}$ ^{P. 17}, $\backslash\text{RenewOverArrowCommand}$ ^{P. 17}, $\backslash\text{ProvideOverArrowCommand}$ ^{P. 17} or $\backslash\text{DeclareOverArrowCommand}$ ^{P. 17}.
⟨code⟩ must configure **stack macro**^{P. 30} accordingly to the user keys setting.

no arrow macro hook={\langle code\rangle} (no default)

Sets the ⟨code⟩ executed if **arrow macro**^{P. 30} is left unset, after user evaluation of ⟨keys⟩ in $\backslash\text{NewOverArrowCommand}$ ^{P. 17}, $\backslash\text{RenewOverArrowCommand}$ ^{P. 17}, $\backslash\text{ProvideOverArrowCommand}$ ^{P. 17} or $\backslash\text{DeclareOverArrowCommand}$ ^{P. 17}.
⟨code⟩ must configure **arrow macro**^{P. 30} accordingly to the user keys setting.

fill macro={\langle definition\rangle} (no default, initially unset)

Defines the fill macro to be ⟨definition⟩. The fill macro is used by arrows created with the **symb** method, to set **arrow macro**^{P. 30} in **no arrow macro hook**. It is called with fours arguments: start, middle and end symbols used to draw the arrow, and the math style. ⟨definition⟩ can be, for example, the macro \arrowfill@ used by **amsmath** $\text{\overrightarrow{}}$.

5 Complements

5.1 Know issues

5.1.1 Math font change

If the math font differs from the default *Computer Modern*, arrow drawn with the **symb** method may have a central part of the arrow with inappropriate position or line width. This is because the default symbol used for the arrow line is \relbar - from the **esvect** package. This can be fixed with the **noesvect**^{P. 14} option.

Depending of the math font, predefined commands may be faulty. For example, at the time of writing, hooks vertical position is incorrect with *Asana Math* or \harpoonright is badly positioned with *Stix two Math* (for the smallest math styles), *Libertinus Math* and *GFSNeohellenicMath*.

5.1.2 Detection of non standard subscripts

The subscript detection enabled by the key **detect subscripts**^{P. 25} is based on the **LATEX** macro \@ifnextchar . The detection may fail if the standard subscript command is modified or altered. This is the case, as example:

- with the **spbmark** package (<https://www.ctan.org/pkg/spbmark>), by Qu Yi, which allows a complete customisation of subscripts, through the \sub command;
- with the **altsupsub** package (<https://www.ctan.org/pkg/altsupsub>), by Julien Labb , which provides an alternative subscript format, and changes, for this purpose, the catcode of the underscore symbol “_” from 8 (*subscript* catcode category) to 12 (*other* catcode category).

To handle these cases, the command used for subscript detection can be re-defined with `\SetOverArrowsSubscriptCommand→P.30`. Compatibility with the `spmark` package is then obtained by:

```
\SetOverArrowsSubscriptCommand{\sub}
```

In the same way, with the `alsubsup` package, add:

```
\SetOverArrowsSubscriptCommand{_}
```

after the `\begin{document}` (namely, after the catcode redefinition done by `alsubsup`).

Alternatively, two package options handle the cases where the catcode of the underscore “`_`” symbol is changed: `subother→P.17` (for catcode 12, or *other*) and `subactive→P.17` (for catcode 13, or *active*). Hence, setting the `subother→P.17` option is sufficient for compatibility with the `alsubsup` package (no need of `\SetOverArrowsSubscriptCommand→P.30`). Note, that with options `subother→P.17` and `subactive→P.17`, the command `\TestOverArrow*→P.18` may give bad results for kerning test, as defined before the catcode redefinition.

5.2 Package dependencies

The following packages are used by `overarrows`:

- `amsmath`
- `etoolbox`
- `pgfkeys`
- `esvect` (unless the option `noesvect→P.14` is used)
- `old-arrows` (when the option `old-arrows→P.16` is used)
- `tikz` (when the `tikz` method or the option `tikz→P.16` is used)
- `pict2e` (when the option `pstarrows→P.17` is used)

`LATEX` distributions prior to 2020/10/01 must load the `xparse` package before `overarrows`.

5.3 Alternatives

esvect package (<https://www.ctan.org/pkg/esvect>), by Eddie Saudrais, provides the fine vector macro `\vv`. This package is loaded by default by `overarrows`.

letterswitharrows package (<https://www.ctan.org/pkg/letterswitharrows>), by Max Teegen, provides left and right over arrows commands, which can extend to multiple characters.

overrightarrow package (<https://www.ctan.org/pkg/overrightarrow>), by Robin Fairbairns, provides the `\Overrightarrow` which is an amalgam of `\overrightarrow` and `\Rightarrow`.

harpoon package (<https://ctan.org/pkg/harpoon>), by Tobias Kuipers, provides over- and under-harpoon symbol commands.

5.4 Changelog

- v1.2
 - Fix compatibility issues with `unicode-math`.
 - Allow to draw the arrow with PStricks.
 - Make `esvect` handle all font sizes.
 - Rewrite starred variant for better performances.
- v1.1 Support for non-standard subscripts.
- v1.0.1 Bug fix for `under*` options.
- v1.0 Initial version.

6 Implementation

Management of options

Declaration of conditionals

```
1 \newif\ifovar@option@oldarrows@
2 \newif\ifovar@option@esvect@ \ovar@option@esvect@true \PassOptionsToPackage{f}{esvect}
3 \newif\ifovar@option@tikz@
4 \newif\ifovar@option@pstricks@
5 \newif\ifovar@option@pstarrows@
6 \newif\ifovar@detectsubscripts@
7 \newif\ifovar@option@subother@
8 \newif\ifovar@option@subactive@
9 \newif\ifovar@option@debug@
```

Following conditionals are for predefined commands.

```
10 \newif\ifovar@option@overrightarrow@
11 \newif\ifovar@option@underrightarrow@
12 \newif\ifovar@option@overleftarrow@
13 \newif\ifovar@option@underleftarrow@
14 \newif\ifovar@option@overleftrightarrow@
15 \newif\ifovar@option@underleftrightarrow@
16 \newif\ifovar@option@overrightharpoonup@
17 \newif\ifovar@option@underrightharpoonup@
18 \newif\ifovar@option@overrightharpoondown@
19 \newif\ifovar@option@underrightharpoondown@
20 \newif\ifovar@option@overleftharpoonup@
21 \newif\ifovar@option@underleftharpoonup@
22 \newif\ifovar@option@overleftharpoondown@
23 \newif\ifovar@option@underleftharpoondown@
24 \newif\ifovar@option@overbar@
25 \newif\ifovar@option@underbar@
```

Declaration of options

```
26 \DeclareOption{esvect}{\ovar@option@esvect@true}
27 \DeclareOption{noesvect}{\ovar@option@esvect@false}
28 \DeclareOption{esvecta}{\ovar@option@esvect@true\PassOptionsToPackage{a}{esvect}}
29 \DeclareOption{esvectb}{\ovar@option@esvect@true\PassOptionsToPackage{b}{esvect}}
30 \DeclareOption{esvectc}{\ovar@option@esvect@true\PassOptionsToPackage{c}{esvect}}
```

```

31 \DeclareOption{esvectd}{\ovar@option@esvect@true\PassOptionsToPackage{d}{esvect}}
32 \DeclareOption{esvecte}{\ovar@option@esvect@true\PassOptionsToPackage{e}{esvect}}
33 \DeclareOption{esvectf}{\ovar@option@esvect@true\PassOptionsToPackage{f}{esvect}}
34 \DeclareOption{esvectg}{\ovar@option@esvect@true\PassOptionsToPackage{g}{esvect}}
35 \DeclareOption{esvecth}{\ovar@option@esvect@true\PassOptionsToPackage{h}{esvect}}
36 \DeclareOption{old-arrows}{\ovar@option@oldarrows@true}
37 \DeclareOption{tikz}{\ovar@option@tikz@true}
38 \DeclareOption{pstricks}{\ovar@option@pstricks@true}
39 \DeclareOption{pstarrows}{\ovar@option@pstarrows@true}
40 \DeclareOption{subscripts}{\ovar@detectsubscripts@true}
41 \DeclareOption{subother}{\ovar@option@subother@true}
42 \DeclareOption{subactive}{\ovar@option@subactive@true}
43 \DeclareOption{debug}{\ovar@option@debug@true}

```

Following options are for predefined commands.

```

44 \DeclareOption{overrightarrow}{\ovar@option@overrightarrow@true}
45 \DeclareOption{underrightarrow}{\ovar@option@underrightarrow@true}
46 \DeclareOption{overleftarrow}{\ovar@option@overleftarrow@true}
47 \DeclareOption{underleftarrow}{\ovar@option@underleftarrow@true}
48 \DeclareOption{overleftrightarrow}{\ovar@option@overleftrightarrow@true}
49 \DeclareOption{underleftrightarrow}{\ovar@option@underleftrightarrow@true}
50 \DeclareOption{overrightharpoonup}{\ovar@option@overrightharpoonup@true}
51 \DeclareOption{underrightharpoonup}{\ovar@option@underrightharpoonup@true}
52 \DeclareOption{overrightharpoondown}{\ovar@option@overrightharpoondown@true}
53 \DeclareOption{underrightharpoondown}{\ovar@option@underrightharpoondown@true}
54 \DeclareOption{overleftharpoonup}{\ovar@option@overleftharpoonup@true}
55 \DeclareOption{underleftharpoonup}{\ovar@option@underleftharpoonup@true}
56 \DeclareOption{overleftharpoondown}{\ovar@option@overleftharpoondown@true}
57 \DeclareOption{underleftharpoondown}{\ovar@option@underleftharpoondown@true}
58 \DeclareOption{overbar}{\ovar@option@overbar@true}
59 \DeclareOption{underbar}{\ovar@option@underbar@true}

```

Following options are for sets of predefined commands.

```

60 \DeclareOption{overcommands}{%
61   \ovar@option@overrightarrow@true
62   \ovar@option@overleftarrow@true
63   \ovar@option@overleftrightarrow@true
64   \ovar@option@overrightharpoonup@true
65   \ovar@option@overrightharpoondown@true
66   \ovar@option@overleftharpoonup@true
67   \ovar@option@overleftharpoondown@true
68   \ovar@option@overbar@true
69 }
70 \DeclareOption{undercommands}{%
71   \ovar@option@underrightarrow@true
72   \ovar@option@underleftarrow@true
73   \ovar@option@underleftrightarrow@true
74   \ovar@option@underrightharpoonup@true
75   \ovar@option@underrightharpoondown@true
76   \ovar@option@underleftharpoonup@true
77   \ovar@option@underleftharpoondown@true
78   \ovar@option@underbar@true
79 }
80 \DeclareOption{allcommands}{%
81   \ovar@option@overrightarrow@true
82   \ovar@option@underrightarrow@true
83   \ovar@option@overleftarrow@true
84   \ovar@option@underleftarrow@true
85   \ovar@option@overleftrightarrow@true
86   \ovar@option@underleftrightarrow@true
87   \ovar@option@overrightharpoonup@true
88   \ovar@option@underrightharpoonup@true

```

```

89   \ovar@option@overrightharpoondown@true
90   \ovar@option@underrightharpoonup@true
91   \ovar@option@overleftharpoonup@true
92   \ovar@option@underleftharpoonup@true
93   \ovar@option@overleftharpoondown@true
94   \ovar@option@underleftharpoondown@true
95   \ovar@option@overbar@true
96   \ovar@option@underbar@true
97 }

```

Options processing

```

98 \DeclareOption*{\PackageWarning{overarrows}{Unknown option: '\CurrentOption'}}
99 \ProcessOptions\relax

```

Package dependencies

LATEX distributions prior to 2020/10/01 must add the `xparse` package.

```

100 \RequirePackage{amsmath}
101 \RequirePackage{etoolbox}

```

Option `old-arrows`^{→ P. 16}. Configuration of arrows used for predefined commands.

```

102 \def\ovar@rightarrow{\rightarrowarrow}
103 \def\ovar@leftarrow{\leftarrowarrow}
104 \ifovar@option@oldarrows@
105   \RequirePackage[old]{old-arrows}
106   \def\ovar@rightarrow{\varrightarrowarrow}
107   \def\ovar@leftarrow{\varleftarrowarrow}
108 \fi

```

Option `esvect`^{→ P. 13}.

```

109 \ifovar@option@esvect@
110   \RequirePackage{esvect}

```

Fix font description in `uesvect.fd` to allow any sizes (taken from Enrico Gregorio, <https://tex.stackexchange.com/a/689863/>)

```

111 \DeclareFontFamily{U}{esvect}{}{}
112 \DeclareFontShape{U}{esvect}{m}{n}{
113   <-5.5> vect5
114   <5.5-6.5> vect6
115   <6.5-7.5> vect7
116   <7.5-8.5> vect8
117   <8.5-9.5> vect9
118   <9.5-> vect10
119 }{}
120 \fi

```

Option `tikz`^{→ P. 16}.

```

121 \ifovar@option@tikz@
122   \RequirePackage{tikz}
123   \usetikzlibrary{arrows.meta}
124 \fi

```

Option `pstricks`^{→ P. 16}.

```

125 \ifovar@option@pstricks@
126   \RequirePackage{pstricks-add}
127 \fi

```

Option `pstarrows`^{→ P. 17}.

```

128 \ifovar@option@pstarrows@
129   \RequirePackage[pstarrows]{pict2e}
130 \fi

Add hook rules to apply settings after unicode-math.

131 \DeclareHookRule{begindocument}{overarrows}{after}{unicode-math-luatex}
132 \DeclareHookRule{begindocument}{overarrows}{after}{unicode-math-xetex}

Set \ovar@auto@middle and \ovar@auto@trim@middle, used by configurations
made with middle config=auto.

133 \AddToHook{begindocument}{overarrows}
134 {%
135   \ifdef{\relbareda}
136   {%
137     \gdef\ovar@auto@middle{\relbareda}
138     \gdef\ovar@auto@trim@middle{1}
139   }
140   {%
141     \gdef\ovar@auto@middle{\relbar}
142     \gdef\ovar@auto@trim@middle{2.5}
143   }%
144   \@ifpackage{unicode-math}
145   {%

```

Test of \harrowextender availability taken from Enrico Gregorio, (<https://tex.stackexchange.com/a/218407/>).

```

146   \check@mathfonts
147   \iffontchar{textfont}{tw@}{\string"23AF}
148   \gdef\ovar@auto@middle{\mathrel\harrowextender}
149   \gdef\ovar@auto@trim@middle{0}
150   \fi
151   }
152   {}%
153 }


```

Configuration of subscripts detection

\SetOverArrowsSubscriptCommand

Sets the subscript command.

```

154 \newcommand{\SetOverArrowsSubscriptCommand}[1]{\global\let\ovar@subcmd=#1}
```

Initial configuration.

```

155 \SetOverArrowsSubscriptCommand{_}
```

Option **subother**^{→ P. 17} for *other* (catcode 12) subscript commands.

```

156 \ifovar@option@subother@
157   \begingroup
158   \catcode`_=12
159   \SetOverArrowsSubscriptCommand{_}%
160   \endgroup
161 \fi
```

Option **subactive**^{→ P. 17} for *active* (catcode 13) subscript commands.

```

162 \ifovar@option@subactive@
163   \begingroup
164   \catcode`_=13
165   \SetOverArrowsSubscriptCommand{_}%
166   \endgroup
167 \fi
```

Management of keys

Family declaration and setters

```
168 \RequirePackage{pgfkeys}
169 \pgfkeys{overarrows/.is family}
170 \newcommand{\ovar@set}[1]{\pgfqkeys{/overarrows}{#1}}
\SetOverArrowsMethod
171 \NewDocumentCommand{\SetOverArrowsMethod}{ s O{fill} m O{} m }{%
172   \IfBooleanTF{#1}{%
173     \csgdef{\ovar@set@#3}{\#4\ovar@set{\#5}}%
174   }{%
175     \csgdef{\ovar@set@#3}{\#4\ovar@set{%
176       no stack macro hook/.code={%
177         \ovar@set{stack macro/.expanded={%
178           \expandafter\expandonce\csname ovar@stack@#2\endcsname%
179           {\expandonce\ovar@length@min}%
180           {\expandonce\ovar@before@arrow}{\expandonce\ovar@after@arrow}%
181           }%
182         },#5}%
183       }%
184     }%
185 }
```

Common keys

```
185 \SetOverArrowsMethod*{common}[\undef{\ovar@macro@stack}\undef{\ovar@macro@arrow}]{%
186   detect subscripts\rightarrow P.25.
187   detect subscripts/.is if=\ovar@detectsubscripts@,
188   stack macro\rightarrow P.30 and arrow macro\rightarrow P.30.
189   stack macro/.store in=\ovar@macro@stack,
190   arrow macro/.store in=\ovar@macro@arrow,
191   stack macro/.value required,
192   arrow macro/.value required,
```

no stack macro hook^{\rightarrow P.31}, no arrow macro hook^{\rightarrow P.31}. These two keys must be redefined by the command \ovar@set@<method>.

```
193   no stack macro hook/.code={%
194     \PackageError{overarrows}{Undefined stack macro}%
195     {The requested method is perhaps misspelled}%
196   },
197   no arrow macro hook/.code={%
198     \PackageError{overarrows}{Undefined arrow macro}%
199     {The requested method is perhaps misspelled}%
200   },
201
202   min length\rightarrow P.23.
203   min length/.store in=\ovar@length@min,
204   min length/.value required,
205   min length=0,
206
207   before arrow\rightarrow P.24, after arrow\rightarrow P.24, space before arrow\rightarrow P.24, space after
208   arrow\rightarrow P.24.
209   before arrow/.store in=\ovar@before@arrow,
210   after arrow/.store in=\ovar@after@arrow,
211   before arrow/.value required,
212   after arrow/.value required,
213   before arrow=\empty,
214   after arrow=\empty,
215   space before arrow/.code=\pgfkeysalso{before arrow={\kern ##1}},
216   space after arrow/.code=\pgfkeysalso{after arrow={\kern ##1}},
```

```

shift left→ P.23, shift right→ P.23, shift leftright→ P.24, center arrow→ P.24,
left arrow→ P.24, right arrow→ P.24.
210  shift left/.store in=\ovar@shift@left,
211  shift right/.store in=\ovar@shift@right,
212  shift left/.value required,
213  shift right/.value required,
214  shift leftright/.code=\pgfkeysalso{%
215    shift left=##1, shift right=##1,
216  },
217  center arrow/.code=\pgfkeysalso{shift leftright=0},
218  shift leftright/.value required,
219  center arrow/.value forbidden,
220  left arrow/.code=\pgfkeysalso{%
221    shift left=0, shift right=##1,
222  },
223  right arrow/.code=\pgfkeysalso{%
224    shift left=##1, shift right=0,
225  },
226  left arrow/.default=2,
227  right arrow/.default=2,
228  right arrow,
229
arrow under→ P.23.
230  arrow under/.is choice,
231  arrow under/noconfig/.code={%
232    \def\ovar@stack@fill{\ovar@stackunder@fill}
233    \def\ovar@stack@lens{\ovar@stackunder@lens}
234  },
235  arrow under/autoconfig/.code={%
236    \pgfkeysalso{%
237      arrow under=noconfig,
238      detect subscripts=false,
239      before arrow={\kern 1.3\ex@relax},% like underarrow@ from amsmath
240    }
241  },
242  arrow under/.default=autoconfig,
}

```

Keys for the symb method

```
243 \SetOverArrowsMethod{symb}[\undef{\ovar@macro@arrowfill}]{%
```

Fill macro.

```
244 fill macro/.store in=\ovar@macro@arrowfill,
245 fill macro/.value required,
```

Arrow macro.

```

246 no arrow macro hook/.code={%
247 \ifdef{\ovar@macro@arrowfill}{}{%
248   \ovar@set{%
249     fill macro/.expanded={%
250       \noexpand\ovar@arrow@fill%
251       {\expandonce{\ovar@shift@left}}{\expandonce{\ovar@shift@right}}%
252     }
253   }
254 }
255 \ovar@set{%
256   arrow macro/.expanded={%
257     \expandonce{\ovar@macro@arrowfill}%
258     {\expandonce{\ovar@arrow@start}\expandonce{\ovar@trim@start}}%
259     {\expandonce{\ovar@trim@middle}\expandonce{\ovar@arrow@middle}}%
260     \expandonce{\ovar@trim@middle}}%
}

```

```

261         {\expandonce{\ovar@trim@end}\expandonce{\ovar@arrow@end}}%
262     }
263   }
264 },
265 start→P.25, middle→P.25, end→P.25.
266 start/.store in=\ovar@arrow@start,
267 middle/.store in=\ovar@arrow@middle,
268 end/.store in=\ovar@arrow@end,
269 start/.value required,
270 middle/.value required,
271 end/.value required,
272
273 trim start→P.25, trim middle→P.25, trim end→P.26, trim→P.26, no trimming→P.26.
274
275 trim start/.code={\def\ovar@trim@start{\xjoinrel[##1]}},
276 trim middle/.code={\def\ovar@trim@middle{\xjoinrel[##1]}},
277 trim end/.code={\def\ovar@trim@end{\xjoinrel[##1]}},
278 trim start/.value required,
279 trim middle/.value required,
280 trim end/.value required,
281 trim/.code={\pgfkeysalso{trim start={##1}, trim middle={##1}, trim end={##1}}},
282 trim/.value required,
283 no trimming/.code={%
284   \let\ovar@trim@start\empty
285   \let\ovar@trim@middle\empty
286   \let\ovar@trim@end\empty
287 },
288 no trimming/.value forbidden,
289
290 middle config→P.26.
291
292 middle config/.is choice,
293 middle config/.value required,
294 middle config/relbar/.code=\pgfkeysalso{%
295   middle={\relbar},
296   trim middle={2.5},
297 },
298 middle config/relbareda/.code={%
299   \ifundef{\relbareda}{%
300     \PackageWarning{overarrows}{Key 'middle config=relbareda' used,
301       \MessageBreak%
302       but \protect\relbareda\space is undefined; ignored.
303       \MessageBreak%
304       Load 'esvect' package, or use 'esvect' option \MessageBreak%
305       to remove this warning}
306   }{%
307     \pgfkeysalso{%
308       middle={\relbareda},
309       trim middle={1},
310     }
311   }
312
313 middle config/harrowextender/.code={%
314   \pgfkeysalso{%
315     middle={\harrowextender},
316     trim middle={0},
317   }
318 },

```

Set `middle config` with (hopefully) a good configuration. It would be better to reuse the previous `middle config` settings, but we have to wait for the `begindocument` hook to know which one to use.

```

312   middle config/auto/.code={%
313     \pgfkeysalso{%
314       middle={\ovar@auto@middle},
315       trim middle={\ovar@auto@trim@middle},
316     }
317   },
318 
319   amsmath/.is choice,%
320   amsmath/mimic/.code=\pgfkeysalso{%
321     start={\relbar}, middle={\relbar}, end={\rightarrow},
322     trim start=7,
323     trim middle=2,
324     trim end=7,
325     shift leftright=0,
326     after arrow={}, before arrow={},
327   },
328   amsmath/strict/.code=\pgfkeysalso{%
329     amsmath=mimic,
330     no trimming,
331     fill macro={\arrowfill@}, stack macro={\overarrow@},
332   },
333   amsmath/.default=mimic,
334 
335   esvect/.is choice,%
336   esvect/mimic/.code=\pgfkeysalso{%
337     start={\relbared}, middle={\relbareda}, end={\fldr},
338     trim start=1.5,
339     trim end=1.5,
340     trim middle=0,
341     right arrow=2,
342     space before arrow=-.7pt,
343     space after arrow=-.3pt,
344   },
345   esvect/strict/.code=\pgfkeysalso{%
346     esvect=mimic,
347     no trimming,
348     fill macro={\traitfill@}, stack macro={\overvect@},
349   },
350   esvect/.default=mimic,

```

Initial configuration.

```

349   amsmath, middle config=auto, end=\ovar@rightarrow, right arrow,
350 }

```

Keys for the tikz method

```

351 \SetOverArrowsMethod[lens]{tikz}{\undef{\ovar@tikz@command}}{%

```

Arrow macro.

```

352   no arrow macro hook/.code={%
353     \ifdef{\ovar@tikz@command}{}{%
354       \pgfkeysgetvalue{/overarrows/path options}{\ovar@tikz@pathoptions}
355       \ovar@set{%
356         tikz command/.expanded={%
357           \noexpand\draw[\expandonce\ovar@tikz@pathoptions]\expandonce\ovar@tikz@path;
358         }
359       }
360     }
361     \pgfkeysgetvalue{/overarrows/tikz options}{\ovar@tikz@options}
362     \ovar@set{%

```

```

363     arrow macro/.expanded={%
364         $\noexpand\mkern \expandonce{\ovar@shift@left} mu\noexpand\relax$%
365         \noexpand\tikz[\expandonce{\ovar@tikz@options}]{\expandonce{\ovar@tikz@command}}%
366         $\noexpand\mkern \expandonce{\ovar@shift@right} mu\noexpand\relax$%
367     }
368 }
369 },

```

TikZ parts: tikz command \rightarrow P. 28, tikz options \rightarrow P. 27, path options \rightarrow P. 27, path \rightarrow P. 27.

```

370 tikz command/.store in=\ovar@tikz@command,
371 tikz options/.initial={x=\overarrowlength, line width=\overarrowthickness},
372 path options/.initial={arrows={-Classical TikZ Rightarrow}, cap=round},
373 path/.store in=\ovar@tikz@path,
374 path={(0,0)--(1,0)},
375 tikz command/.value required,
376 tikz options/.value required,
377 path options/.value required,
378 path/.value required,

```

TikZ handy keys: add path options \rightarrow P. 27, add tikz options \rightarrow P. 27, arrows \rightarrow P. 27, line thickness \rightarrow P. 27, thinner \rightarrow P. 28.

```

379 add path options/.code=\pgfkeysalso{%
380     path options/.append={, ##1}},%
381 add tikz options/.code=\pgfkeysalso{%
382     tikz options/.append={, ##1}},%
383 arrows/.code=\pgfkeysalso{add path options={arrows={##1}}},%
384 line thickness/.code=\pgfkeysalso{add path options=[line width=##1]},%
385 thinner/.code=\pgfkeysalso{line thickness={\overarrowsmallerthickness}},%
386 add path options/.value required,%
387 add tikz options/.value required,%
388 arrows/.value required,%
389 line thickness/.value required,%
390 thinner/.value forbidden,%

```

Initial configuration.

```

391 shift right=-2,
392 min length=12,
393 }

```

Keys for the pstricks method

```
394 \SetOverArrowsMethod[lens]{pstricks}{%
```

Arrow macro.

```

395 no arrow macro hook/.code={%
396     \ovar@set{%
397         arrow macro/.expanded={%
398             $\noexpand\mkern \expandonce{\ovar@shift@left} mu\noexpand\relax$%
399             \noexpand\begin{pspicture}\expandonce{\ovar@pstricks@geometry}%
400                 \noexpand\psset{linewidth=\expandonce{\ovar@pstricks@linethickness}}%
401                 \noexpand\psset{\expandonce{\ovar@pstricks@psset}}%
402                 \expandonce{\ovar@pstricks@command}%
403                 \noexpand\end{pspicture}%
404                 $\noexpand\mkern \expandonce{\ovar@shift@right} mu\noexpand\relax$%
405             }
406         }
407     },

```

Pstricks parts: pstricks command \rightarrow P. 28, psset \rightarrow P. 28, geometry \rightarrow P. 28, line thickness \rightarrow P. 29.

```

408 pstricks command/.store in=\ovar@pstricks@command,
409 psset/.store in=\ovar@pstricks@psset,
410 geometry/.store in=\ovar@pstricks@geometry,
411 line thickness/.store in=\ovar@pstricks@linethickness,
412 pstricks command/.value required,
413 psset/.value required,
414 geometry/.value required,
415 line thickness/.value required,

```

Pstricks handy key: `arrow`^{→ P. 28}, `thinner`^{→ P. 29}.

```

416 arrow/.style={pstricks command={\psline{##1}(0,0)(\overarrowlength,0)}},%
417 arrow/.value required,%
418 thinner/.style={line thickness={\overarrowsmallerthickness}},%
419 thinner/.value forbidden,%

```

Initial configuration.

```

420 shift right=-2,
421 min length=12,
422 geometry={(0,-0.5ex)(\overarrowlength,0.5ex)},%
423 line thickness={\overarrowthickness},%
424 arrow={->},%
425 psset={},%
426 }

```

Keys for the picture method

```

427 \SetOverArrowsMethod[lens]{picture}{%

```

Arrow macro.

```

428 no arrow macro hook/.code={%
429   \ovar@set{%
430     arrow macro/.expanded={%
431       $\noexpand\mkern \expandonce{\ovar@shift@left} mu\noexpand\relax$%
432       \noexpand\begin{picture}\expandonce{\ovar@picture@geometry}%
433         \noexpand\linethickness{\expandonce{\ovar@picture@linethickness}}%
434         \expandonce{\ovar@picture@command}%
435         \noexpand\end{picture}%
436       $\noexpand\mkern \expandonce{\ovar@shift@right} mu\noexpand\relax$%
437     }
438   }
439 },

```

Picture parts: `picture command`^{→ P. 29}, `geometry`^{→ P. 29}, `line thickness`^{→ P. 29}.

```

440 picture command/.store in=\ovar@picture@command,
441 geometry/.store in=\ovar@picture@geometry,
442 line thickness/.store in=\ovar@picture@linethickness,
443 picture command/.value required,
444 geometry/.value required,
445 line thickness/.value required,

```

Picture handy key: `thinner`^{→ P. 29}.

```

446 thinner/.code=\pgfkeysalso{line thickness={\overarrowsmallerthickness}},%

```

Initial configuration.

```

447 shift right=-2,
448 min length=18,
449 geometry={(\overarrowlength,1ex)(0,-0.5ex)},%
450 line thickness={\overarrowthickness},%
451 picture command={\put(0,0){\vector(1,0){\overarrowlength}}},%
452 }

```

Commands

Macros for symbols assemblage

```
\xjoinrel  
453 \ifdef{\xjoinrel}{%  
454   \PackageWarning{overarrows}{Command \protect\xjoinrel\space already defined.  
455     \MessageBreak%  
456     Previous definition will be overridden}  
457 }{}
```

Use a default value of 3.5 mu, as recommended by Enrico Gregorio (see <https://tex.stackexchange.com/a/471736>). \joinrel uses a value of 3 mu.

```
458 \DeclareRobustCommand{\xjoinrel}[1][3.5]{\mathrel{\mkern-#1mu}}  
\smallermathstyle  
459 \newcommand*{\smallermathstyle}{%  
460   \mathchoice{\scriptstyle}{\scriptstyle}{\scriptstyle}{\scriptstyle}{}}  
461 }
```

\ovar@arrow@fill Macro used for default fill macro^{→ P. 31}.

- #1: left shift
- #2: right shift
- #3: arrow start
- #4: arrow middle
- #5: arrow end
- #6: math style

```
462 \def\ovar@arrow@fill#1#2#3#4#5#6{  
463   $@\thickmuskip0mu\medmuskip\thickmuskip\thinmuskip\thickmuskip\relax%  
464   \mkern #1 mu\relax#6#3%  
465   \cleaders\hbox{$#6#4$}\hfill%  
466   #5\mkern #2 mu\relax$%  
467 }
```

Macros for fixed length arrows

Lengths declaration.

```
468 \newlength{\overarrowlength}  
469 \newlength{\overarrowthickness}  
470 \newlength{\overarrowsmallerthickness}  
471 \newlength{\ovar@tempdim}
```

\ovar@set@arrowlength Sets \overarrowlength^{→ P. 20}.

- #1: min length, in math units
- #2: math style
- #3: content

```
472 \def\ovar@set@arrowlength#1#2#3{  
473   \settowidth{\ovar@tempdim}{$@\thickmuskip\mskip #1 mu\relax$}%  
474   \settowidth{\overarrowlength}{$@\thickmuskip\mskip #2#3$}%  
475   \ifdim \overarrowlength < \ovar@tempdim \overarrowlength=\ovar@tempdim\fi%  
476 }
```

\ovar@set@arrowthickness

Sets \overarrowthickness^{→ P. 20} and \overarrowsmallerthickness^{→ P. 20}.

- #1: math style

Set to the default rule thickness of the current math style, normally given by \fontdimen 8 family 3. With unicode-math, use instead:

- \fontdimen 54 family 2 with XeTeX,
- \Umathoverbarrule with LuaTeX.

```

477 \def\ovar@rulethickness@fontdimen{8}
478 \def\ovar@rulethickness@family{3}
479 \def\ovar@set@arrowthickness#1{%
480   \ifx#1\displaystyle%
481     \overarrowthickness =
482       \fontdimen \ovar@rulethickness@fontdimen \textfont \ovar@rulethickness@family%
483     \overarrowsmallerthickness =
484       \fontdimen \ovar@rulethickness@fontdimen \scriptfont \ovar@rulethickness@family%
485   \else\ifx#1\textstyle%
486     \overarrowthickness =
487       \fontdimen \ovar@rulethickness@fontdimen \textfont \ovar@rulethickness@family%
488     \overarrowsmallerthickness =
489       \fontdimen \ovar@rulethickness@fontdimen \scriptfont \ovar@rulethickness@family%
490   \else\ifx#1\scriptstyle%
491     \overarrowthickness =
492       \fontdimen \ovar@rulethickness@fontdimen \scriptfont \ovar@rulethickness@family%
493     \overarrowsmallerthickness =
494       \fontdimen \ovar@rulethickness@fontdimen \scriptscriptfont \ovar@rulethickness@family%
495   \else%
496     \overarrowthickness =
497       \fontdimen \ovar@rulethickness@fontdimen \scriptscriptfont \ovar@rulethickness@family%
498     \overarrowsmallerthickness = \overarrowthickness%
499   \fi\fi\fi%
500 }

```

unicode-math with LuaTeX version.

```

501 \def\ovar@set@arrowthickness@UM@lua#1{%
502   \overarrowthickness = \Umathoverbarrule #1
503   \ifx#1\displaystyle%
504     \overarrowsmallerthickness = \Umathoverbarrule \textstyle%
505   \else\ifx#1\textstyle%
506     \overarrowsmallerthickness = \Umathoverbarrule \scriptstyle%
507   \else%
508     \overarrowsmallerthickness = \Umathoverbarrule \scriptscriptstyle%
509   \fi\fi%
510 }

```

Test which version to use.

```

511 \AddToHook{begindocument}[overarrows]
512 {%
513   \@ifpackageloaded{unicode-math-luatex}%
514   {%
515     \global\let\ovar@set@arrowthickness\ovar@set@arrowthickness@UM@lua
516   }%
517   {%
518     \@ifpackageloaded{unicode-math-xetex}%
519     {%
520       \gdef\ovar@rulethickness@fontdimen{54}%
521       \gdef\ovar@rulethickness@family{2}%
522     }%
523     {}%
524   }%
525 }

```

Stack macros

```
\ovar@stackover@@
\ovar@stackunder@@
```

Bases of all stack macros.

#1: min length, in math units

#2: vertical mode material before arrow

#3: vertical mode material after arrow

```

#4: arrow
#5: math style
#6: content

526 \def\ovar@stackover@@#1#2#3#4#5#6{\vbox{\ialign{##\cr\cr%
527   $#5\mskip #1 mu\relax$\cr\cr%
528   \noalign{\#2\nointerlineskip}#4\cr\cr%
529   \noalign{\#3\nointerlineskip}%
530   $\m@th\hfil#5#6\hfil$\cr\cr%
531   }%
532   }%
533 }
534 \def\ovar@stackunder@@#1#2#3#4#5#6{\vtop{\ialign{##\cr\cr%
535   $\m@th\hfil#5#6\hfil$\cr\cr%
536   \noalign{\#2\nointerlineskip}#4\cr\cr%
537   \noalign{\#3\nointerlineskip}%
538   $#5\mskip #1 mu\relax$\cr\cr%
539   }%
540   }%
541 }

\ovar@stackover@
Stack macros without min arrow length.
\ovar@stackunder@
#1: vertical mode material before arrow
#2: vertical mode material after arrow
#3: arrow macro
#4: math style
#5: content

542 \def\ovar@stackover@#1#2#3#4#5{\ovar@stackover@@{#1}{#2}{#3}{#4}{#5}}
543 \def\ovar@stackunder@#1#2#3#4#5{\ovar@stackunder@@{#1}{#2}{#3}{#4}{#5}}

\ovar@stackover@fill
Stack macros for extensible arrows.
\ovar@stackunder@fill
#1: min length, in math units
#2: vertical mode material before arrow
#3: vertical mode material after arrow
#4: arrow filler macro
#5: math style
#6: content

544 \def\ovar@stackover@fill#1#2#3#4#5#6{\ovar@stackover@@{#1}{#2}{#3}{#4#5}{#5}{#6}}
545 \def\ovar@stackunder@fill#1#2#3#4#5#6{\ovar@stackunder@@{#1}{#2}{#3}{#4#5}{#5}{#6}}

\ovar@stack@fill matches the macro \ovar@stackover@fill by default, or
\ovar@stackunder@fill with arrow underP.23.
546 \def\ovar@stack@fill{\ovar@stackover@fill}

\ovar@stackover@lens
\ovar@stackunder@lens
Stack macros for fixed-length arrows (these call \ovar@set@arrowlength and
\ovar@set@arrowthickness).
\ovar@stack@lens
#1: min length, in math units
#2: vertical mode material before arrow
#3: vertical mode material after arrow
#4: arrow content macro
#5: math style
#6: content

547 \def\ovar@stackover@lens#1#2#3#4#5#6{%
548   \ovar@set@arrowlength{#1}{#5}{#6}%
549   \ovar@set@arrowthickness{#5}%
550   \ovar@stackover@{#2}{#3}{#4}{#5}{#6}%
551 }

```

```

552 \def\ovar@stackunder@lens#1#2#3#4#5#6{%
553   \ovar@set@arrowlength{#1}{#5}{#6}%
554   \ovar@set@arrowthickness{#5}%
555   \ovar@stackunder@{#2}{#3}{#4}{#5}{#6}%
556 }

\ovar@stack@lens matches the macro \ovar@stackover@lens by default, or
\ovar@stackunder@lens with arrow underP.23..

```

557 \def\ovar@stack@lens{\ovar@stackover@lens}

Macro for commands creation

In the initial version, the commands names must be given as csname (without backslash). To harmonize the syntax with standard \NewDocumentCommand, define an argument processor so that both \NewOverArrowCommand{\myarrow} and \NewOverArrowCommand{myarrow} are accepted.

```

558 \ExplSyntaxOn
559 \cs_new_protected:Npn \__overarrows_processor_strip_escape_char:n #1
560   {
561     \regex_match:nnTF { ^\cC. } { #1 }
562     { \tl_set:Nx \ProcessedArgument { \cs_to_str:N #1 } }
563     { \tl_set:Nx \ProcessedArgument { #1 } }
564   }
565 \cs_new_eq:NN \ovar@cmdname@processor \__overarrows_processor_strip_escape_char:n
566 \ExplSyntaxOff

\DeclareOverArrowCommand
567 \NewDocumentCommand{\DeclareOverArrowCommand}{%
568   O{symb} >{\ovar@cmdname@processor} m m
569 }{%
570   \begingroup
571   \ovar@set@common
572   \ifcsdef{ovar@set@#1}{%
573     \csuse{ovar@set@#1}
574   }{%
575     \PackageError{overarrows}{Unknown method #1}%
576     {Try with 'symb', 'tikz', 'pstriks' or 'picture'}%
577   }
578   \ovar@set{#3}
579   \ifdef{\ovar@macro@arrow}{%
580     \ovar@set{no arrow macro hook}
581   }
582   \ifdef{\ovar@macro@stack}{%
583     \ovar@set{no stack macro hook}
584   }
585   \csxdef{ovar@#2@normal}{%
586     \noexpand\mathpalette{%
587       \expandonce{\ovar@macro@stack}{\expandonce{\ovar@macro@arrow}}%
588     }
589   }
590   \csxdef{ovar@#2@starred}{%
591     \noexpand\mathpalette{%
592       \noexpand\ovar@starversion{%
593         \expandonce{\ovar@macro@stack}{\expandonce{\ovar@macro@arrow}}%
594       }
595     }
596   }
597   \ifovar@detectsubscripts@%
598   \csgdef{ovar@#2@auto}##1{%
599     \Q_ifnextchar \ovar@subcmd {%
600       \csuse{ovar@#2@starred}{##1}%
601     }
602   }
603 }

```

```

601     }{%
602         \csuse{oivar@#2@normal}{##1}%
603     }%
604 }
605 \csgdef{#2}{%
606     @ifstar{\csuse{oivar@#2@starred}}{\csuse{oivar@#2@auto}}%
607 }
608 \else
609 \csgdef{#2}{%
610     @ifstar{\csuse{oivar@#2@starred}}{\csuse{oivar@#2@normal}}%
611 }
612 \fi
613 \ifovar@option@debug@
614 \PackageInfo{overarrows}{%
615     Meaning of \protect\oivar@#2@normal\MessageBreak
616     used for \@backslashchar#2:\MessageBreak%
617     \expandafter\meaning\csname oivar@#2@normal\endcsname}
618 \fi
619 \endgroup
620 }

\ProvideOverArrowCommand
621 \NewDocumentCommand{\ProvideOverArrowCommand}{%
622     O{symb} >{\oivar@cmdname@processor} m m
623 }{%
624     \ifcsdef{#2}{}{%
625         \DeclareOverArrowCommand[#1]{#2}{#3}
626     }
627 }

\NewOverArrowCommand
628 \NewDocumentCommand{\NewOverArrowCommand}{%
629     O{symb} >{\oivar@cmdname@processor} m m
630 }{%
631     \ifcsdef{#2}{}{%
632         \PackageError{overarrows}{Command \csname #2\endcsname already defined}%
633         {You have used \protect\NewOverArrowCommand\space with a command that
634          already has a definition. \MessageBreak%
635          Choose another name, or use instead \protect\DeclareOverArrowCommand.}%
636     }{%
637         \DeclareOverArrowCommand[#1]{#2}{#3}
638     }
639 }

\RenewOverArrowCommand
640 \NewDocumentCommand{\RenewOverArrowCommand}{%
641     O{symb} >{\oivar@cmdname@processor} m m
642 }{%
643     \ifcsundef{#2}{%
644         \PackageError{overarrows}{Command \csname #2\endcsname undefined}%
645         {You have used \protect\RenewOverArrowCommand\space with a command that was
646          never defined. \MessageBreak%
647          Check the requested name, or use instead \protect\NewOverArrowCommand.}%
648     }{%
649         \DeclareOverArrowCommand[#1]{#2}{#3}
650     }
651 }

```

Starred variant

```

\oivar@starversion
#1: definition (stack macro + arrow macro)
#2: math style
#3: content
652 \newsavebox\oivar@tempbox

```

```

653 \def\ovar@starversion#1#2#3{%
654   \sbox{\ovar@tempbox}{$\mathbf{#1}^{#2}\mathbf{#3}$}%
655   \usebox{\ovar@tempbox}%

```

Remove the extra space added by the arrow.

```

656 \settowidth{\ovar@tempdim}{$\mathbf{#2}\mathbf{#3}$}%
657 \kern\dimeaval{0.5\ovar@tempdim - 0.5\wd\ovar@tempbox}%
658 }

```

\vv vector command

```

\vv
\esvectvv Backup and redefinition of esvect \vvP.20 vector command.
\ifovar@option@esvect@
  \let\esvectvv\vv
  \undef\vv
  \NewOverArrowCommand{\vv}{esvect, middle config = relbareda}
\fi

```

Predefined commands

Declare predefined commands after `unicode-math` settings.

```

664 \AddToHook{begindocument}[overarrows]
665 {
\overrightarrow
666   \ifovar@option@overrightarrow@
667     \DeclareOverArrowCommand{\overrightarrow}{%
668       amsmath, middle config=relbar,
669       end=\ovar@rightarrow,
670       right arrow,
671     }
672   \fi
\underrightarrow
673   \ifovar@option@underrightarrow@
674     \DeclareOverArrowCommand{\underrightarrow}{%
675       amsmath, middle config=relbar,
676       end=\ovar@rightarrow,
677       right arrow,
678       arrow under,
679     }
680   \fi
\overleftarrow
681   \ifovar@option@overleftarrow@
682     \DeclareOverArrowCommand{\overleftarrow}{%
683       amsmath, middle config=relbar,
684       start=\ovar@leftarrow,
685       end=\relbar,
686       left arrow,
687     }
688   \fi
\underleftarrow
689   \ifovar@option@underleftarrow@
690     \DeclareOverArrowCommand{\underleftarrow}{%
691       amsmath, middle config=relbar,
692       start=\ovar@leftarrow,
693       end=\relbar,
694       left arrow,
695       arrow under,
696     }
697   \fi
\overleftrightarrow

```

```

698 \ifovar@option@overleftrightarrow@
699   \DeclareOverArrowCommand{\overleftrightarrow}{%
700     amsmath, middle config=relbar,
701     start=\ovar@leftarrow,
702     end=\ovar@rightarrow,
703     center arrow,
704   }
705 \fi
706 \underleftrightarrow
707   \ifovar@option@underleftrightarrow@
708   \DeclareOverArrowCommand{\underleftrightarrow}{%
709     amsmath, middle config=relbar,
710     start=\ovar@leftarrow,
711     end=\ovar@rightarrow,
712     center arrow,
713     arrow under,
714   }
715 \fi
716 \overrightharpoonup
717   \ifovar@option@overrightharpoonup@
718   \DeclareOverArrowCommand{\overrightharpoonup}{%
719     amsmath, middle config=relbar,
720     end=\rightharpoonup,
721     right arrow,
722   }
723 \fi
724 \underrightharpoonup
725   \ifovar@option@underrightharpoonup@
726   \DeclareOverArrowCommand{\underrightharpoonup}{%
727     amsmath, middle config=relbar,
728     end=\rightharpoonup,
729     right arrow,
730   }
731 \fi
732 \overrightharpoondown
733   \ifovar@option@overrightharpoondown@
734   \DeclareOverArrowCommand{\overrightharpoondown}{%
735     amsmath, middle config=relbar,
736     end=\rightharpoondown,
737     right arrow,
738   }
739 \fi
740 \underrightharpoondown
741   \ifovar@option@underrightharpoondown@
742   \DeclareOverArrowCommand{\underrightharpoondown}{%
743     amsmath, middle config=relbar,
744     end=\rightharpoondown,
745     right arrow,
746     arrow under,
747   }
748 \fi
749 \overleftharpoonup
750   \ifovar@option@overleftharpoonup@
751   \DeclareOverArrowCommand{\overleftharpoonup}{%
752     amsmath, middle config=relbar,
753     start=\leftharpoonup,
754     end=\relbar,
755     left arrow,
756   }
757 \fi
758 \underleftharpoonup
759   \ifovar@option@underleftharpoonup@
760   \DeclareOverArrowCommand{\underleftharpoonup}{%
761     amsmath, middle config=relbar,

```

```

756     start=\leftharpoonup,
757     end=\relbar,
758     left arrow,
759     arrow under,
760   }
761 \fi
\overleftharpoondown
762 \ifovar@option@overleftharpoondown@
763   \DeclareOverArrowCommand{\overleftharpoondown}{%
764     amsmath, middle config=relbar,
765     start=\leftharpoondown,
766     end=\relbar,
767     left arrow,
768   }
769 \fi
\underleftharpoondown
770 \ifovar@option@underleftharpoondown@
771   \DeclareOverArrowCommand{\underleftharpoondown}{%
772     amsmath, middle config=relbar,
773     start=\leftharpoondown,
774     end=\relbar,
775     left arrow,
776     arrow under,
777   }
778 \fi
\overbar
779 \ifovar@option@overbar@
780   \DeclareOverArrowCommand{\overbar}{%
781     amsmath, middle config=relbar,
782     start={\std@minus}, end={\std@minus},% \relbar is defined with \mathsm@sh
783     shift leftright=0,
784     space after arrow=-0.3ex,
785   }
786 \fi

```

With `unicode-math`, add `\vphantom{+}` to get the correct position.

```

\underbar
787 \ifovar@option@underbar@
788   \DeclareOverArrowCommand{\underbar}{%
789     amsmath, middle config=relbar,
790     start={\vphantom{+}\std@minus}, end={\std@minus},% \relbar is defined with \mathsm@sh
791     shift leftright=0,
792     arrow under,
793     space before arrow=-0.3ex,
794   }
795 \fi

```

End of `\AddToHook{begindocument}` hook.

```
796 }
```

Test macros

```
\ovar@testmathstyles
```

Tabular containing the output of a command for the four math styles and different patterns.

```

797 \newcommand{\ovar@testmathstyles}[2][]{%
798   \begingroup
799   \newcommand*{\ovar@row@teststyle}[1]{%
800     \$\displaystyle ##1\$\\
801     & \$\textstyle ##1\$\\
802     & \$\scriptstyle ##1\$\\
803     & \$\scriptscriptstyle ##1\$\\
804   }

```

```

805 }
806 \renewcommand*\{arraystretch}{1.5}
807 \begin{tabular}{0.95\linewidth}{@\{\extracolsep{\fill}\} cccc}
808   \hline
809   \footnotesize\textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash displaystyle}}}
810   & \footnotesize\textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash textstyle}}}
811   & \footnotesize\textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash scriptstyle}}}
812   & \footnotesize\textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash scriptscriptstyle}}}
813   \\
814   \hline
815   \ovar@row@teststyle{\csuse{#2}{v}}
816   \ovar@row@teststyle{\csuse{#2}{AB}}
817   \ovar@row@teststyle{\csuse{#2}{\mathrm{grad}}}
818   \ovar@row@teststyle{\csuse{#2}{my-long-vector}}
819   \IfValueT{#1}{\ovar@row@teststyle{\csuse{#2}{#1}}}
820   \\
821   \hline
822 \end{tabular}
823 \endgroup
824
\ovar@testkerning
825 \begingroup
826 \ifovar@option@subother@ \catcode `_=12 \fi
827 \ifovar@option@subactive@ \catcode `_=13 \fi
828 \gdef\ovar@testkerning#1{%
829   \begin{displaymath}
830     #1{t}_\{#1{u}_\{#1{v}\}\}
831     \qquad
832     #1{\imath}_0
833     \qquad
834     #1{v}_x + #1{v}_y + #1{v}_z
835     = v_x #1{\imath} + v_y #1{\jmath} + v_z #1{k}
836   \end{displaymath}
837 }
838 \endgroup
839 \TestOverArrow
840 \NewDocumentCommand{\TestOverArrow}{%
841   s o >{\ovar@cmdname@processor} m
842 }{%
843   \ifcsdef{#3}{}{%
844     \PackageWarning{overarrows}{Unknown name '#3' passed to
845       \protect\TestOverArrow}
846   }%
847   \IfBooleanTF{#1}{%
848     \noindent\framebox{%
849       \begin{minipage}{0.95\linewidth}
850         \centering
851         \noindent\textrt{\texttt{\textbackslash large}}
852         Test of \textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash#3}}} and \textrt{\texttt{\textbackslash texttt{\textbackslash textbackslash#3*}}}
853         macros
854         \bigskip\par
855         \textrt{\textbf{\texttt{\textbackslash texttt{\textbackslash textbackslash#3} for different math styles}}}
856         \smallskip\par
857         \ovar@testmathstyles[#2]{#3}%
858         \bigskip\par
859         \textrt{\textbf{\texttt{\textbackslash texttt{\textbackslash textbackslash#3} kerning}}}
860         \ovar@testkerning{\csuse{#3}}
861         \textrt{\textbf{\texttt{\textbackslash texttt{\textbackslash textbackslash#3*} kerning}}}
862         \ovar@testkerning{\csuse{#3*}}
863       \end{minipage}%
864     }%
865   }%
866 }

```

Index

Entries listed in the categories “commands”, “lengths”, and “internal macros” also include references to package implementation.

Package options
 `allcommands`, 15
 `debug`, 17
 `esvect`, 13
 `esvecta`, 14
 `esvectb`, 14
 `esvectc`, 14
 `esvectd`, 14
 `esvecte`, 14
 `esvectf`, 14
 `esvectg`, 14
 `esvecth`, 14
 `noesvect`, 14
 `old-arrows`, 16
 `overbar`, 15
 `overcommands`, 15
 `overleftarrow`, 15
 `overleftharpoondown`, 15
 `overleftharpoonup`, 15
 `overleftrightarrow`, 15
 `overrightarrow`, 15
 `overrightharpoondown`, 15
 `overrightharpoonup`, 15
 `pstarrows`, 17
 `pstricks`, 16
 `subactive`, 17
 `subother`, 17
 `subscripts`, 17
 `tikz`, 16
 `underbar`, 16
 `undercommands`, 15
 `underleftarrow`, 15
 `underleftharpoondown`, 16
 `underleftharpoonup`, 16
 `underleftrightarrow`, 16
 `underrightarrow`, 15
 `underrightharpoondown`, 16
 `underrightharpoonup`, 16

 `add path options` key, 27
 `add tikz options` key, 27
 `after arrow` key, 24
 `allcommands` package option, 15
 `amsmath` key, 26
 `arrow` key, 28
 `arrow macro` key, 30
 `arrow under` key, 23

 `arrows` key, 27
 `before arrow` key, 24
 `center arrow` key, 24
Commands
 `\DeclareOverArrowCommand`, 17, 46–50
 `\esvectvv`, 20, 48
 `\NewOverArrowCommand`, 17, 47, 48
 `\overbar`, 21, 34, 50
 `\overleftarrow`, 21, 34, 48
 `\overleftharpoondown`, 21, 34, 50
 `\overleftharpoonup`, 21, 34, 49
 `\overleftrightarrow`, 21, 34, 49
 `\overrightarrow`, 21, 34, 48
 `\overrightharpoondown`, 21, 34, 49
 `\overrightharpoonup`, 21, 34, 49
 `\ProvideOverArrowCommand`, 17, 47
 `\RenewOverArrowCommand`, 17, 47
 `\SetOverArrowsMethod`, 30, 37, 38, 40–42
 `\SetOverArrowsMethod*`, 30
 `\SetOverArrowsSubscriptCommand`, 30, 36
 `\smallermathstyle`, 19, 43
 `\TestOverArrow`, 18, 51
 `\TestOverArrow*`, 18
 `\underbar`, 22, 34, 50
 `\underleftarrow`, 22, 34, 48
 `\underleftharpoondown`, 22, 34, 50
 `\underleftharpoonup`, 22, 34, 49
 `\underleftrightarrow`, 22, 34, 49
 `\underrightarrow`, 22, 34, 48
 `\underrightharpoondown`, 22, 34, 49
 `\underrightharpoonup`, 22, 34, 49
 `\vv`, 20, 48
 `\vv*`, 20
 `\xjoinrel`, 19, 39, 43

 `debug` package option, 17
 `\DeclareOverArrowCommand`, 17
 `detect subscripts` key, 25

 `end` key, 25

```

esvect key, 26
esvect package option, 13
esvecta package option, 14
esvectb package option, 14
esvectc package option, 14
esvectd package option, 14
esvecte package option, 14
esvectf package option, 14
esvectg package option, 14
esvecth package option, 14
\esvectvv, 20

fill macro key, 31

geometry key, 28, 29

Internal macros
    \ifovar@detectsubscripts@, 33,
        46
    \ifovar@option@debug@, 33, 47
    \ifovar@option@esvect@, 33, 35,
        48
    \ifovar@option@oldarrows@, 33,
        35
    \ifovar@option@overbar@, 33, 50
    \ifovar@option@overleftarrow@,
        33, 48
    \ifovar@option@overleftharpoondown@,
        33, 50
    \ifovar@option@overleftharpoonup@,
        33, 49
    \ifovar@option@overrightarrow@,
        33, 49
    \ifovar@option@overrightarrow@,
        33, 48
    \ifovar@option@overrightharpoondown@,
        33, 49
    \ifovar@option@overrightharpoonup@,
        33, 49
    \ifovar@option@pstarrows@, 33,
        36
    \ifovar@option@pstricks@, 33, 35
    \ifovar@option@subactive@, 33,
        36, 51
    \ifovar@option@subother@, 33,
        36, 51
    \ifovar@option@tikz@, 33, 35
    \ifovar@option@underbar@, 33, 50
    \ifovar@option@underleftarrow@,
        33, 48
    \ifovar@option@underleftharpoondown@,
        33, 50
    \ifovar@option@underleftharpoonup@,
        33, 49
    \ifovar@option@underrightarrow@,
        33, 49
    \ifovar@option@underrightarrow@,
        33, 48
    \ifovar@option@underrightharpoondown@,
        33, 49
    \ifovar@option@underrightharpoonup@,
        33, 49
    \ovar@after@arrow, 37
    \ovar@arrow@end, 39
    \ovar@arrow@fill, 38, 43
    \ovar@arrow@middle, 38, 39
    \ovar@arrow@start, 38, 39
    \ovar@auto@middle, 36, 40
    \ovar@auto@trim@middle, 36, 40
    \ovar@before@arrow, 37
    \ovar@cmdname@processor, 46, 47,
        51
    \ovar@leftarrow, 35, 48, 49
    \ovar@length@min, 37
    \ovar@macro@arrow, 37, 46
    \ovar@macro@arrowfill, 38
    \ovar@macro@stack, 37, 46
    \ovar@picture@command, 42
    \ovar@picture@geometry, 42
    \ovar@picture@linethickness, 42
    \ovar@pstricks@command, 41, 42
    \ovar@pstricks@geometry, 41, 42
    \ovar@pstricks@linethickness,
        41, 42
    \ovar@pstricks@psset, 41, 42
    \ovar@rightarrow, 35, 40, 48, 49
    \ovar@row@teststyle, 50, 51
    \ovar@rulethickness@family, 44
    \ovar@rulethickness@fontdimen,
        44
    \ovar@set, 37, 38, 40–42, 46
    \ovar@set@arrowlength, 43, 45,
        46
    \ovar@set@arrowthickness, 44–46
    \ovar@set@arrowthickness@UM@lua,
        44
    \ovar@set@common, 46
    \ovar@shift@left, 38, 41, 42
    \ovar@shift@right, 38, 41, 42
    \ovar@stack@fill, 38, 45
    \ovar@stack@lens, 38, 46
    \ovar@stackover@, 45
    \ovar@stackover@0, 45
    \ovar@stackover@fill, 45
    \ovar@stackover@lens, 45, 46
    \ovar@stackunder@, 45, 46
    \ovar@stackunder@0, 45
    \ovar@stackunder@fill, 38, 45

```

```

\ovar@stackunder@lens, 38, 46
\ovar@starversion, 46, 48
\ovar@subcmd, 36, 46
\ovar@tempbox, 47, 48
\ovar@tempdim, 43, 48
\ovar@testkerning, 51
\ovar@testmathstyles, 50, 51
\ovar@tikz@command, 40, 41
\ovar@tikz@options, 40, 41
\ovar@tikz@path, 40, 41
\ovar@tikz@pathoptions, 40
\ovar@trim@end, 39
\ovar@trim@middle, 38, 39
\ovar@trim@start, 38, 39

Keys
  add path options, 27
  add tikz options, 27
  after arrow, 24
  amsmath, 26
  arrow, 28
  arrow macro, 30
  arrow under, 23
  arrows, 27
  before arrow, 24
  center arrow, 24
  detect subscripts, 25
  end, 25
  esvect, 26
  fill macro, 31
  geometry, 28, 29
  left arrow, 24
  line thickness, 27, 29
  middle, 25
  middle config, 26
  min length, 23
  no arrow macro hook, 31
  no stack macro hook, 31
  no trimming, 26
  path, 27
  path options, 27
  picture command, 29
  psset, 28
  pstricks command, 28
  right arrow, 24
  shift left, 23
  shift leftright, 24
  shift right, 23
  space after arrow, 24
  space before arrow, 24
  stack macro, 30
  start, 25
  thinner, 28, 29
  tikz command, 28

  tikz options, 27
  trim, 26
  trim end, 26
  trim middle, 25
  trim start, 25

  left arrow key, 24
Lengths
  \overarrowlength, 20, 41–43
  \overarrowsmallerthickness, 20,
    41–44
  \overarrowthickness, 20, 41–44
  line thickness key, 27, 29

  middle key, 25
  middle config key, 26
  min length key, 23

  \NewOverArrowCommand, 17
  no arrow macro hook key, 31
  no stack macro hook key, 31
  no trimming key, 26
  noesvect package option, 14

  old-arrows package option, 16
  \overarrowlength length, 20
  \overarrowsmallerthickness length,
    20
  \overarrowthickness length, 20
  \overbar, 21
  overbar package option, 15
  overcommands package option, 15
  \overleftarrow, 21
  overleftarrow package option, 15
  \overleftharpoondown, 21
  overleftharpoondown package option,
    15
  \overleftharpoonup, 21
  overleftharpoonup package option, 15
  \overleftrightarrow, 21
  overleftrightarrow package option, 15
  \overrightarrow, 21
  overrightarrow package option, 15
  \overrightharpoondown, 21
  overrightharpoondown package option,
    15
  \overrightharpoonup, 21
  overrightharpoonup package option, 15

  path key, 27
  path options key, 27
  picture command key, 29
  \ProvideOverArrowCommand, 17
  psset key, 28
  pstarrows package option, 17

```

```


pstricks package option, 16  

pstricks command key, 28  

\RenewOverArrowCommand, 17  

right arrow key, 24  

\SetOverArrowsMethod, 30  

\SetOverArrowsMethod*, 30  

\SetOverArrowsSubscriptCommand, 30  

shift left key, 23  

shift leftright key, 24  

shift right key, 23  

\smallermathstyle, 19  

space after arrow key, 24  

space before arrow key, 24  

stack macro key, 30  

start key, 25  

subactive package option, 17  

subother package option, 17  

subscripts package option, 17  

\TestOverArrow, 18  

\TestOverArrow*, 18  

thinner key, 28, 29  

tikz package option, 16  

tikz command key, 28  

tikz options key, 27  

trim key, 26  

trim end key, 26  

trim middle key, 25  

trim start key, 25  

\underline, 22  

underline package option, 16  

undercommands package option, 15  

\underleftarrow, 22  

underleftarrow package option, 15  

\underleftharpoondown, 22  

underleftharpoondown package option,  

    16  

\underleftharpoonup, 22  

underleftharpoonup package option, 16  

\underleftarrow, 22  

underleftarrow package option, 15  

\underrightharpoondown, 22  

underrightharpoondown package  

    option, 16  

\underrightharpoonup, 22  

underrightharpoonup package option,  

    16  

\vv, 20


```

Change History

v1.0		
General: Initial version	1	
v1.0.1		
General: Bug fix for under* options	34	
v1.1		
General: Support for non-standard subscripts	36, 46, 51	
v1.2		
General: Add option pstricks	33	
Add the method pstricks	41	
Allow backslash in command name	46	
Declare predefined commands		
	after <code>unicode-math</code> settings	48
	Fix esvect font sizes	35
	Get the correct rule thickness with <code>unicode-math</code>	44
	Remove useless <code>\AtBeginDocument</code>	36
	Use <code>\def</code> instead of <code>\let</code> for <code>\ovar@rightarrow</code> and <code>\ovar@leftarrow</code>	35
	Use <code>\harrowextender</code> , if available.	36
	Use boxes in starred variant for better performances	47