

# The **processkv** package\*

Jonathan Sauer  
`jonathan.sauer@gmx.de`

2004/08/09

## Abstract

This file describes the **processkv** package that provides macros for processing of key-value-lists by calling a user-defined macro for each key-value-pair.

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Using the package</b>	<b>1</b>
<b>3</b>	<b>Implementation</b>	<b>2</b>
3.1	Main macros . . . . .	2
3.2	Internal macros . . . . .	2

## 1 Introduction

The `keyval` package provides the possibility of specifying macro arguments as `key=value`, where `key` is one of previously defined keys. Sometimes it is necessary not to have to define the keys in advance, but to specify arbitrary keys which are then processed.

This package provides the macro `\processkeyvalues` that calls a user-defined macro for each key-value-pair.

This package makes use of some internal macros of the package `keyval`. I hope this will not break someday ...

## 2 Using the package

`\processkeyvalues` Usage: `\processkeyvalues {\langle keyvalue-list \rangle} {\langle macro \rangle}`.  
The main macro of this package. It calls `\langle macro \rangle` for each key-value-pair in `\langle keyvalue-list \rangle`. Macros in the list are not expanded.

---

\*This document corresponds to `processkv.sty` v1.0.1, dated 2004/08/09.

*<macro>* can be any macro with two parameters, i.e:

```
\def\testmacro#1#2{%
  \message{Key = '#1', value = '#2'}%
}
```

Or

```
\newcommand{\testmacro}[2]{%
  \message{Key = '#1', value = '#2'}%
}
```

## 3 Implementation

### 3.1 Main macros

**\processkeyvalues** Usage: `\processkeyvalues {<keyvalue-list>} {<macro>}`.  
Calls *<macro>* for each key-value-pair in the list. *<macro>* must have two parameters, *(key)* and *(value)*.

```
1 \def\processkeyvalues#1#2{%
2   \def\PKV@process{#2}%
3   \PKV@do#1,\relax,%
4 }
```

### 3.2 Internal macros

**\PKV@do** Processes the list.

```
5 \def\PKV@do#1{%
6   \ifx\relax#1\empty\else%
7   \PKV@split#1=\relax%
8   \expandafter\PKV@do\fi%
9 }
```

**\PKV@split** Processes a key-value-pair of the list. Uses some macros of the `keyval` package.

```
10 \def\PKV@split#1=#2=#3\relax{%
11   \KV@Csp@def\@tempa{#1}%
12   \ifx\@tempa\empty\else%
13   \KV@Csp@def\@tempb{#2}%
14   \expandafter\expandafter\expandafter\PKV@process%
15   \expandafter\expandafter\expandafter{\expandafter\@tempa}%
16   \expandafter}\expandafter{\@tempb}%
17 \fi%
18 }
```

## Change History

1.0.1 General: Mangled macronames corrected. . . . . 1

## Index

Numbers written in italic refer to the page where the corresponding entry is described, the ones underlined to the code line of the definition, the rest to the code lines where the entry is used.

<b>K</b>	<b>P</b>	<b>\PKV@split</b> . . . . . 7, <u>10</u>
\KV@sp@def . . . . . 11, 13	\PKV@do . . . . . 3, <u>5</u> \PKV@process . . . . . 2, 14	\processkeyvalues <u>1</u> , <u>1</u>